


Data Sheet	(preliminary)
<b>DR17-STD-STN</b>	
Conventional (dumb) charger for DR17 (or similar) standard form factor dumb batteries	
Issued :	30.03.00
	Page 1



Input Voltage		Output Voltage		Tolerance
minimum	maximum	minimum	maximum	
18 V AC	25 V AC		15.0 V DC	max. + / - 1 %

Input Power		Output Power		
Current	Power	Current	Power	Efficiency
800 mA	~ 14 W	800 mA	~ 12 W	> 90 %


Operating Temperature		Storage Temperature		Relative Humidity
minimum	maximum	minimum	maximum	
0 ° C	40 ° C	- 40 ° C	70 ° C	no condensation 95 %

Electrical Safety Specifications				
Short Circuit	Reverse Voltage	Input Current	Housing Isolation	Cables
continuous	continuous	none	none	n/a

Mechanical Specifications				
MTBF (MIL-HDBK217F)	Housing Material	Thermal	Over Temperature	Cable Mounting
20,000 hours	ABS plastic UL94-V0	EN60950	Dependent upon battery NTC	n/a

Housing Specifications				
Length	Width	Height	Weight (approx.)	Operation Display
100 mm	100 mm	40 mm	180 gm (exc. PSU)	red & green LEDs

Data Sheet	(preliminary)
<b>DR17-STD-STN</b>	
Conventional (dumb) charger for DR17 (or similar) standard form factor dumb batteries	
Issued :	30.03.00
	Page 2



### Connector and Cable Specifications

Input connector	Input cable length	Output connector	Output cable length	Cables
DIN 45323	n/a	AMP 787443-1	n/a	n/a


### Electro Magnetic Interference (EMI) Specifications

Conducted and Radiated Emissions	EN50082
Interference Immunity	EN50081

### Charger Specifications

Description	Parameter	minimum	typical	maximum
Charge Voltage		6.0 V	9.1 V	15.0 V
Primary charge termination	-dV	54 mV		90 mV
Quick charge current		550 mA	570 mA	600 mA
Back up charge termination	timer	3.8 hours		4.5 hours
Maintenance charge current		5 mA	8 mA	10 mA
Temperature cutoff (lower)	automatic switch to maintenance charge	8 ° C	10 ° C	
Temperature cutoff (upper)		41 ° C	45 ° C	48 ° C
Charge time DR17 (1800 mAh)			3.5 hours	

Data Sheet	(preliminary)
<b>DR17-STD-STN</b>	
Conventional (dumb) charger for DR17 (or similar) standard form factor dumb batteries	
Issued :	30.03.00
	Page 3



Battery Specifications				
Battery type	Cell chemistry	Nominal voltage	Typical capacity	Internal electronic
DR17	NiMH	7.2 V	1800 mAh	only safety components
please consult individual battery manufacturers data sheets for more explicit information				

Test Specifications				
Cold	Dry Heat	Damp Heat	Shock	Vibration
IEC68-2-1	IEC68-2-2	IEC68-2-3	IEC68-2-27 & -29 & -32	IEC68-2-6
all values quoted measured at 25 ° C unless otherwise stated				

Worldwide Approvals	
Norms met and certification attained	CE
Other norms adhered to and / or applied	89/336/EEC & 92/31/EEC

External Power Supply Specifications				
Output @ 0 mA	25 V AC		Output @ 1 A	18 V AC
country	minimum	maximum	frequency	approvals
USA	108 V AC	132 V AC	60 Hz	UL, CSA
Europe	207 V AC	253 V AC	50 Hz	CE, VDE, GS, ÖVE, KEMA, SEV, CEBC, SETI, UTE, DEMKO, NEMKO, SEMKO
UK	207 V AC	253 V AC	50 Hz	BATB, BSI