


100VAC Input/-12VDC (500mA) Output Non-Isolated AC/DC Converter BP5062A

Absolute Maximum Ratings

Parameter	Symbol	Limits	Unit
Input voltage	Vi	-190	V
Output current	lo	500	mA
ESD endurance	Vsurge	2	kV
Operating temperature range	Topr	-20 to +80	°C
Storage temperature range	Tstg	-25 to +105	c

Dimensions (Unit : mm)




Electrical Characteristics

Symbol	Min.	Тур.	Max.	Unit	Conditions
Vi	-113	-141	-180	V	DC (80 to 127VAC)
Vo	-11.0	-12.0	-13.0	V	Vi= -141V, lo=300mA
lo	0	-	500	mA	Vi= -141V *1
Vr	-	0.05	0.15	V	Vi= -113V to -170V, Io=300mA
VI	-	0.07	0.20	V	Vi= -141V, Io=0 to 300mA
Vp	_	0.05	0.15	Vp-p	Vi= -141V, lo=300mA *2
η	75	83	_	%	Vi= –141V, lo=500mA
	Vi Vo Io Vr VI Vp	Vi -113 Vo -11.0 Io 0 Vr - VI - Vp -	Vi -113 -141 Vo -11.0 -12.0 lo 0 - Vr - 0.05 VI - 0.07 Vp - 0.05	Vi -113 -141 -180 Vo -11.0 -12.0 -13.0 lo 0 - 500 Vr - 0.05 0.15 VI - 0.07 0.20 Vp - 0.05 0.15	Vi -113 -141 -180 V Vo -11.0 -12.0 -13.0 V lo 0 - 500 mA Vr - 0.05 0.15 V VI - 0.07 0.20 V Vp - 0.05 0.15 Vp-p

*1 Maximum output current varies depending on ambient temperature ; please refer to derating curve

*2 Spike noise is not included in output ripple voltage.

Application Circuit




Be sure to use fuse for safety.

Please verify operation and characteristics in the customer's circuit before actual usage. Ensure that the load current does not exceed the maximum rating.


External Component Specifications

FUSE: Fuse	Use a quick-acting fuse of 2A
C1: Input smoothing capacitor	Capacitance : 22 to 47μ F Rated voltage : 200V or higher Ripple current is 0.22Arms or greater.
C2: Noise reduction capacitor	Capacitance : 0.1μ F to 0.22μ F Rated voltage : 200V or higher Use a film or ceramic capacitor. Evaluate under actual operating conditions.
C3: Output smoothing capacitor	Capacitance : 220μ F to 820μ F Rated voltage : 25 V or higher, ESR is 0.15Ω max. Ripple current is 1.0Arms or greater. Evaluate under actual operating conditions.
D1: Rectifier diode	In the absolute maximum ratings, the reverse peak voltage should be 400V or higher, the average rectifying current should be 1A or higher, and the peak surge current should be 40A or higher. (Full-wave rectification can be used.)
L1: Choke coil	Coil for switching regulator. The inductance should be 470μ H, the rated direct current should be 1.0A or greater in order to prevent overheating or abnormal oscillation.
R1: Noise reduction resistor	10 to 22Ω 1/4W Determine the ideal value through actual testing.
ZNR: Varistor	A varistor is required to protect against lightning surges and static electricity.


Derating Curve
 Derating Curve



Conversion Efficiency



Load Regulation



Surface Temperature Increase

_	50	;	Surf	ace (Ta=	Ten 25°	nper C, V	atur 'i=-`	e In 141	crea V)	ase		
iemperature Hising ∆I (°C)	45											
⊲	40									-		
Ê.	40 35 30 25 20											
ř	25								\sim			
e l	20		_				\leq	<u> </u>				
La l	15					F				-		
ę.	10 5		\sim									
e	0	\geq										
	0) 5	0 10								50 50	00
				Ou	tput	Cu	ren	t 10(mA)			

Power Module Usage Precautions

Safety Precautions

- 1) The products are designed and manufactured for use in ordinary electronic equipment (i.e. AV/OA/ telecommunication/amusement equipment, home appliances). Please consult with the Company's (ROHM) sales staff if intended for use in devices requiring high reliability (e.g. medical/transport/ aircraft/spacecraft equipment, nuclear power/fuel controllers, automotive/safety devices) and whose malfunction may result in injury or death. In this case, failsafe measures must be taken, including the following:
 - [a] Installation of protection circuits in order to improve system safety
 - [b] Incorporation of redundant circuits in the case of single-circuit failure
- 2) The products are designed for use under normal conditions. Application in special environments can cause a deterioration in product performance. Therefore, verification and confirmation of product performance, prior to use, is recommended. The following environments are considered to be 'special':

 [a] Outdoors, exposed to direct sunlight or dust
 - [b] In contact with liquids, such as water, oils, chemicals, or organic solvents
 - [c] In areas where exposure to the sea air or corrosive gases (i.e. Cl₂, H₂S, NH₃, SO₂, NO₂) can occur
 - [d] In places where the products may be in contact with static electricity or electromagnetic waves
 - [e] In proximity to heat-producing items, plastic cords, or flammable materials
 - [f] In contact with sealing or coating products, such as resin
 - [g] In contact with unclean solder or exposed to water or water-soluble cleaning agents used after soldering
 - [h] In areas where dew condensation occurs
- 3) The products are not designed to be radiation resistant
- 4) The Company is not responsible for any problems resulting from use of the products under conditions not recommended herein.
- 5) The Company should be notified of any product safety issues. Moreover, product safety issues should be periodically monitored by the customer.

Application Notes

- 1) A sufficient margin must be allowed if changes are made to the peripheral circuit due to variations in the inherent tolerances of the external components as well as transient and static characteristics. In addition, please be aware that the Company has not conducted investigations on whether or not particular changes in the example application circuits would result in patent infringement.
- 2) The application examples, their constants, and other types of information contained herein are applicable only when the products are used in accordance with standard methods.

Therefore, if mass production is intended, sufficient consideration to external conditions must be made.

Notes Regarding Industrial Property

- 1) The specifications included herein contain information related to the Company's industrial property. Their use other than pertaining to the relevant products is forbidden. Duplication and/or disclosure to a third party without express written permission is strictly prohibited.
- 2) Product information and data, including application examples, contained in the specifications are for reference purposes only; the Company does not guarantee the industrial/intellectual property rights or any other rights of a third party. Accordingly, the Company shall not bear responsibility for:
 [a] Infringement of the intellectual property rights of a third party
 [b] Problems arising from the use of the products listed herein
- 3) The Company prohibits the purchaser from exercising or using the intellectual/industrial property rights or any rights belonging to or are controlled by the Company, other than the right to use, sell, or dispose of the products.

Power Module Usage Precautions

Safety Precautions

- 1) The products are designed and manufactured for use in ordinary electronic equipment (i.e. AV/OA/ telecommunication/amusement equipment, home appliances). Please consult with the Company's (ROHM) sales staff if intended for use in devices requiring high reliability (e.g. medical/transport/ aircraft/spacecraft equipment, nuclear power/fuel controllers, automotive/safety devices) and whose malfunction may result in injury or death. In this case, failsafe measures must be taken, including the following:
 - [a] Installation of protection circuits in order to improve system safety
 - [b] Incorporation of redundant circuits in the case of single-circuit failure
- 2) The products are designed for use under normal conditions. Application in special environments can cause a deterioration in product performance. Therefore, verification and confirmation of product performance, prior to use, is recommended. The following environments are considered to be 'special':

 [a] Outdoors, exposed to direct sunlight or dust
 - [b] In contact with liquids, such as water, oils, chemicals, or organic solvents
 - [c] In areas where exposure to the sea air or corrosive gases (i.e. Cl₂, H₂S, NH₃, SO₂, NO₂) can occur
 - [d] In places where the products may be in contact with static electricity or electromagnetic waves
 - [e] In proximity to heat-producing items, plastic cords, or flammable materials
 - [f] In contact with sealing or coating products, such as resin
 - [g] In contact with unclean solder or exposed to water or water-soluble cleaning agents used after soldering
 - [h] In areas where dew condensation occurs
- 3) The products are not designed to be radiation resistant
- 4) The Company is not responsible for any problems resulting from use of the products under conditions not recommended herein.
- 5) The Company should be notified of any product safety issues. Moreover, product safety issues should be periodically monitored by the customer.

Application Notes

- 1) A sufficient margin must be allowed if changes are made to the peripheral circuit due to variations in the inherent tolerances of the external components as well as transient and static characteristics. In addition, please be aware that the Company has not conducted investigations on whether or not particular changes in the example application circuits would result in patent infringement.
- 2) The application examples, their constants, and other types of information contained herein are applicable only when the products are used in accordance with standard methods.

Therefore, if mass production is intended, sufficient consideration to external conditions must be made.

Notes Regarding Industrial Property

- 1) The specifications included herein contain information related to the Company's industrial property. Their use other than pertaining to the relevant products is forbidden. Duplication and/or disclosure to a third party without express written permission is strictly prohibited.
- 2) Product information and data, including application examples, contained in the specifications are for reference purposes only; the Company does not guarantee the industrial/intellectual property rights or any other rights of a third party. Accordingly, the Company shall not bear responsibility for:
 [a] Infringement of the intellectual property rights of a third party
 [b] Problems arising from the use of the products listed herein
- 3) The Company prohibits the purchaser from exercising or using the intellectual/industrial property rights or any rights belonging to or are controlled by the Company, other than the right to use, sell, or dispose of the products.

	copying or reproduction of this document, in part or in whole, is permitted without the sent of ROHM Co.,Ltd.
The	content specified herein is subject to change for improvement without notice.
"Pro	content specified herein is for the purpose of introducing ROHM's products (hereinafte oducts"). If you wish to use any such Product, please be sure to refer to the specifications ch can be obtained from ROHM upon request.
illus	mples of application circuits, circuit constants and any other information contained herein trate the standard usage and operations of the Products. The peripheral conditions mus aken into account when designing circuits for mass production.
Hov	at care was taken in ensuring the accuracy of the information specified in this document vever, should you incur any damage arising from any inaccuracy or misprint of such rmation, ROHM shall bear no responsibility for such damage.
exa imp othe	technical information specified herein is intended only to show the typical functions of an mples of application circuits for the Products. ROHM does not grant you, explicitly o licitly, any license to use or exercise intellectual property or other rights held by ROHM and er parties. ROHM shall bear no responsibility whatsoever for any dispute arising from the of such technical information.
equ	Products specified in this document are intended to be used with general-use electronic ipment or devices (such as audio visual equipment, office-automation equipment, commution devices, electronic appliances and amusement devices).
The	Products specified in this document are not designed to be radiation tolerant.
	le ROHM always makes efforts to enhance the quality and reliability of its Products, a duct may fail or malfunction for a variety of reasons.
aga failu sha	ase be sure to implement in your equipment using the Products safety measures to guard inst the possibility of physical injury, fire or any other damage caused in the event of the ire of any Product, such as derating, redundancy, fire control and fail-safe designs. ROHM Il bear no responsibility whatsoever for your use of any Product outside of the prescribed pe or not in accordance with the instruction manual.
sys may inst con of t	Products are not designed or manufactured to be used with any equipment, device o tem which requires an extremely high level of reliability the failure or malfunction of which result in a direct threat to human life or create a risk of human injury (such as a medica rument, transportation equipment, aerospace machinery, nuclear-reactor controller, fuel- troller or other safety device). ROHM shall bear no responsibility in any way for use of any he Products for the above special purposes. If a Product is intended to be used for any h special purpose, please contact a ROHM sales representative before purchasing.
be	bu intend to export or ship overseas any Product or technology specified herein that may controlled under the Foreign Exchange and the Foreign Trade Law, you will be required to ain a license or permit under the Law.



Thank you for your accessing to ROHM product informations. More detail product informations and catalogs are available, please contact us.

ROHM Customer Support System

http://www.rohm.com/contact/