



Preliminary Data Sheet


Features

- For IF applications
- Typical 3 dB bandwidth of 0.7 MHz
- High attenuation
- Single-ended operation
- Ceramic Surface Mount Package (SMP)
- Replaces Sawtek P/N 851542 (BW 3dB = 0.5 MHz)
- Hermetic
- RoHS compliant (2002/95/EC), Pb-free 




Package

Surface Mount 24.60 x 9.00 x 2.31 mm



Pin Configuration

Bottom View



Pin No.	Description
1	Input return
5	Output
6	Output return
10	Input
2,3,4,7,8,9	Case ground

Dimensions shown are nominal in millimeters
 All tolerances are $\pm 0.15\text{mm}$ except overall
 length and width $\pm 0.20\text{mm}$

Body: Al_2O_3 ceramic
 Lid: Kovar, Ni plated
 Terminations: Au plating 0.5 - 1.0 μm ,
 over a 2 - 6 μm Ni plating

Preliminary Data Sheet

Electrical Specifications ⁽¹⁾


Operating Temperature Range: ⁽²⁾ 0 to +70 °C

Parameter ⁽³⁾	Minimum	Typical	Maximum	Unit
Center Frequency	-	70	-	MHz
Minimum Insertion Loss	-	21.3	22	dB
Upper 1 dB Point ⁽⁴⁾	70.155	70.205	-	MHz
Lower 1 dB Point ⁽⁴⁾	-	69.795	69.845	MHz
Upper 3 dB Point ⁽⁴⁾	70.31	70.35	-	MHz
Lower 3 dB Point ⁽⁴⁾	-	69.65	69.69	MHz
Upper 40 dB Point ⁽⁴⁾	-	70.815	70.836	MHz
Lower 40 dB Point ⁽⁴⁾	69.165	69.185	-	MHz
Absolute Attenuation				
10 - 68 MHz	60	62	-	dB
72 - 85 MHz	45	55	-	dB
85 - 108 MHz	60	62	-	dB
108 - 140 MHz	50	55	-	dB
140 - 200 MHz	60	62	-	dB
Amplitude Variation				
69.85 - 70.15 MHz	-	0.8	1	dB p-p
Phase Ripple				
69.85 - 70.15 MHz	-	1.2	3	deg p-p
Group Delay Variation				
69.85 - 70.15 MHz	-	100	200	nsec p-p
Source Impedance: ⁽⁶⁾	-	50	-	Ω
Load Impedance: ⁽⁶⁾	-	50	-	Ω

Notes:







1. All specifications are based on the test circuit shown below
2. In production, devices will be tested at room temperature to a guardbanded specification to ensure electrical compliance over temperature
3. Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances
4. All attenuation measurements are measured relative to minimum insertion loss
5. This is the optimum impedance in order to achieve the performance shown

Test Circuit:



Preliminary Data Sheet


Typical Performance (at +25°C)




Preliminary Data Sheet

Matching Schematics

Actual matching values may vary due to PCB layout and parasitics




Marking





The date code consists of: day of the current year (Julian, 3 digits), last digit of the year (1 digit) and hour (2 digits)

PCB Footprint



This footprint represents a recommendation only
Dimensions shown are nominal in millimeters

Tape and Reel



Dimensions shown are nominal in millimeters
Packaging quantity: 1000 units/reel


Preliminary Data Sheet

Maximum Ratings


Parameter	Symbol	Minimum	Maximum	Unit
Operating Temperature Range	T	0	+70	°C
Storage Temperature Range	T _{stg}	-40	+85	°C
RF Power	P _{in}	-	+10	dBm

Important Notes

Warnings

- Electrostatic Sensitive Device (ESD) 
- Avoid ultrasonic exposure

RoHS Compliance

- This product complies with EU directive 2002/95/EC (RoHS) 

Solderability

- Compatible with JEDEC J-STD-020C **Pb**-free process, **260°C** peak reflow temperature ([see soldering profile](#))

Links to Additional Technical Information

[PCB Layout Tips](#)
[Qualification Flowchart](#)
[Soldering Profile](#)
[S-Parameters](#)
[RoHS Information](#)
[Other Technical Information](#)

Sawtek's liability is limited only to the Surface Acoustic Wave (SAW) component(s) described in this data sheet. Sawtek does not accept any liability for applications, processes, circuits or assemblies, which are implemented using any Sawtek component described in this data sheet.

Contact Information



PO Box 609501
Orlando, FL 32860-9501
USA

Phone: +1 (407) 886-8860
Fax: +1 (407) 886-7061
Email: custservice@sawtek.com
Web: www.sawtek.com

Or contact one of our worldwide
Network of [sales offices](#),
[representatives or distributors](#)