

Transmitter for Digital Signals Type G 3420 5502



- 8-channel transmitter
- 8 opto-isolated voltage inputs:
10 to 265 VAC/DC
- H4-housing
- For mounting on DIN-rail (EN 50022)
- LED-indications for supply, input activated and Dupline® carrier
- AC or DC power supply
- Channel coding by GAP 1605

Product Description

Dupline® transmitter for external supply. Detects the signals from 8 devices with voltage outputs of up to 265 VAC/DC, e.g. the presence of mains supply to machinery.

Ordering Key

G 3420 5502 024

Type: Dupline®
H4-housing
Transmitter
No. of channels
Input type
Power supply

Type Selection

Supply	Ordering no. 8 channels 10 to 265 VAC/DC
24 VAC	G 3420 5502 024
115 VAC	G 3420 5502 115
230 VAC	G 3420 5502 230
10 to 30 VDC	G 3420 5502 800

Input Specifications

Inputs	8 voltage-type 10 to 265 VAC/DC 45 to 400 Hz ≤ 1 VAC/DC ≥ 10 VAC/DC Typ. 10 mA (V_{BB} 10-18 VDC) lower at other input voltages
Input voltage range V_{BB}	Yes
Frequency range on AC	≤ 450 mA (at V_{BB} = 265 VDC)
Input voltage for signal "0"	≤ 1 pulse train + 3 ms
Input voltage for signal "1"	≤ 1 pulse train + 50 ms
Input current for signal "1"	≤ 25 m
Input current limiter	≥ 4 kVAC (rms)
Inrush current	
Operating time for signal "1"	
Operating time for signal "0"	
Cable length	
Dielectric voltage Inputs - Dupline®	

Supply Specifications

Power supply AC types	Overvoltage cat. III (IEC 60664)
Rated operational voltage through term. 21 & 22	230 VAC, ±15% 115 VAC, ±15% 24 VAC, ±15%
Frequency	45 to 65 Hz
Voltage interruption	≤ 40 ms
Rated operational power	Typ. 4.5 VA
Power dissipation	≤ 8 W
Rated impulse withstand voltage	4 kV 2.5 kV 800 V
Dielectric voltage Supply - Dupline® Supply - Inputs	≥ 4 kVAC (rms) ≥ 4 kVAC (rms)
Power supply DC type	Overvoltage cat. III (IEC 60664)
Rated operational voltage through term. 21 & 22	10 to 30 VDC (ripple included)
Ripple	≤ 3 V
Reverse-polarity protection	Yes
Power consumption	< 1 W
Power dissipation	≤ 5.5 W
Inrush current	≤ 1 A
Rated impulse withstand voltage	800 V
Dielectric voltage Supply - Dupline® Supply - Inputs	≥ 200 VAC (rms) ≥ 4 kVAC (rms)

General Specifications

Power ON delay	Typ. 2 s
Power OFF delay	≤ 1 s
Output OFF delay upon loss of Dupline® carrier	≤ 20 ms
Indication for Supply ON Input activated Dupline® carrier	LED, green LED, red LED, yellow
Environment Degree of protection Pollution degree Operating temperature Storage temperature	IP 20 3 (IEC 60664) -20° to +50°C (-4° to +122°F) -50° to +85°C (-58° to +185°F)
Humidity (non-condensing)	20 to 80%
Mechanical resistance Shock Vibration	15 G (11 ms) 2 G (6 to 55 Hz)
Dimensions Material (see "Technical Information")	H4-housing
Weight	250 g

Mode of Operation

8-channel transmitter with 8 voltage inputs (10 to 265 VAC/DC).

Each input may be coded individually by means of the code programmer GAP 1605. For details, please refer to the respective data sheet.

When a voltage (10 to 265 VAC/DC) is applied to terminal 25 (input 1), the transmitter transmits on the channel coded for input 1.

Whenever the voltage of the input is < 1 V, the transmitter

stops transmitting on the respective channel.


Notes:

- Terminals 4 and 24 are internally connected.
- Terminals 4 and 24 are common (minus).


Input connections

Input 1:	terminals 24 & 25
Input 2:	terminals 24 & 26
Input 3:	terminals 24 & 27
Input 4:	terminals 24 & 28
Input 5:	terminals 4 & 5
Input 6:	terminals 4 & 6
Input 7:	terminals 4 & 7
Input 8:	terminals 4 & 8


Operation Diagram



Wiring Diagram



Dimensions (mm)



Accessories

DIN-rail FMD 411

For further information, see "Accessories".