



**HIGH REPEATABILITY,  
BROADBAND TO-5 RELAYS  
DPDT**



SERIES	RELAY TYPE
RF300	Repeatable, RF relay
RF300D	Repeatable, RF relay with internal diode for coil transient suppression
RF300DD	Repeatable, RF relay with internal diodes for coil transient suppression and polarity reversal protection
RF303	Sensitive, repeatable, RF relay
RF303D	Sensitive, repeatable, RF relay with internal diode for coil transient suppression
RF303DD	Sensitive, repeatable, RF relay with internal diodes for coil transient suppression and polarity reversal protection

**DESCRIPTION**

The ultraminiature RF300 and RF303 relays are designed to provide improved RF signal switching repeatability over the frequency range. These relays are engineered for use in RF attenuator, RF switch matrices, ATE and other applications that require dependable high frequency signal fidelity and performance.

The RF300 and RF303 feature:

- High repeatability
- Broader bandwidth
- Metal enclosure for EMI shielding
- High isolation between control and signal paths
- High resistance to ESD


The following unique construction features and manufacturing techniques provide excellent robustness to environmental extremes and overall high reliability:

- Uniframe motor design provides high magnetic efficiency and mechanical rigidity
- Minimum mass components and welded construction provide maximum resistance to shock and vibration
- Advanced cleaning techniques provide maximum assurance of internal cleanliness
- Hermetically sealed
- Solder Dipped Leads, (RoHS compliant solder option available)






The Series RF300D/RF303D and RF300DD/RF303DD relays have internal discrete silicon diodes for coil suppression and polarity reversal protection. This hybrid package reduces required PC board floor space by reducing the number of external components needed to drive the relay.

ENVIRONMENTAL AND PHYSICAL SPECIFICATIONS		
Temperature (Ambient)	Storage	-65°C to +125°C
	Operating	-55°C to +85°C
Vibration (General Note I)		10 g's to 500 Hz
Shock (General Note I)		30 g's, 6ms half sine
Enclosure		Hermetically sealed
Weight	RF300	0.09 oz. (2.55g) max.
	RF303	0.16 oz. (4.5g) max.

**INTERNAL CONSTRUCTION**



**SERIES RF300/RF303**  
TYPICAL RF CHARACTERISTICS (See RF Notes)





**RF NOTES**

- Test conditions:
  - Fixture: .031" copper clad, reinforced PTFE, RT/duroid® 6002 with SMA connectors. (RT/duroid® is a registered trademark of Rogers Corporation.)
  - Room ambient temperature.
  - Terminals not tested were terminated with 50-ohm load.
  - Contact signal level: -10 dBm.
  - No. of test samples: 4.
- Data presented herein represents typical characteristics and is not intended for use as specification limits.
- Data is per pole, except for pole-to-pole data.
- Data is the average from readings taken on all open contacts.
- Data is the average from readings taken on poles with coil energized and de-energized.
- Data is the average from readings taken on all closed contacts.
- Test fixture effect de-embedded from frequency and time response data.

**SERIES RF300/RF303**  
TYPICAL RF REPEATABILITY PERFORMANCE (See RF Notes 1,2 and 3)

1 Million Cycle Repeatability  $\pm 0.1$  dB from DC to 3GHz



**RF NOTES**

1. One million cycle repeatability data is based upon 396 observations with an average repeatability  $\pm 0.033$  dB and a range of  $\pm 0.093$  dB.
2. Repeatability of attenuation values were obtained from tests conducted in a 20 dB attenuator network with a 0 dBm input signal.
3. Relay operates at frequencies higher than 3 GHz with reduced RF performance characteristics.
4. Curves were developed from tests performed on a 0.031" copper clad, reinforced PTFE circuit board at 20°C (ref). The unutilized contacts were terminated in 50 ohms; characteristic impedance of measuring equipment is 50 ohms. The relays were mounted flush to the circuit board ground plane without the relay header soldered to the ground plane.

**SERIES RF300/RF303**  
**GENERAL ELECTRICAL SPECIFICATIONS (@25°C)**


Contact Arrangement	2 Form C (DPDT)	
Rated Duty	Continuous	
Contact Resistance	0.15 $\Omega$ max.	
Contact Load Rating	Resistive: 1Amp/28Vdc Low level: 10 to 50 $\mu$ A @ 10 to 50 mV	
Contact Life Ratings	10,000,000 cycles (typical) at low level	
Coil Operating Power	RF300: 450 mW typical at nominal rated voltage RF303: 200 mW typical at nominal rated voltage	
Operate Time	RF300: 4.0 mS max. RF303: 6.0 mS max.	
Release Time	RF300: 3.0 mS max.	RF300D, RF300DD: 6.0 mS max.
	RF303: 3.0 mS max.	RF303D, RF303DD: 7.5 mS max.
Intercontact Capacitance	0.4 pf typical	
Insulation Resistance	1,000 M $\Omega$ min. between mutually isolated terminals	
Dielectric Strength	350 Vrms (60 Hz) @ atmospheric pressure	
Negative Coil Transient (Vdc)	RF300D/RF303D,RF300DD/RF303DD	2.0 max
Diode P.I.V. (Vdc)	RF300D/RF303D,RF300DD/RF303DD	60 min.

**DETAILED ELECTRICAL SPECIFICATIONS (@25°C)**


BASE PART NUMBERS (RF300, RF300D, RF300DD)		RF300-5 RF300D-5 RF300DD-5	RF300-12 RF300D-12 RF300DD-12
Coil Voltage, Nominal (Vdc)		5.0	12.0
Coil Resistance (Ohms $\pm$ 20%)	RF300, RF300D	50	390
	RF300DD (General Note II)	39	390
Coil Current (mAdc@ 25 °C) (RF300DD Series)	Min.	93.2	25.6
	Max.	128.2	32.8
Pick-up Voltage (Vdc max.)	RF300, RF300D, RF300DD	3.6	9.0

BASE PART NUMBERS (RF303, RF303D, RF303DD)		RF303-5 RF303D-5 RF303DD-5	RF303-12 RF303D-12 RF303DD-12
Coil Voltage, Nominal (Vdc)		5.0	12.0
Coil Resistance (Ohms $\pm$ 20%)	RF303, RF303D	100	850
	RF303DD (General Note II)	64	850
Coil Current (mAdc@ 25 °C) (RF303DD Series)	Min.	56.8	11.7
	Max.	78.1	15.0
Pick-up Voltage (Vdc max.)	RF303, RF303D, RF303DD	3.6	9.0

**SERIES RF300/RF303  
OUTLINE DIMENSIONS**




**SCHEMATIC DIAGRAMS**



**NOTES:**

1. DIMENSIONS ARE IN INCHES, METRIC EQUIVALENTS SHOWN IN [ ].
2. POSITIONS 5 AND 10 ARE FOR UNINSULATED CASE GROUND OPTIONS.
3. NO PROTRUSION BELOW BOTTOM OF HEADER WHEN GROUND PINS ARE INSTALLED
4. TO ORDER THE CASE GROUND OPTION, AFTER THE SERIES DESIGNATOR, ADD "Y" TO THE PART NUMBER FOR POSITION 5 OR "Z" TO THE PART NUMBER FOR POSITION 10.

**Teledyne Part Numbering System for RF300/RF303 Relays**



General Note: Parts ordered without suffix may be supplied with Solder-Coated or Gold-Plated leads

<sup>1</sup> Parts ordered with Solder-Coated leads will have (Sn60/Pb40)


<sup>2</sup> Parts ordered with RoHS Solder-Coated leads will have (Sn99.3/Cu0.7)

**GENERAL NOTES**

- Relays will exhibit no contact chatter in excess of 10 μsec or transfer in excess of 1 μsec.
- For reference only. Coil resistance not directly measurable at relay terminals due to internal series diode.


**SERIES RF300/RF303**  
**TYPICAL SIGNAL INTEGRITY CHARACTERISTICS**

Normally Closed (Typ.)



Eye Height	Eye Width	SNR	Jitter <sub>p-p</sub>
254.7 mV	90.38 ps	18.52	8.44 ps

Normally Open (Typ.)



Eye Height	Eye Width	SNR	Jitter <sub>p-p</sub>
250.9 mV	88.21 ps	16.84	8.00 ps

**PATTERN GENERATOR SETTINGS**

- 10 Gbps Random Pulse Pattern Generator
- $2^{31} - 1$  PRBS signal
- PRBS output of 300 mV<sub>p-p</sub> (nominal)
- RF PCB effect (negligible) not removed from measurement
- Data shown is typical of both poles