

2nd Generation thinQ!TM SiC Schottky Diode


Features

- Revolutionary semiconductor material - Silicon Carbide
- Switching behavior benchmark
- No reverse recovery/ No forward recovery
- No temperature influence on the switching behavior
- High surge current capability
- Pb-free lead plating; RoHS compliant
- Qualified according to JEDEC¹⁾ for target applications
- Breakdown voltage tested at 20mA²⁾
- Optimized for high temperature operation

Product Summary

| | | |
|----------|-----|----|
| V_{DC} | 600 | V |
| Q_c | 8 | nC |
| I_F | 4 | A |

PG-TO252



thinQ! 2G Diode specially designed for fast switching applications like:

- SMPS e.g.; CCM PFC; typ P_{out} = 400 - 800W
- Motor Drives; Solar applications; UPS

| Type | Package | Marking | Pin 1 | Pin 2 | Pin 3 |
|-----------|----------|---------|-------|-------|-------|
| IDD04S60C | PG-TO252 | D04S60C | n.c. | A | C |

Maximum ratings

| Parameter | Symbol | Conditions | Value | Unit |
|---|----------------|---|-------------|------------------|
| Continuous forward current | I_F | $T_C < 130\text{ °C}$ | 4 | A |
| | | $T_C < 100\text{ °C}$ | 6 | |
| RMS forward current | $I_{F,RMS}$ | $f = 50\text{ Hz}$ | 5.6 | |
| Surge non-repetitive forward current, sine halfwave | $I_{F,SM}$ | $T_C = 25\text{ °C}, t_p = 10\text{ ms}$ | 32.6 | |
| Repetitive peak forward current | $I_{F,RM}$ | $T_j = 150\text{ °C}, T_C = 100\text{ °C}, D = 0.1$ | 19.6 | |
| Non-repetitive peak forward current | $I_{F,max}$ | $T_C = 25\text{ °C}, t_p = 10\text{ }\mu\text{s}$ | 200 | |
| i^2t value | $\int i^2 dt$ | $T_C = 25\text{ °C}, t_p = 10\text{ ms}$ | 5.3 | A ² s |
| Repetitive peak reverse voltage | V_{RRM} | | 600 | V |
| Diode dv/dt ruggedness | dv/dt | $V_R = 0 \dots 480\text{ V}$ | 50 | V/ns |
| Power dissipation | P_{tot} | $T_C = 25\text{ °C}$ | 42 | W |
| Operating and storage temperature | T_j, T_{stg} | | -55 ... 175 | °C |

| Parameter | Symbol | Conditions | Values | | | Unit |
|-----------|--------|------------|--------|------|------|------|
| | | | min. | typ. | max. | |

Thermal characteristics

| | | | | | | |
|--|------------|---|---|---|-----|-----|
| Thermal resistance, junction - case | R_{thJC} | | - | - | 3.6 | K/W |
| Thermal resistance, junction - ambient | R_{thJA} | SMD version, device on PCB, minimal footprint | - | - | 75 | |
| | | SMD Version, device on PCB, 6 cm ² cooling ³⁾ | - | - | 50 | |
| Soldering temperature reflowsoldering | T_{sold} | reflow MSL 3 | - | - | 260 | °C |

Electrical characteristics, at $T_j=25\text{ °C}$, unless otherwise specified
Static characteristics

| | | | | | | |
|-----------------------|----------|---------------------------------------|-----|-----|-----|----|
| DC blocking voltage | V_{DC} | $I_R=0.05\text{ mA}$ | 600 | - | - | V |
| Diode forward voltage | V_F | $I_F=4\text{ A}, T_j=25\text{ °C}$ | - | 1.7 | 1.9 | |
| | | $I_F=4\text{ A}, T_j=150\text{ °C}$ | - | 2 | 2.4 | |
| | | $I_F=_\text{A}, T_j=25\text{ °C}$ | | 1.9 | 2.1 | |
| | | $I_F=_\text{A}, T_j=150\text{ °C}$ | | 2.3 | 2.9 | |
| Reverse current | I_R | $V_R=600\text{ V}, T_j=25\text{ °C}$ | - | 0.5 | 50 | μA |
| | | $V_R=600\text{ V}, T_j=150\text{ °C}$ | - | 2 | 500 | |

AC characteristics

| | | | | | | |
|------------------------------|-------|---|---|-----|-----|----|
| Total capacitive charge | Q_c | $V_R=400\text{ V}, I_F \leq I_{F,max}, di_F/dt=200\text{ A}/\mu\text{s}, T_j=150\text{ °C}$ | - | 8 | - | nC |
| Switching time ⁴⁾ | t_c | | - | - | <10 | ns |
| Total capacitance | C | $V_R=1\text{ V}, f=1\text{ MHz}$ | - | 130 | - | pF |
| | | $V_R=300\text{ V}, f=1\text{ MHz}$ | - | 20 | - | |
| | | $V_R=600\text{ V}, f=1\text{ MHz}$ | - | 20 | - | |

¹⁾ J-STD20 and JESD22

²⁾ All devices tested under avalanche conditions, for a time periode of 5ms at 20 mA.

³⁾ Device on 40mm*40mm*1.5mm epox PCB FR4 with 6cm² (one layer, 70μm thick) copper area for drain connection. PCB is vertikal with out blown air.


⁴⁾ t_c is the time constant for the capacitive displacement current waveform (independent from T_j, I_{LOAD} and di/dt), different from t_{rr} , which is dependent on $T_j, I_{LOAD}, di/dt$. No reverse recovery time constant t_{rr} due to absence of minority carrier injection.

⁵⁾ Only capacitive charge occuring, guaranteed by design.

⁶⁾ Repetitive condition defined by $T_j \leq 175\text{ °C}$


1 Power dissipation

$P_{tot}=f(T_C)$




2 Diode forward current

$I_F=f(T_C)^4$; $T_j \leq 175\text{ °C}$; parameter: $D= t_p/T$




3 Typ. forward characteristic

$I_F=f(V_F)$; $t_p=400\text{ }\mu\text{s}$; parameter: T_j




4 Typ. forward characteristic in surge current mode

$I_F=f(V_F)$; $t_p=400\text{ }\mu\text{s}$; parameter: T_j




5 Max. repetitive pulse current

$I_{\text{pulse}}=f(t_p)^{4/5}$; parameter T_C




6 Typ. reverse current vs. reverse voltage

$I_R=f(V_R)$; parameter: T_j




7 Transient thermal impedance

$Z_{\text{thJC}}=f(t_p)$; parameter: $D = t_p/T$




8 Typ. capacitance vs. reverse voltage

$C=f(V_R)$; $T_C=25\text{ °C}$, $f=1\text{ MHz}$




9 Typ. C stored energy

$$E_C = f(V_R)$$




10 Typ. capacitance charge vs. current slope

$$Q_C = f(di_F/dt)^5; T_j = 150 \text{ }^\circ\text{C}; I_F \leq I_{F,max}$$



Package Outline:PG-TO252-3-1/TO252-3-11/TO252-3-21



| DIM | MILLIMETERS | | INCHES | |
|-----|-------------|--------|--------|-------|
| | MIN | MAX | MIN | MAX |
| A | 2.159 | 2.413 | 0.085 | 0.095 |
| A1 | 0.000 | 0.150 | 0.000 | 0.006 |
| b | 0.635 | 0.889 | 0.025 | 0.035 |
| b2 | 0.650 | 1.150 | 0.026 | 0.045 |
| b3 | 5.004 | 5.500 | 0.197 | 0.217 |
| c | 0.457 | 0.580 | 0.018 | 0.023 |
| c2 | 0.460 | 0.980 | 0.018 | 0.039 |
| D | 5.969 | 6.223 | 0.235 | 0.245 |
| D1 | 5.020 | 5.842 | 0.198 | 0.230 |
| E | 6.400 | 6.731 | 0.252 | 0.265 |
| E1 | 4.850 | 5.207 | 0.191 | 0.205 |
| e | 2.286 | | 0.090 | |
| e1 | 4.572 | | 0.180 | |
| N | 3 | | 3 | |
| H | 9.400 | 10.480 | 0.370 | 0.413 |
| L3 | 0.900 | 1.143 | 0.035 | 0.045 |
| L4 | 0.584 | 0.950 | 0.023 | 0.037 |
| L6 | 0.510 | 0.686 | 0.020 | 0.027 |
| F1 | 10.500 | 10.700 | 0.413 | 0.421 |
| F2 | 6.300 | 6.500 | 0.248 | 0.256 |
| F3 | 2.100 | 2.300 | 0.083 | 0.091 |
| F4 | 5.700 | 5.900 | 0.224 | 0.232 |
| F5 | 5.660 | 5.860 | 0.222 | 0.231 |
| F6 | 1.100 | 1.300 | 0.043 | 0.051 |

REFERENCE
JEDEC TO252

SCALE

EUROPEAN PROJECTION

ISSUE DATE
21-09-2005

FILE
TO252_1

Published by
Infineon Technologies AG
81726 Munich, Germany
© 2012 Infineon Technologies AG
All Rights Reserved.

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

Warnings

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office. Infineon Technologies components may be used in life-support devices or systems and/or automotive, aviation and aerospace applications or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support, automotive, aviation and aerospace device or system or to affect the safety or effectiveness of that device or system. Life support systems are intended to be implanted in the human body and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.