


SWITCHING REGULATOR APPLICATIONS

Features

- High Voltage: $BV_{DSS}=500V$ (Min.)
- Low C_{rss} : $C_{rss}=8.4\text{pF}$ (Typ.)
- Low gate charge : $Q_g=17\text{nC}$ (Typ.)
- Low $R_{DS(on)}$: $R_{DS(on)}=1.5\Omega$ (Max.)

Ordering Information

Type NO.	Marking	Package Code
STK830F	STK830	TO-220F-3L

Outline Dimensions
unit : mm


Absolute maximum ratings(T_c=25°C)

Characteristic	Symbol	Rating	Unit
Drain-source voltage	V _{DSS}	500	V
Gate-source voltage	V _{GSS}	±30	V
Drain current (DC)	I _D	T _C =25°C	4.5
		T _C =100°C	3.3
Drain current (Pulsed) *	I _{DM}	18	A
Drain power dissipation	P _D	28	W
Avalanche current (Single) ②	I _{AS}	4.5	A
Single pulsed avalanche energy ②	E _{AS}	250	mJ
Avalanche current (Repetitive) ①	I _{AR}	4.5	A
Repetitive avalanche energy ①	E _{AR}	5.0	mJ
Junction temperature	T _J	150	°C
Storage temperature range	T _{stg}	-55~150	°C

* Limited by maximum junction temperature

Characteristic	Symbol	Typ.	Max	Unit
Thermal resistance	R _{th(J-C)}	-	4.46	°C/W
	R _{th(J-A)}	-	62.5	

Electrical Characteristics

(Tc=25°C)

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Drain-source breakdown voltage	$V_{(BR)DSS}$	$I_D=250 \mu A, V_{GS}=0V$	500	-	-	V
Gate threshold voltage	$V_{GS(th)}$	$I_D=250 \mu A, V_{DS}=V_{GS}$	2.0	-	4.0	V
Drain-source cut-off current	I_{DSS}	$V_{DS}=500V, V_{GS}=0V$	-	-	10	μA
Gate leakage current	I_{GSS}	$V_{DS}=0V, V_{GS}=\pm 30V$	-	-	± 100	nA
Drain-source on-resistance ④	$R_{DS(on)}$	$V_{GS}=10V, I_D=2.25A$	-	-	1.5	Ω
Forward transfer conductance ④	g_{fs}	$V_{DS}=10V, I_D=2.25A$	-	3.3	-	S
Input capacitance	C_{iss}	$V_{GS}=0V, V_{DS}=25V$ $f=1 \text{ MHz}$	-	550	830	pF
Output capacitance	C_{oss}		-	46	70	
Reverse transfer capacitance	C_{rss}		-	8.4	15	
Turn-on delay time	$t_{d(on)}$	$V_{DD}=250V, I_D=4.5A$ $R_G=12\Omega$	-	12	-	ns
Rise time	t_r		-	46	-	
Turn-off delay time	$t_{d(off)}$		-	50	-	
Fall time	t_f		-	48	-	
Total gate charge	Q_g	$V_{DS}=250V, V_{GS}=10V$ $I_D=4.5A$	-	17	26	nC
Gate-source charge	Q_{gs}		-	2.6	4.0	
Gate-drain charge	Q_{gd}		-	5.8	9.0	

Source-Drain Diode Ratings and Characteristics

(Tc=25°C)

Characteristic	Symbol	Test Condition	Min	Typ	Max	Unit
Source current (DC)	I_S	Integral reverse diode in the MOSFET	-	-	4.5	A
Source current (Pulsed) ①	I_{SP}		-	-	18	
Forward voltage ④	V_{SD}	$V_{GS}=0V, I_S=4.5A$	-	-	1.4	V
Reverse recovery time	t_{rr}	$I_S=4.5A, V_{GS}=0V$ $dI_S/dt=100A/\mu s$	-	188	-	ns
Reverse recovery charge	Q_{rr}		-	2.1	-	μC

Note :

- ① Repetitive rating : Pulse width limited by maximum junction temperature
- ② L=20mH, $I_{AS}=4.5A$, $V_{DD}=50V$, $R_G=27\Omega$
- ③ Pulse Test : Pulse width $\leq 400 \mu s$, Duty cycle $\leq 2\%$
- ④ Essentially independent of operating temperature

Electrical Characteristic Curves







Fig. 1 I_D - V_{DS} **Fig. 2** I_D - V_{GS} **Fig. 3** $R_{DS(on)}$ - I_D **Fig. 4** I_S - V_{SD} **Fig. 5** Capacitance - V_{DS} **Fig. 6** V_{GS} - Q_G 

Fig. 7 $V_{(BR)DSS}$ - T_J




Fig. 8 $R_{DS(on)}$ - T_J




Fig. 9 I_D - T_C




Fig. 10 Safe Operating Area




Fig. 11 Gate Charge Test Circuit & Waveform




Fig. 12 Switching Time Test Circuit & Waveform




Fig. 13 E_{AS} Test Circuit & Waveform








Fig. 14 Peak Diode Recovery dv/dt Test Circuit & Waveform



The AUK Corp. products are intended for the use as components in general electronic equipment (Office and communication equipment, measuring equipment, home appliance, etc.).

Please make sure that you consult with us before you use these AUK Corp. products in equipments which require high quality and / or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, transportation, combustion control, all types of safety device, etc.). AUK Corp. cannot accept liability to any damage which may occur in case these AUK Corp. products were used in the mentioned equipments without prior consultation with AUK Corp..

Specifications mentioned in this publication are subject to change without notice.