

1. Features


- ◆ 1.6mm(L)×0.8mm small size surface mount type
- ◆ Thin package of 0.55mm(H) thickness
- ◆ Diffusion lens optic
- ◆ Low power consumption type chip led

2. Applications

- ◆ LCD backlighting
- ◆ Keypad backlighting
- ◆ Symbol backlighting
- ◆ Front panel indicator lamp

3. Outline Dimensions

unit : mm



The contents of this data sheet are subject to change without advance notice for the purpose of improvement.
When using this product, would you please refer to the latest specifications.

4. Absolute Maximum Ratings


(Ta=25°C)

Characteristic	Symbol	Rating	Unit
Power dissipation	P _D	63	mW
Forward current	I _F	25	mA
*1 Peak forward current	I _{FP}	50	mA
Reverse voltage	V _R	4	V
Operating temperature range	T _{opr}	-25~80	°C
Storage temperature range	T _{stg}	-30~100	°C
*2 Soldering temperature	T _{sol}	240°C for 10 seconds	

*1.Duty ratio = 1/16, Pulse width = 0.1ms

*2.Recommended reflow soldering temperature profile

- Preheating 150°C to 185°C within 120 seconds soldering 240°C within 10 seconds
- Gradual cooling (Avoid quenching)



The contents of this data sheet are subject to change without advance notice for the purpose of improvement.
When using this product, would you please refer to the latest specifications.

5. Electrical / Optical Characteristics

(Ta=25°C)

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Forward voltage	V _F	I _F = 20mA	-	2.2	2.5	V
*3 Luminous intensity	I _V	I _F = 20mA	27	-	155	mcd
Peak wavelength	λ _P	I _F = 20mA	588	-	597	nm
Spectrum bandwidth	Δλ	I _F = 20mA	-	30	-	nm
Reverse current	I _R	V _R =4V	-	-	10	uA
*4 Half angle	θ1/2	X Y	I _F = 20mA	- -	±65 ±70	- - deg

*3.The test result of I_F=20mA is only for reference


*4.θ1/2 is the off-axis angle where the luminous intensity is 1/2 the peak intensity

◆ VF/ I_V / λ_P Grade Classification (Ta=25°C)

Test Condition @I _F =20mA		
VF[V]	Luminous Intensity[mcd]	Peak wavelength [nm]
1 : 1.95 ~2.2	I : 27~43	a : 588 ~ 590
	J : 43~68	b : 590 ~ 592
2 : 2.2 ~ 2.35	K : 68~100	c : 592 ~ 594
	L : 100~155	d : 594 ~ 597

(Each V_F, I_V, λ_P range did not consider a margin. Please refer to ±0.1V of V_F range, ±18% of I_V range, ±1nm of λ_P range as a permitted limit and do not use to combine grade classification. It must be used separately grade classification)

* Recommended Soldering Land Pattern



The contents of this data sheet are subject to change without advance notice for the purpose of improvement. When using this product, would you please refer to the latest specifications.

6. Characteristic Diagrams

Fig. 1 $I_F - V_F$




Fig. 2 $I_V - I_F$




Fig. 3 $I_F - Ta$




Fig.4 Spectrum Distribution




Fig. 5-1 Radiation Diagram(X)





Fig. 5-2 Radiation Diagram(Y)



The contents of this data sheet are subject to change without advance notice for the purpose of improvement.
When using this product, would you please refer to the latest specifications.