

AX7020K/7002P/7300T

AX7020K

Rackmount Membrane Keyboard

Specifications

- 19" rackmount or desktop membrane keyboard
- 101 keys, IBM™ PC AT-compatible
- Dust-protected and waterproof surface
- Built-in speaker with sound upon every key stroke
- Environment-protection switch contacts and electronics
- Liquid coated polycarbonate graphics
- MTBF: 2,000,000 key strokes
- Dimensions (W x D x H): 19" (482.6 mm) x 5.25" (133 mm) x 1.18" (30 mm)

Ordering Information

AX7020K Rackmount membrane keyboard



AX7002P

Wrist Rest Track Ball

Specifications

- Compatible with IBM™ PC XT, AT PS/2
- Hardware Resolution: 400 dpi
- Tracking Speed: 500 mm/sec
- Encoder: Opto-Mechanical
- Switch: 1 million cycle life
- Total Current: Less than 8mA
- Baud Rate: 1,200 bps
- Dimensions (W x D x H): 12.4" (316 mm) x 2.4" (60 mm) x 1.4" (35 mm)

Ordering Information

AX7002P Wrist rest track ball



AX7300T

5.25" Multiple Drives with USB, K/B and M/S Ports

Specifications

- Combinations for 1 x slim CD-ROM & 1 x standard FDD or 1 x slim CD-ROM & 1 x 3.5" HDD (Storage devices are not included)
- Dimensions (W x D x H): 5.87" (149 mm) x 5.51" (140 mm) x 1.66" (42.1 mm)(Storage devices are not included)

Ordering Information

AX7300T 5.25" multiple drives w/ USB, KB & MS ports (color: Black)



Overview

Embedded Systems

Embedded Systems for Transportation

Embedded Field Controllers

Embedded MicroBoxes

Industrial Barebone Systems

Industrial Chassis

Backplanes

Power Supplies

Peripherals & Accessories