
P1153-841

15" TFT Intel[®] Core™2 Duo Expandable Industrial Panel Computer with 2 PCI Slots





- 1. COM 1 (RS-232/RS-422/RS-485) 5. USB 2.0 x 4 2. DVI-I 3. Ethernet x 2
 - 4. IEEE 1394a x 2 6. Audio (Mic-in/Line-out) 7. COM 2/3 (RS-232)

8. Power switch

9. AC power

10. PCI x 2



Introduction

The P1153-841 is a 15 Industrial panel PC which features Intel[®] Core™2 Duo processor and Intel® Q965 chipset to provide powerful computing performance. This panel PC also offers the expansion ability with 2 PCI slots. Further, the P1153-841 adopts built-in speaker and WLAN module for wireless connectivity.

Powerful computing: Intel[®] Core[™]2 Duo processor

The P1153-841 features Intel® Core™2 Duo with a maximum of FSB 1066MHz and Intel® Q965+ICH8 chipset. It features two IEEE 1394a ports, two gigabit Ethernet ports and up to 4GB of dual-channel DDR2 system memory which deliver high computing capability for high performance-demanding applications.

Expandable for 2 PCI slots

The P1153-841 has 2 PCI slots for expansion purpose. User can easily plug in standard half-size PCI cards such as motion card, communication card and so on.

Speaker & WLAN antenna supported

The P1153-841 features built-in speaker, optional WLAN module and antenna for wireless network connectivity.

Features

- 15" XGA TFT LCD display
- Intel[®] Core[™]2 Duo processor
- Intel[®] Q965 + ICH8 chipset
- Supports 2 PCI slots
- Built-in speakers & optional WLAN module
- Windows[®] Vista and 7 supported
- Supports panel mount and rack mount
- Supports dimming control



▲ Side view

Specifications

Front Bezel	Industrial-grade material with IP65/NEMA 4 rugged protection		
LCD Panel	Display Type	15" XGA TFT	
	Brightness (cd/m ²)	250 nits	
	Resolution	1024 x 768 pixels	
	Viewing Angle (H/V)	140°/120°	
Main system	CPU	LGA775 for Intel [®] Core™2 Duo/ Core™ Solo processor with FSB 533/667/800/1066 MHz	
	Chipset	Intel® Q965 + ICH8	
	System Memory	2 x 240-pin DDR2 DIMM max. up to 4 GB	
	BIOS	Phoenix-Award 4 Mbit with RPL/PXE LAN Boot ROM, SmartView and customer CMOS backup	
	Storage	2 x 3.5" or 2 x 2.5" SATA HDD	
	Drive	1 x built-in slim CD-ROM	
	Watchdog Timer	255 levels, 1~255 sec.	

Specifications

I/O Connector	2 x RS-232 (COM 2/3)	
	1 x RS-232/422/485 (COM 1)	
	2 x IEEE 1394a	
	4 x USB 2.0	
	2 x PS/2 keyboard/mouse	
	2 x 10/100/1000Mbps Ethernet	
	1 x DVI-I for display (a converter for DVI-I to VGA is included)	
	1 x Audio (Mic-in/Line-out)	
Expansion	2 x PCI slotInterface	
Touchscreen	Resistive type	
	Light Transmission 79%	
	1 million activations (typical) at a single point	
Power supply	100 ~ 240VAC, 250W	
Dimensions	420 mm (16.54") (W) x 149.4 mm (5.88") (D) x 335 mm (13.19") (H)	
Packing Dimensions	610 mm (24.02") (W) x 260 mm (10.24") (D) x 590 mm	
r doking bintensions	(23.23") (H)	
Weight (net/gross)	6.6 kg (14.6 lb)/10 kg (22.0 lb)	
Environment	Operating temperature: 0° ~ +40°C (32°F ~ 104°F)	
	Storage Temperature: -20°C ~ +65°C (-4°F ~ +149°F)	
	Relative humidity: 10 ~ 95% @ 40°C, non-condensing	
	Operation vibration: 1.0G, 5~500Hz, random	
Certification	CE	

Ordering Information

P1153-841	15" XGA TFT LGA775 socket Intel [®] Core™2 Duo expandable panel PC with 2 PCI slots		
* Specification and certifications are based on options and may vary.			

Overview

Optional Accessories

82211530050E	2 x 3.5 HDD kit	M
82211580080E	2 x 2.5 HDD kit	Heavy-dut
82211530110E	Wireless LAN kit	Tor
82261580070E	Rack mount kit	

Optional OS Installation

Windows® 2000/XP/Vista/7

Industrial Panel Computers & Monitors

duty Fanless Touch Panel Computers

Digital Signage Solutions

Healthcare & Medical Solutions

Open Frame Panel Computers

Accessories

Dimensions

