


Xinger®



Ultra Low Profile 0404 Balun 50Ω to 100Ω Balanced

Description

The BD1416N50100AHF is a low profile sub-miniature unbalanced to balanced transformer designed for differential inputs and output locations on modern chipsets specifically in the GPS, GLONASS, WiMAX 1.5 (legacy TDM) and US DVB-H space and in an easy to use surface mount package. The BD1416N50100AHF is ideal for high volume manufacturing and delivers higher performance than traditional ceramic baluns. The BD1416N50100AHF has an unbalanced port impedance of 50Ω and a 50Ω balanced port impedance. This transformation enables single ended signals to be applied to differential ports on modern integrated chipsets. The output ports have equal amplitude (-3dB) with 180 degree phase differential. The BD1416N50100AHF is available on tape and reel for pick and place high volume manufacturing.


Detailed Electrical Specifications:

Specifications subject to change without notice.


Features:	Parameter	ROOM (25°C)			Unit
		Min.	Typ.	Max	
• 1400 – 1600 MHz	Frequency	1400		1600	MHz
• 0.57 mm Height Profile	Unbalanced Port Impedance		50		Ω
• 50 Ohm to 2 x 50 Ohm	Balanced Port Impedance		100		Ω
• Low Insertion Loss	Return Loss	14	18		dB
• Class Leading CMRR	Insertion Loss*		0.7	0.9	dB
• Targeted At GPS, GLONASS, WiMAX 1.5 (legacy TDM) & US DVB-H Markets	Amplitude Balance		0.8	1.2	dB
• Surface Mountable	Phase Balance		4	9	Degrees
• Tape & Reel	CMRR		26		dB
• Non-Conductive Top Surface	Power Handling			0.75	Watts
• RoHS Compliant	Operating Temperature	-55		+85	°C
• Halogen Free					

* Insertion Loss stated at room temperature (Insertion Loss is approximately 0.1 dB higher at +85 °C) Outline Drawing


Top View (Near-side)



Side View








Bottom View (Far-side)



Pin	Designation
1	GND / DC Feed + RF GND
2	Unbalanced Port
3	Balanced Port
4	Balanced Port


Dimensions are in Millimeters
Mechanical Outline

Tolerances are Non-Cumulative


Typical Performance: 1300 MHz. to 1700 MHz.

Wide Band Performance: 10 MHz. to 8010 MHz.


Insertion Loss




Return Loss-Input




Amplitude Balance



Phase Balance



CMRR




Mounting Configuration:

In order for Xinger surface mount components to work optimally, the proper impedance transmission lines must be used to connect to the RF ports. If this condition is not satisfied, insertion loss, Isolation and VSWR may not meet published specifications.

All of the Xinger components are constructed from organic PTFE based composites which possess excellent electrical and mechanical stability. Xinger components are compliant to a variety of ROHS and Green standards and ready for Pb-free soldering processes. Pads are Gold plated with a Nickel barrier.

An example of the PCB footprint used in the testing of these parts is shown below. In specific designs, the transmission line widths need to be adjusted to the unique dielectric coefficients and thicknesses as well as varying pick and place equipment tolerances.



Packaging and Ordering Information

Parts are available in reel and are packaged per EIA 481-2. Parts are oriented in tape and reel as shown below. Minimum order quantities are 4000 per reel. See Model Numbers below for further ordering information.





TABLE 1	
QUANTITY/REEL	REEL DIMENSIONS mm
4000	ØA 177.80
	B 8.00
	ØC 50.80
	ØD 13.00