



Versa-Pot:

Panel mountable, industrial potentiometer recommended for remote time delay adjustment. The shaft is slotted for screwdriver adjustment and serrated for slip-proof finger adjustment. Accepts Versa-Knob or Lock Shaft. May be ordered with two 8 in. (20.3 cm) wires soldered to pot (clockwise increase) and female quick connect terminals on other ends by adding suffix -X to end of part number.

P/N	With Wire Leads	Value
P1004-198		25k Ω
P1004-199		50k Ω
P1004-95	P1004-95-X	100k Ω
P1004-17		500k Ω
P1004-16	P1004-16-X	1M Ω
P1004-15		1.5M Ω
P1004-12	P1004-12-X	3M Ω
P1004-13		5M Ω

Specifications	
Rating	0.25W at 55°C
Taper	Linear
Shaft Rotation	300° \pm 5°
Tolerance	\pm 10%

Versa-Knob:

P/N: 0700-7

Versa-Knob is designed for 0.25 in. (6.35 mm) shaft of Versa-Pot. Semi-gloss industrial black finish.



Lock Shaft:

P/N: P0700-8

Fits 0.25 in. (6.35 mm) potentiometer shafts. Locks by tightening nut onto four tapered/slotted fingers. Pressure on the shaft locks control against mis-adjustment. Nickel plated brass finish.



Mini-Pot:

P/N: P1004-10 & P1004-31

A high quality, industrial potentiometer for remote time delay adjustment. The shaft extends through the timer's center hole for easy panel mounting. Use mini-mount bracket for standup mounting of timer. Adjustment by screwdriver or mini-knob. May be ordered with two 3 in. (7.6 cm) wires soldered to pot (clockwise increase) and female quick connect terminals on other ends by adding suffix -X to end of part number.



P/N	With Wire Leads	Value
P1004-9	P1004-9-X	500k Ω
P1004-10	P1004-10-X	1M Ω
P1004-31	P1004-31-X	3M Ω

Specifications	
Rating	0.25W at 55°C
Taper	Linear
Shaft Rotation	300° \pm 5°
Tolerance	\pm 10%

Mini-Knob:

P/N: 0700-21

Black plastic control knob with fluted body and white index/dot for setting accuracy. Mounts on 0.125 in. (3.2 mm) shaft of Mini-Pot.

