

Spot Cooling



Extend the Life
of Your Equipment

Complete Kit	OD1232-SPOT / DIN Part Number - 124141794 Includes: 120x32mm Fan * DIN rail DIN mount fan bracket Mounting screws 2 fan guards Power adaptor with 6' cord Automotive grade, double-sided, mount anywhere tape
Spot Cooler Only	OD1232-SPOT Part Number - 124141794 Includes: 120x32mm Fan * 1 fan guard Power adaptor with 6' cord
Fan ID	OD1232-12HB-03 *
VOLTAGE INPUT	120VAC / 60Hz
INPUT POWER	19 Watts
DC Nominal Current	0.60 A
DC Locked Current	0.05 A
Rated Speed (RPM)	1600 Max. (40C)
Airflow	65CFM @ 25C / 120CFM @ 40C
Noise Level (dB)	20 ~ 47
Max. Static Pressure	0.43" H ₂ O
Bearing System	Dual Ball
Frame & Impeller	PBT, UL94V-O plastic
Motor	Brushless DC, auto restart, polarity protected. Thermal Control.
Bearing System	Dual ball bearing
Insulation Resistance	10M ohm between leadwire and frame (500VDC)
Dielectric Strength	5mA max at 1500VAC for 1 minute between the leadwire and frame
Operation Temperature	-10C ~ +70C
Life (L10)	60,000 hours

Thermal Speed Control
Airflow Range

65 CFM at 25C
120 CFM at 40C

Energy Saving Solution for your
Green Initiative

Clips to standard
DIN rail



Plugs into any
115VAC power
source

OD1232-SPOT / DIN

Part Number - 124141794
 120x32mm
 Thermally controlled Fan *
 6' Cord with adaptor
 2 guards (1 installed)
 DIN rail
 DIN mount fan bracket
 Mounting screws
 Automotive grade, double-sided,
 mount anywhere tape

OD1232-SPOT

Part Number - 124141794
 120x32mm
 Thermally controlled Fan *
 6' Cord with adaptor
 1 guard installed



OD9225-SPOT - Instant smart cooling
for small spaces is also available in a
smaller package

Part Number - 193141791
 92x25mm thermally controlled fan.
 [50CFM (3100RPM) at 34C to
 < 30CFM (1600RPM) at 22C]
 6' cord with adaptor
 1 guard installed



Patent Pending