


SCMD4D10

SMD POWER INDUCTORS





Features

1. Open frame construction
2. Excellent Power Density
3. Engineered to Provide High Efficiency

ELECTRICAL CHARACTERISTICS



Part Number	Inductance (uH) (1)	Test Frequency	DC Resistance (Ω MAX) (2)	Saturation Current ⁽³⁾ (A)	Temperature Current ⁽⁴⁾ (A)
SCMD4D10-3R3	3.3	100KHZ	0.20	1.37	1.16
SCMD4D10-4R7	4.7	100KHZ	0.28	1.12	0.96
SCMD4D10-6R8	6.8	100KHZ	0.38	1.10	0.80
SCMD4D10-100	10	100KHZ	0.60	0.82	0.64
SCMD4D10-150	15	100KHZ	0.90	0.67	0.50
SCMD4D10-220	22	100KHZ	1.30	0.55	0.42
SCMD4D10-330	33	100KHZ	1.75	0.45	0.36
SCMD4D10-470	47	100KHZ	2.80	0.40	0.30



- (1). Inductance tolerance ±20% tested at 0.25V, 0ADC and 25°C.
- (2). DCR measured at 25°C.
- (3). The DC current at which the inductance decreases by 10% from its initial value.
- (4). The DC current that results in a 40°C temperature rise from 25°C ambient.

[Click here for QUANTITY PER REEL & PACKING INFORMATION](#)

Custom versions available upon request.