


N-CHANNEL ENHANCEMENT MODE VERTICAL DMOS FET

ZVN0545A

ISSUE 2 – MARCH 94

FEATURES

- * 450 Volts V_{DS}
- * $R_{DS(on)} = 50\Omega$



E-Line
TO92 Compatible

ABSOLUTE MAXIMUM RATINGS.

| PARAMETER | SYMBOL | VALUE | UNIT |
|---|---------------|-------------|-------------|
| Drain-Source Voltage | V_{DS} | 450 | V |
| Continuous Drain Current at $T_{amb}=25^{\circ}C$ | I_D | 90 | mA |
| Pulsed Drain Current | I_{DM} | 600 | mA |
| Gate-Source Voltage | V_{GS} | ± 20 | V |
| Power Dissipation at $T_{amb}=25^{\circ}C$ | P_{tot} | 700 | mW |
| Operating and Storage Temperature Range | $T_j:T_{stg}$ | -55 to +150 | $^{\circ}C$ |

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}C$ unless otherwise stated).

| PARAMETER | SYMBOL | MIN. | MAX. | UNIT | CONDITIONS. |
|---|--------------|------|-----------|--------------------|--|
| Drain-Source Breakdown Voltage | BV_{DSS} | 450 | | V | $I_D=1mA, V_{GS}=0V$ |
| Gate-Source Threshold Voltage | $V_{GS(th)}$ | 1 | 3 | V | $I_D=1mA, V_{DS}=V_{GS}$ |
| Gate-Body Leakage | I_{GSS} | | 20 | nA | $V_{GS}=\pm 20V, V_{DS}=0V$ |
| Zero Gate Voltage Drain Current | I_{DSS} | | 10 400 | μA μA | $V_{DS}=450V, V_{GS}=0$ $V_{DS}=405V, V_{GS}=0V,$ $T=125^{\circ}C (2)$ |
| On-State Drain Current(1) | $I_{D(on)}$ | 150 | | mA | $V_{DS}=25V, V_{GS}=10V$ |
| Static Drain-Source On-State Resistance (1) | $R_{DS(on)}$ | | 50 | Ω | $V_{GS}=10V, I_D=100mA$ |
| Forward Transconductance(1)(2) | g_{fs} | 100 | | mS | $V_{DS}=25V, I_D=100mA$ |
| Input Capacitance (2) | C_{iss} | | 70 | pF | $V_{DS}=25V, V_{GS}=0V, f=1MHz$ |
| Common Source Output Capacitance (2) | C_{oss} | | 10 | pF | |
| Reverse Transfer Capacitance (2) | C_{rss} | | 4 | pF | |
| Turn-On Delay Time (2)(3) | $t_{d(on)}$ | | 7 | ns | $V_{DD}\approx 25V, I_D=100mA$ |
| Rise Time (2)(3) | t_r | | 7 | ns | |
| Turn-Off Delay Time (2)(3) | $t_{d(off)}$ | | 16 | ns | |
| Fall Time (2)(3) | t_f | | 10 | ns | |