



SPECIFICATIONS:

MATERIAL:-

INSULATOR: LCP, UL94V-0

CONTACT: PHOSPHOR BRONZE

FINISH:-

CONTACT: GOLD OVER NICKEL UNDERPLATE

SOLDER TAIL: TIN OVER NICKEL UNDERPLATE

ELECTRICAL:-

CURRENT RATING: 1 AMP MAX.

CONTACT RESISTANCE: 100 mΩ MAX.

INSULATION RESISTANCE: 1000 MΩ MIN.

MECHANICAL:-

DURABILITY: 5000 CYCLES MIN.

ENVIRONMENTAL:-

TEMPERATURE RANGE: -40°C TO + 85°C

NOTES: ALL DIMENSIONS AND NOTES

MARKED * ARE CRITICAL AND

MUST BE CHECKED IN ACCORDANCE

WITH QUALITY DOC. Q1-02A

TOLERANCES
X. = ±0.5mm
X.X = ±0.30mm
X.XX = ±0.20mm

Allan	1	01.08.06	-
NAME	ISS.	DATE	C/NOTE
APPROVED: <i>Alan</i>			
CHECKED:			
DRAWN: Allan			
CUSTOMER REF.:			
ASSEMBLY DRG:			

HARWIN

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES
X. = ±1mm
X.X = ±0.25mm
X.XX = ±0.10mm
X.XXX = ±0.01mm
ANGLES = ±5°
UNLESS STATED

MATERIAL: SEE NOTES
FINISH: SEE NOTES
S/AREA: mm²

TITLE: MEMORY STICK SOCKET STANDARD
DRAWING NUMBER: M506-5582042
SHT 1 OF 1

HARWIN USA
TEL: 603 893 5376
FAX: 603 893 5396
mis@harwin.com

HARWIN Europe (UK)
TEL: 023 9231 4545
FAX: 023 9231 4590
mis@harwin.co.uk

HARWIN Asia
TEL: +65 6 779 4909
FAX: +65 6 779 3868
mis@harwin.com.sg