



NOTES: ALL DIMENSIONS AND NOTES MARKED * ARE CRITICAL AND MUST BE CHECKED IN ACCORDANCE WITH QUALITY DOC. Q1-02A

△ SPECIFICATIONS:

ELECTRICAL:-

CURRENT RATING: 1.5A
VOLTAGE RATING: 250V
DIELECTRIC WITHSTANDING VOLTAGE: 750V AC PER MINUTE
CONTACT RESISTANCE: 50 mΩ MAX.
INSULATION RESISTANCE: 1000 MΩ MIN.

MECHANICAL:-

INSERTION FORCE: 35N MAX.
EXTRACTION FORCE: 10N MAX.

ENVIRONMENTAL:

OPERATING TEMPERATURE: -55°C TO +85°C

SPECIFICATIONS:

MATERIAL:-

① HOUSING: P.B.T, BLACK, QTY:1
② PIN TERMINAL: PHOSPHOR BRONZE, QTY: 8
③ SHELL: BRASS, T=0.3mm
④ SHELL: BRASS, T=0.3mm
⑤ SHELL: SPCC, T=0.3mm
FINISH:-
② PIN TERMINAL: GOLD/TIN PLATED OVER NICKEL
③ SHELL: BRASS: TIN PLATED
④ SHELL: BRASS: TIN PLATED
⑤ SHELL: BRASS: NICKEL PLATED

Allan	2	24.11.08	A174
Allan	1	01.08.06	-
NAME	ISS.	DATE	C/NOTE
APPROVED: <i>[Signature]</i>			
CHECKED: <i>[Signature]</i>			
DRAWN: Allan			
CUSTOMER REF.:			
ASSEMBLY DRG:			

TOLERANCES

X.X = ±0.25mm
X.XX = ±0.20mm

HARWIN

HARWIN USA
TEL: 603 893 5376
FAX: 603 893 5396
mis@harwin.com

HARWIN Europe (UK)
TEL: 023 9231 4545
FAX: 023 9231 4590
mis@harwin.co.uk

HARWIN Asia
TEL: +65 6 779 4909
FAX: +65 6 779 3868
mis@harwin.com.sg

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES
X. = ±1mm
X.X = ±0.25mm
X.XX = ±0.10mm
X.XXX = ±0.01mm
ANGLES = ±5°
UNLESS STATED

MATERIAL:

SEE NOTES

FINISH: SEE NOTES

S/AREA: mm²

TITLE:

USB A TYPE FEMALE DUAL PORTS

DRAWING NUMBER:

M701-230842

SHT
1
OF
1