



Recommended PCB Layout

SPECIFICATIONS:

MATERIAL:-

HOUSING: P.B.T +30%G.F, UL94V-0, WHITE \triangle

CONTACTS: PHOSPHOR BRONZE

SHELL: BRASS

BACK SHELL: SPCC

FINISH:-

CONTACTS: 2u" GOLD AND 30u" PALLADIUM NICKEL ON CONTACT,
150u" TIN ON SOLDER TAIL OVER 50u" NICKEL \triangle

SHELL: 100u" TIN PLATED OVER 40u" NICKEL

ELECTRICAL:-

CURRENT RATING: 1.5A

WORKING VOLTAGE: 30V AC/DC

 \triangle DIELECTRIC STRENGTH: 500V AC FOR ONE MINUTECONTACT RESISTANCE: 30 m Ω MAX.INSULATION RESISTANCE: 1000 M Ω MIN.

MECHANICAL:-

MATING FORCE: 35N MAX.

WITHDRAWAL FORCE: 10N MIN.

DURABILITY: 1500 CYCLES MIN.

ENVIRONMENTAL:-

 \triangle OPERATING TEMPERATURE: -55°C TO +85°C

NOTES: ALL DIMENSIONS AND NOTES
MARKED * ARE CRITICAL AND
MUST BE CHECKED IN ACCORDANCE
WITH QUALITY DOC. QI-02A

Allan	9	19.11.10	A335
Allan	8	25.03.10	A271
Allan	7	03.02.10	A262
Allan	6	21.01.10	A251

NAME	ISS.	DATE	C/NOTE
------	------	------	--------

APPROVED: *Ben*

CHECKED:

DRAWN: Allan

CUSTOMER REF.:

ASSEMBLY DRG:

TID 60001572 \triangle \triangle \triangle

HARWIN

HARWIN USA
TEL: 603 893 5376
FAX: 603 893 5396
mis@harwin.com

HARWIN Europe (UK)
TEL: 023 9231 4545
FAX: 023 9231 4590
mis@harwin.co.uk

HARWIN Asia
TEL: +65 6 779 4909
FAX: +65 6 779 3868
mis@harwin.com.sg

THIS DRAWING AND ANY
INFORMATION OR DESCRIPTIVE
MATTER SET OUT HEREON ARE
CONFIDENTIAL AND COPYRIGHT
PROPERTY OF THE HARWIN
GROUP AND MUST NOT BE
DISCLOSED, LOANED, COPIED
OR USED FOR MANUFACTURING,
TENDERING OR FOR ANY
OTHER PURPOSE WITHOUT
THEIR WRITTEN PERMISSION.

TOLERANCES

X.X = ± 0.20 mm
X.XX = ± 0.15 mm
X.XXX = ± 0.05 mm
ANGLES = $\pm 3^\circ$
UNLESS STATED

MATERIAL:

SEE NOTES

FINISH:

SEE NOTES

S/AREA:

mm²

TITLE:

USB B TYPE

DRAWING NUMBER:

M701-320442

SHT
1
OF
1