



SPECIFICATIONS

VOLTAGE 500Vac
 FREQUENCY 50/60Hz
 CURRENT 100A @ 40°C
 TEMPERATURE -25 TO 100°C
 LEAKAGE CURRENT 154mA @ 500V 50Hz
 HUMIDITY 90% RH (NON-CONDENSING)
 VIBRATION 10-200Hz 1.8G
 ELECTRIC STRENGTH 2250Vac/1min.
 POWER DISSIPATION 18W
 MASS 4.5kg
 TERMINALS 50sqmm TERMINAL BLOCK
 EARTH TERMINALS M8 STUD
 FLANGE MOUNTING 4x M6

RoHS
 2002/95/EC
 Compliant

Tel No. +44(0)1724 273200 E-mail www.dem-uk.com

Alpha3 manufacturing ROXBURGH EMC DELTRON Components DELTRON Enclosures

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ALPHA 3 MANUFACTURING.
 ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ALPHA 3 MANUFACTURING IS PROHIBITED.

DEM Manufacturing, Deltron Emcon House Hargreaves Way, Sawcliffe Ind. Park, Scunthorpe, North Lincolnshire, DN15 8RF, UK

UNLESS OTHERWISE SPECIFIED:
 DIMENSIONS ARE IN MILLIMETRES
 LINEAR TOLERANCE:
 NO DECIMAL PLACES ±0.5mm
 1 DECIMAL PLACE ±0.25mm
 2 DECIMAL PLACES ±0.125mm
 ANGULAR TOLERANCE: ±1°

FINISH	-	DEBURR AND BREAK SHARP EDGES	DRAWN BY	AT	TITLE	GENERAL SPECIFICATION
			APPROVED BY	SW		3 PHASE 100A 500V INDUSTRIAL FILTER
			THIRD ANGLE PROJECTION		DRAWING NO.	KMF3100A
			IF IN DOUBT ASK DO NOT SCALE DRAWING		ISSUE	03
MATERIAL	ALU 1.2mm		SHEET 1 OF 1	SCALE 1:1		Release

