



Lead Lengths 40mm +5/-0mm

TOR	
PART No	T68-40A AL 47
SIZE (OD/ID/Ht)	17.5/9.4/6.35
COATING	NA
MATERIAL	IRON POWDER
K VALUE	NA
Cu Wire	
PART No	COP207 weight 4.5g
SIZE (Dia)	0.28
COATING	SOL 2
COAT MATERIAL	NA
Winding	
No Turns	292
No Layers	CONTINUOUS
No Strands	ONE
Direction	AS PER SKETCH

TEST	Nom	Tolerance	Min	Max
Inductance (mH)	4	+20/-20%	3.2	4.8
Res (Ohm)	1.8	+15/-15%	1.53	2.07
Hi Pot (V AC)	NA			

Tel No. +44(0)1724 273200 Website www.dem-uk.com

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ALPHA 3 MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ALPHA 3 MANUFACTURING IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN MILLIMETRES
LINEAR TOLERANCE:
NO DECIMAL PLACES ±0.5mm
1 DECIMAL PLACE ±0.25mm
2 DECIMAL PLACES ±0.125mm
ANGULAR TOLERANCE: ±1°

FINISH -

DEBURR AND BREAK SHARP EDGES

DRAWN BY SPB

APPROVED BY SW

THIRD ANGLE PROJECTION



SHEET 1 OF 1

SCALE 1:1

A4

TITLE
PROCUREMENT SPECIFICATION
ASSEMBLY FOR
CHKSF1120

DRAWING NO.
SF1120-CHK

ISSUE
02
Release



DEM Manufacturing, Deltron Emcon House
Hargreaves Way, Sawcliffe Ind. Park,
Scunthorpe, North Lincolnshire, DN15 8RF, UK