A range of high quality UK manufactured phono plugs made from machined brass with various plating options.

-Centre contact available in solid pin.

-Ground contact with unique 'T' shape slot for maximum contact area.
-Internal cable clamp for secure cable connection.

-Spring strain relief.

-Colour coded ID rings for easy cable identification.


-Attractive body styling.


-Maximum cable size 5.5mm

Rating -

Rated Current: 5A. Rated Voltage: 50V

Insulation resistance - 100M  $\Omega$  at 500 Vdc





Material

Centre contact :Brass, flash gold plated Ground contact :Brass, flash gold plated

Insulation :Noryl SE1

Cable clamp :Brass, flash gold plated Spring :Spring steel, black chrome plated

Cap :Brass, black chrome plated

Deltron Part No.	Description
335-0000	FLASH GOLD PLUG ASSY/BLACK CHROME CAP & SPRING
335-0100	FLASH GOLD PLUG ASSY/BLACK CHROME CAP & SPRING (BLACK ID RING)
335-0200	FLASH GOLD PLUG ASSY/BLACK CHROME CAP & SPRING (BLUE ID RING)
335-0500	FLASH GOLD PLUGASSY/BLACK CHROME CAP & SPRING (RED ID RING)
335-0600	FLASH GOLD PLUG ASSY/BLACK CHROME CAP & SPRING (WHITE ID RING)
335-0700	FLASH GOLD PLUG ASSY/BLACK CHROME CAP & SPRING (YELLOW ID RING)



THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ALPHA 3 MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION O

Harareaves Way, Sawcliffe Ind. Park

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETRES LINEAR TOLERANCE: NO DECIMAL PLACES ±0.5mm 1 DECIMAL PLACE ±0.25mm 2 DECIMAL PLACES ±0.125mm ANGULAR TOLERANCE: +1°

DEBURR AND BREAK DRAWN BY FINISH SEE NOTE SHARP EDGES IF IN DOUBT ASK DO NOT SCALE DRAWING MATERIAL SEE NOTE

GENERAL SPECIFICATION APPROVED BY 335 SERIES PROFESSIONAL PHONO LINE PLUG SHEET 1 OF 1 04 SCALE 1:1 335 SERIES A4 Release