## Old Company Name in Catalogs and Other Documents

On April 1<sup>st</sup>, 2010, NEC Electronics Corporation merged with Renesas Technology Corporation, and Renesas Electronics Corporation took over all the business of both companies. Therefore, although the old company name remains in this document, it is a valid Renesas Electronics document. We appreciate your understanding.

Renesas Electronics website: <a href="http://www.renesas.com">http://www.renesas.com</a>

April 1<sup>st</sup>, 2010 Renesas Electronics Corporation

Issued by: Renesas Electronics Corporation (<a href="http://www.renesas.com">http://www.renesas.com</a>)

Send any inquiries to http://www.renesas.com/inquiry.



### Notice

- 1. All information included in this document is current as of the date this document is issued. Such information, however, is subject to change without any prior notice. Before purchasing or using any Renesas Electronics products listed herein, please confirm the latest product information with a Renesas Electronics sales office. Also, please pay regular and careful attention to additional and different information to be disclosed by Renesas Electronics such as that disclosed through our website.
- 2. Renesas Electronics does not assume any liability for infringement of patents, copyrights, or other intellectual property rights of third parties by or arising from the use of Renesas Electronics products or technical information described in this document. No license, express, implied or otherwise, is granted hereby under any patents, copyrights or other intellectual property rights of Renesas Electronics or others.
- 3. You should not alter, modify, copy, or otherwise misappropriate any Renesas Electronics product, whether in whole or in part.
- 4. Descriptions of circuits, software and other related information in this document are provided only to illustrate the operation of semiconductor products and application examples. You are fully responsible for the incorporation of these circuits, software, and information in the design of your equipment. Renesas Electronics assumes no responsibility for any losses incurred by you or third parties arising from the use of these circuits, software, or information.
- 5. When exporting the products or technology described in this document, you should comply with the applicable export control laws and regulations and follow the procedures required by such laws and regulations. You should not use Renesas Electronics products or the technology described in this document for any purpose relating to military applications or use by the military, including but not limited to the development of weapons of mass destruction. Renesas Electronics products and technology may not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable domestic or foreign laws or regulations.
- 6. Renesas Electronics has used reasonable care in preparing the information included in this document, but Renesas Electronics does not warrant that such information is error free. Renesas Electronics assumes no liability whatsoever for any damages incurred by you resulting from errors in or omissions from the information included herein.
- 7. Renesas Electronics products are classified according to the following three quality grades: "Standard", "High Quality", and "Specific". The recommended applications for each Renesas Electronics product depends on the product's quality grade, as indicated below. You must check the quality grade of each Renesas Electronics product before using it in a particular application. You may not use any Renesas Electronics product for any application categorized as "Specific" without the prior written consent of Renesas Electronics. Further, you may not use any Renesas Electronics product for any application for which it is not intended without the prior written consent of Renesas Electronics. Renesas Electronics shall not be in any way liable for any damages or losses incurred by you or third parties arising from the use of any Renesas Electronics product for an application categorized as "Specific" or for which the product is not intended where you have failed to obtain the prior written consent of Renesas Electronics. The quality grade of each Renesas Electronics product is "Standard" unless otherwise expressly specified in a Renesas Electronics data sheets or data books, etc.
  - "Standard": Computers; office equipment; communications equipment; test and measurement equipment; audio and visual equipment; home electronic appliances; machine tools; personal electronic equipment; and industrial robots.
  - "High Quality": Transportation equipment (automobiles, trains, ships, etc.); traffic control systems; anti-disaster systems; anti-crime systems; safety equipment; and medical equipment not specifically designed for life support.
  - "Specific": Aircraft; aerospace equipment; submersible repeaters; nuclear reactor control systems; medical equipment or systems for life support (e.g. artificial life support devices or systems), surgical implantations, or healthcare intervention (e.g. excision, etc.), and any other applications or purposes that pose a direct threat to human life.
- 8. You should use the Renesas Electronics products described in this document within the range specified by Renesas Electronics, especially with respect to the maximum rating, operating supply voltage range, movement power voltage range, heat radiation characteristics, installation and other product characteristics. Renesas Electronics shall have no liability for malfunctions or damages arising out of the use of Renesas Electronics products beyond such specified ranges.
- 9. Although Renesas Electronics endeavors to improve the quality and reliability of its products, semiconductor products have specific characteristics such as the occurrence of failure at a certain rate and malfunctions under certain use conditions. Further, Renesas Electronics products are not subject to radiation resistance design. Please be sure to implement safety measures to guard them against the possibility of physical injury, and injury or damage caused by fire in the event of the failure of a Renesas Electronics product, such as safety design for hardware and software including but not limited to redundancy, fire control and malfunction prevention, appropriate treatment for aging degradation or any other appropriate measures. Because the evaluation of microcomputer software alone is very difficult, please evaluate the safety of the final products or system manufactured by you.
- 10. Please contact a Renesas Electronics sales office for details as to environmental matters such as the environmental compatibility of each Renesas Electronics product. Please use Renesas Electronics products in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive. Renesas Electronics assumes no liability for damages or losses occurring as a result of your noncompliance with applicable laws and regulations.
- 11. This document may not be reproduced or duplicated, in any form, in whole or in part, without prior written consent of Renesas Electronics
- 12. Please contact a Renesas Electronics sales office if you have any questions regarding the information contained in this document or Renesas Electronics products, or if you have any other inquiries.
- (Note 1) "Renesas Electronics" as used in this document means Renesas Electronics Corporation and also includes its majority-owned subsidiaries.
- (Note 2) "Renesas Electronics product(s)" means any product developed or manufactured by or for Renesas Electronics.



# **HAT2105T**


# Silicon N Channel MOS FET High Speed Power Switching

REJ03G0384-0200 Rev.2.00 Aug 06, 2007

### **Features**

- Low on-resistance
- Capable of 4 V gate drive
- High density mounting

### **Outline**



### **Absolute Maximum Ratings**

 $(Ta = 25^{\circ}C)$ 

Item	Symbol	Ratings	Unit
Drain to source voltage	$V_{DSS}$	200	V
Gate to source voltage	$V_{GSS}$	±15	V
Drain current	I <sub>D</sub>	0.5	Α
Drain peak current	I <sub>D</sub> (pulse) <sup>Note1</sup>	2	Α
Body-drain diode reverse drain current	I <sub>DR</sub>	0.5	Α
Channel dissipation	Pch <sup>Note 2</sup>	1	W
	Pch <sup>Note 3</sup>	1.5	W
Channel temperature	Tch	150	℃
Storage temperature	Tstg	-55 to +150	℃

Notes: 1. PW  $\leq$  10  $\mu$ s, duty cycle  $\leq$  1 %

2. 1 Drive operation ; When using the glass epoxy board (FR4 40 x 40 x 1.6 mm), PW  $\leq$  10 s

3. 2 Drive operation; When using the glass epoxy board (FR4 40 x 40 x 1.6 mm), PW  $\leq$  10 s


### **Electrical Characteristics**

 $(Ta = 25^{\circ}C)$ 

Item	Symbol	Min.	Тур.	Max.	Unit	Test Conditions	
Drain to source breakdown voltage	$V_{(BR)DSS}$	200	_	_	V	$I_D = 10 \text{ mA}, V_{GS} = 0$	
Gate to source breakdown voltage	$V_{(BR)GSS}$	±15	_	_	V	$I_G = \pm 100 \ \mu A, \ V_{DS} = 0$	
Gate to source leak current	I <sub>GSS</sub>	1	_	±10	μΑ	$V_{GS} = \pm 12 \text{ V}, V_{DS} = 0$	
Zero gate voltage drain current	I <sub>DSS</sub>	1	_	5	μΑ	$V_{DS} = 200 \text{ V}, V_{GS} = 0$	
Gate to source cutoff voltage	$V_{GS(off)}$	1.0	_	2.1	V	$V_{DS} = 10 \text{ V}, I_D = 1 \text{ mA}$	
Static drain to source on state	R <sub>DS(on)</sub>	1	1.6	2.2	Ω	$I_D = 0.5 \text{ A}, V_{GS} = 10 \text{ V}^{\text{Note4}}$	
resistance	R <sub>DS(on)</sub>	1	1.9	2.7	Ω	$I_D = 0.5 \text{ A}, V_{GS} = 4 \text{ V}^{\text{Note4}}$	
	R <sub>DS(on)</sub>	1	2.4	5.5	Ω	$I_D = 2 A$ , $V_{GS} = 5 V^{Note4}$	
Forward transfer admittance	y <sub>fs</sub>	0.56	0.86	_	S	$I_D = 0.5 \text{ A}, V_{DS} = 10 \text{ V}^{\text{Note4}}$	
Input capacitance	Ciss	_	120	_	pF	V <sub>DS</sub> = 10 V	
Output capacitance	Coss	_	29	_	pF	$V_{GS} = 0$	
Reverse transfer capacitance	Crss	_	10	_	pF	f = 1 MHz	
Turn-on delay time	t <sub>d(on)</sub>	_	10	_	ns	$V_{GS} = 5 \text{ V}, I_D = 0.5 \text{ A}$	
Rise time	t <sub>r</sub>	_	14	_	ns	$V_{DD} \cong 30 \text{ V}$	
Turn-off delay time	$t_{d(off)}$		24		ns		
Fall time	t <sub>f</sub>		9		ns		
Body-drain diode forward voltage	$V_{DF}$		0.9	1.4	V	$I_F = 0.5 \text{ A}, V_{GS} = 0^{\text{Note4}}$	

Notes: 4. Pulse test

### **Package Dimensions**



### **Ordering Information**

Part No.	Quantity	Shipping Container
HAT2105T-EL-E	3000 pcs	Taping

Renesas Technology Corp. sales Strategic Planning Div. Nippon Bldg., 2-6-2, Ohte-machi, Chiyoda-ku, Tokyo 100-0004, Japan

- Renesas lechnology Corp. Sales Strategic Planning Div. Nippon Bldg., 2-6-2, Ohte-machi, Chiyoda-ku, Tokyo 100-0004, Japan Notes:

  1. This document is provided for reference purposes only so that Renesas customers may select the appropriate Renesas products for their use. Renesas neither makes warrantes or representations with respect to the accuracy or completeness of the information in this document nor grants any license to any intellectual property girbs to any other rights of representations with respect to the information in this document in this document of the purpose of the respect of the information in this document in the product data, diagrams, charts, programs, algorithms, and application circuit examples.

  3. You should not use the products of the technology described in this document for the purpose of military use. When exporting the products or technology described herein, you should follow the applicable export control laws and regulations, and procedures required by such laws and regulations, and procedures required to change without any plan protein. Before purchasing or using any Renesas products listed in this document, in the such procedure in the procedure of the description of the such and the procedure of the description of the such and the procedure of the description of the description of the such as a such as the disclosed through our website. (http://www.renesas.com.)

  3. Renesas has a used reasonabl



### **RENESAS SALES OFFICES**

http://www.renesas.com

Refer to "http://www.renesas.com/en/network" for the latest and detailed information.

### Renesas Technology America, Inc.

450 Holger Way, San Jose, CA 95134-1368, U.S.A Tel: <1> (408) 382-7500, Fax: <1> (408) 382-7501

Renesas Technology Europe Limited
Dukes Meadow, Millboard Road, Bourne End, Buckinghamshire, SL8 5FH, U.K.
Tel: <44> (1628) 585-100, Fax: <44> (1628) 585-900

Renesas Technology (Shanghai) Co., Ltd.
Unit 204, 205, AZIACenter, No.1233 Lujiazui Ring Rd, Pudong District, Shanghai, China 200120 Tel: <86> (21) 5877-1818, Fax: <86> (21) 6887-7898

Renesas Technology Hong Kong Ltd.
7th Floor, North Tower, World Finance Centre, Harbour City, 1 Canton Road, Tsimshatsui, Kowloon, Hong Kong Tel: <852> 2265-6688, Fax: <852> 2730-6071

**Renesas Technology Taiwan Co., Ltd.** 10th Floor, No.99, Fushing North Road, Taipei, Taiwan Tel: <886> (2) 2715-2888, Fax: <886> (2) 2713-2999

Renesas Technology Singapore Pte. Ltd.
1 Harbour Front Avenue, #06-10, Keppel Bay Tower, Singapore 098632 Tel: <65> 6213-0200, Fax: <65> 6278-8001

Renesas Technology Korea Co., Ltd. Kukje Center Bldg. 18th Fl., 191, 2-ka, Hangang-ro, Yongsan-ku, Seoul 140-702, Korea Tel: <82> (2) 796-3115, Fax: <82> (2) 796-2145

Renesas Technology Malaysia Sdn. Bhd
Unit 906, Block B, Menara Amcorp, Amcorp Trade Centre, No.18, Jalan Persiaran Barat, 46050 Petaling Jaya, Selangor Darul Ehsan, Malaysia Tel: <603> 7955-9390, Fax: <603> 7955-9510