



# PJMBZ5V6 SERIES

## DUAL TVS FOR ESD / TRANSIENT PROTECTION

**VOLTAGE** 5.6 to 6.8 Volts    **POWER** 150 Watts

**SOT-23**    Unit : inch(mm)

### FEATURES


- Working Peak Reverse Voltage Range - 5.6 to 6.8V
- Maximum Leakage Current of 5uA
- IEC61000-4-2 Compliance 15kV Air, 8kV Contact Discharge
- Lead free in comply with EU RoHS 2002/95/EC directives.
- Green molding compound as per IEC61249 Std. . (Halogen Free)

### APPLICATIONS

- Data Transmission Line Ports
- Computer Monitor Interface Port Protection
- Portable Consumer Electronics
- Instrumentation Equipment

### MECHANICAL DATA

- Case: SOT-23, Plastic
- Terminals: Solderable per MIL-STD-750, Method 2026
- Apporx. Weight: 0.0003 ounces, 0.0084 grams



### MAXIMUM RATINGS (TA=25°C unless otherwise noted)

PARAMETER	Symbol	Value	Units
Peak Pulse Power 8x20 usec Waveform	P <sub>PP</sub>	150	W
Peak Pulse Power 10x1000 usec Waveform		30	
ESD per IEC61000-4-2 (Air)	V <sub>PP</sub>	+/-15	kV
ESD per IEC61000-4-2 (Contact)		+/-8	kV
Lead Soldering Temperature (max 10 secs)	T <sub>L</sub>	260	°C
Operating Junction Temperature and Storage Temperature Range	T <sub>J</sub> ,T <sub>STG</sub>	-55 to +150	°C




Fig.25



# PJMBZ5V6 SERIES

## ELECTRICAL CHARACTERISTICS (TA=25°C unless otherwise noted)

PJMBZ5V6 Marking UA						
PARAMETER	Symbol	Test Condition	MIN.	TYP.	MAX.	Units
Reverse Stand-Off Voltage	V <sub>RWM</sub>		-	-	3.3	V
Reverse Breakdown Voltage	V <sub>BR</sub>	I <sub>BR</sub> =1.0 mA I <sub>BR</sub> =20 mA	5.13 5.32	5.4 5.6	5.67 5.88	V
Reverse Leakage Current	I <sub>R</sub>	V <sub>R</sub> =3.3V	-	-	5.0	μA
Clamping Voltage (8x20 usec)	V <sub>CL</sub>	I <sub>PP</sub> =20 Amps	-	-	9.0	V
Clamping Voltage (10x1000 usec)	V <sub>CL</sub>	I <sub>PP</sub> =5.0 Amps	-	-	7.0	V
Off State Junction Capacitance	C <sub>J</sub>	0 Vdc Bias f=1MHz Between I/O pins and pin 3	-	-	90	pF


PJMBZ6V2 Marking UB						
PARAMETER	Symbol	Test Condition	MIN.	TYP.	MAX.	Units
Reverse Stand-Off Voltage	V <sub>RWM</sub>		-	-	4.3	V
Reverse Breakdown Voltage	V <sub>BR</sub>	I <sub>BR</sub> =1.0 mA I <sub>BR</sub> =20 mA	5.89	6.2	6.51	V
Reverse Leakage Current	I <sub>R</sub>	V <sub>R</sub> =4.3V	-	-	0.5	μA
Clamping Voltage (8x20 usec)	V <sub>CL</sub>	I <sub>PP</sub> =20 Amps	-	-	9.5	V
Clamping Voltage (10x1000 usec)	V <sub>CL</sub>	I <sub>PP</sub> =4.0 Amps	-	-	7.5	V
Off State Junction Capacitance	C <sub>J</sub>	0 Vdc Bias f=1MHz Between I/O pins and pin 3	-	-	70	pF

PJMBZ6V8 Marking UC						
PARAMETER	Symbol	Test Condition	MIN.	TYP.	MAX.	Units
Reverse Stand-Off Voltage	V <sub>RWM</sub>		-	-	5.0	V
Reverse Breakdown Voltage	V <sub>BR</sub>	I <sub>BR</sub> =1.0 mA I <sub>BR</sub> =20 mA	6.46	6.8	7.14	V
Reverse Leakage Current	I <sub>R</sub>	V <sub>R</sub> =5.0V	-	-	0.5	μA
Clamping Voltage (8x20 usec)	V <sub>CL</sub>	I <sub>PP</sub> =20 Amps	-	-	10	V
Clamping Voltage (10x1000 usec)	V <sub>CL</sub>	I <sub>PP</sub> =4.0 Amps	-	-	8.5	V
Off State Junction Capacitance	C <sub>J</sub>	0 Vdc Bias f=1MHz Between I/O pins and pin 3	-	-	100	pF




# PJMBZ5V6 SERIES


## RATING AND CHARACTERISTIC CURVES




**Fig.1 8/20µs Peak Pulse Current Waveform**




**Fig.2 10/1000µs Peak Pulse Current Waveform**




**Fig.3 Non-Repetitive Peak Pulse Power vs Pulse Time**



**Fig.4 Capacitance vs. Biasing Voltage @1MHz**



**Fig.5 8x20µsec Surge Waveform**




**Fig.6 10x1000µsec Waveform**



# PJMBZ5V6 SERIES

## MOUNTING PAD LAYOUT



## ORDER INFORMATION

- Packing information
  - T/R - 12K per 13" plastic Reel
  - T/R - 3K per 7" plastic Reel



# PJMBZ5V6 SERIES

## Part No\_packing code\_Version

PJMBZ5V6\_R1\_00001

PJMBZ5V6\_R2\_00001

For example :

**RB500V-40** **R2** **00001**



Packing Code <b>XX</b>				Version Code <b>XXXXX</b>		
Packing type	1 <sup>st</sup> Code	Packing size code	2 <sup>nd</sup> Code	HF or RoHS	1 <sup>st</sup> Code	2 <sup>nd</sup> ~5 <sup>th</sup> Code
Tape and Ammunition Box (T/B)	<b>A</b>	N/A	<b>0</b>	<b>HF</b>	<b>0</b>	serial number
Tape and Reel (T/R)	<b>R</b>	7"	<b>1</b>	<b>RoHS</b>	<b>1</b>	serial number
Bulk Packing (B/P)	<b>B</b>	13"	<b>2</b>			
Tube Packing (T/P)	<b>T</b>	26mm	<b>X</b>			
Tape and Reel (Right Oriented) (TRR)	<b>S</b>	52mm	<b>Y</b>			
Tape and Reel (Left Oriented) (TRL)	<b>L</b>	PANASERT T/B CATHODE UP (PBCU)	<b>U</b>			
FORMING	<b>F</b>	PANASERT T/B CATHODE DOWN (PBCD)	<b>D</b>			



## PJMBZ5V6 SERIES

---

### Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.