



MBR1040CT~MBR10200CT

10 AMPERES SCHOTTKY BARRIER RECTIFIERS


VOLTAGE 40 to 200 Volts **CURRENT** 10 Amperes

FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-O.
Flame Retardant Epoxy Molding Compound.
- Metal silicon junction, majority carrier conduction
- Low power loss, high efficiency.
- High current capability
- Guardring for overvoltage protection
- For use in low voltage, high frequency inverters free wheeling, and polarity protection applications.
- In compliance with EU RoHS 2002/95/EC directives

MECHANICAL DATA

- Case: TO-220AB molded plastic
- Terminals: solder plated, solderable per MIL-STD-750, Method 2026
- Polarity: As marked.
- Mounting Position: Any
- Weight: 0.0655 ounces, 1.859 grams.



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

PARAMETER	SYMBOL	MBR1040CT	MBR1045CT	MBR1050CT	MBR1060CT	MBR1080CT	MBR1090CT	MBR10100CT	MBR10150CT	MBR10200CT	UNITS						
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	40	45	50	60	80	90	100	150	200	V						
Maximum RMS Voltage	V_{RMS}	28	31.5	35	42	56	63	70	105	140	V						
Maximum DC Blocking Voltage	V_{DC}	40	45	50	60	80	90	100	150	200	V						
Maximum Average Forward Current (See fig.1)	$I_{F(AV)}$	10									A						
Peak Forward Surge Current :8.3ms single half sine-wave superimposed on rated load(JEDEC method)	I_{FSM}	150									A						
Maximum Forward Voltage at 5A, per leg	V_F	0.7		0.75		0.8		0.9		V							
Maximum DC Reverse Current $T_J=25^{\circ}\text{C}$ at Rated DC Blocking Voltage $T_J=125^{\circ}\text{C}$	I_R	0.05 20									mA						
Typical Thermal Resistance	R_{aJC}	2									$^{\circ}\text{C} / \text{W}$						
Operating and Storage Junction Temperature Range	T_J, T_{STG}	-55 to +150	-65 to +175														

Notes :

Both Bonding and Chip structure are available.



MBR1040CT~MBR10200CT

RATING AND CHARACTERISTIC CURVES




Fig.1- FORWARD CURRENT DERATING CURVE




Fig.2- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTIC




Fig.3- TYPICAL REVERSE CHARACTERISTICS




Fig.4- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS