

MH5 SERIES

105°C 5mm Height.

◆FEATURES

•RoHS compliance.

**◆SPECIFICATIONS**

Items	Characteristics						
Category Temperature Range	−40~+105°C						
Rated Voltage Range	6.3~50V.DC						
Capacitance Tolerance	±20% (20°C, 120Hz)						
Leakage Current(MAX)	I=0.01CV or 3μA whichever is greater. (After 2 minutes application of rated voltage) I=(μA) C=(μF) V=(V) Leakage Current Rated Capacitance Rated Voltage						
(tanδ) Dissipation Factor(MAX)	Rated Voltage	6.3	10	16	25	35	50
	tanδ	0.28	0.24	0.20	0.16	0.13	0.12
Endurance	After applying rated voltage with rated ripple current for 1000 hours at 105°C, the capacitors shall meet the following requirements.						
	Capacitance Change	Within ±25% of the initial value.					
	Dissipation Factor	Not more than 200% of the specified value.					
	Leakage Current	Not more than the specified value.					
Low Temperature Stability Impedance Ratio(MAX)	Rated Voltage	6.3	10	16	25	35	50
	Z(−25°C)/Z(20°C)	3	3	2	2	2	2
	Z(−40°C)/Z(20°C)	8	5	4	3	3	3

◆STANDARD SIZE Size φD×L(mm), Ripple Current (mA r.m.s./105°C, 120Hz)

WV (V.DC)	Cap (μF)	Size (φDxL)	Rated Ripple Current
6.3 (0J)	22	4×5	23
	33	5×5	30
	47	5×5	37
	100	6.3×5	57
10 (1A)	22	5×5	28
	33	5×5	34
	47	6.3×5	52
	100	6.3×5	62

WV (V.DC)	Cap (μF)	Size (φDxL)	Rated Ripple Current
16 (1C)	10	4×5	20
	22	5×5	31
	33	6.3×5	48
	47	6.3×5	56
25 (1E)	100	6.3×5	62
	10	5×5	22
	22	6.3×5	44
	33	6.3×5	48
	47	6.3×5	56

WV (V.DC)	Cap (μF)	Size (φDxL)	Rated Ripple Current
35 (1V)	4.7	4×5	17
	10	5×5	24
	22	6.3×5	48
	0.1	4×5	1
	0.22	4×5	2
	0.33	4×5	3
	0.47	4×5	4
	1	4×5	8
	2.2	4×5	13
	3.3	4×5	14
50 (1H)	4.7	5×5	18
	10	6.3×5	28

◆OPTION

	Code
PET Sleeve	EFC

◆PART NUMBER

□□□ MH5 □□□□□ M □□□ □□ DXL
 Rated Voltage Series Rated Capacitance Capacitance Tolerance Option Lead Forming Case Size