

SXW SERIES

**105°C Overvoltage Vent Operation Facility,
Lead Wire Type**

◆FEATURES

- Load Life : 105°C 1000~2000 hours.
- Body diameter of $\phi 10\text{mm}$ to $\phi 18\text{mm}$ with high ripple current capability.
- This series has specification of vent operation in overvoltage situation.
Please consult us for any further details.
- RoHS compliance.

**◆SPECIFICATIONS**

Items	Characteristics														
Category Temperature Range	-25~+105°C														
Rated Voltage Range	200, 400V.DC														
Capacitance Tolerance	$\pm 20\%$ (20°C,120Hz)														
Leakage Current(MAX)	$I=3\sqrt{CV}$ (After 5 minutes application of rated voltage) $I=(\mu\text{A})$ $C=(\mu\text{F})$ $V=(\text{V})$ Leakage Current Rated Capacitance Rated Voltage														
(tanδ) Dissipation Factor(MAX)	0.15(20°C,120Hz)														
Endurance	After applying rated voltage with rated ripple current for time of right table at 105°C, the capacitors shall meet the following requirements.														
<table border="1"> <tr> <td>Capacitance Change</td> <td>Within $\pm 20\%$ of the initial value.</td> </tr> <tr> <td>Dissipation Factor</td> <td>Not more than 200% of the specified value.</td> </tr> <tr> <td>Leakage Current</td> <td>Not more than the specified value.</td> </tr> </table>		Capacitance Change	Within $\pm 20\%$ of the initial value.	Dissipation Factor	Not more than 200% of the specified value.	Leakage Current	Not more than the specified value.	<table border="1"> <tr> <td>(μF) Rated Capacitance</td> <td>(hrs) Life Time</td> </tr> <tr> <td>4.7</td> <td>1,000</td> </tr> <tr> <td>10 or over</td> <td>2,000</td> </tr> </table>	(μF) Rated Capacitance	(hrs) Life Time	4.7	1,000	10 or over	2,000	
Capacitance Change	Within $\pm 20\%$ of the initial value.														
Dissipation Factor	Not more than 200% of the specified value.														
Leakage Current	Not more than the specified value.														
(μF) Rated Capacitance	(hrs) Life Time														
4.7	1,000														
10 or over	2,000														
Low Temperature Stability Impedance Ration(MAX)	<table border="1"> <tr> <td>Rated Voltage</td> <td>200</td> <td>400</td> </tr> <tr> <td>$Z(-25^\circ\text{C})/Z(20^\circ\text{C})$</td> <td>3</td> <td>8</td> </tr> </table> (120Hz)			Rated Voltage	200	400	$Z(-25^\circ\text{C})/Z(20^\circ\text{C})$	3	8						
Rated Voltage	200	400													
$Z(-25^\circ\text{C})/Z(20^\circ\text{C})$	3	8													

◆MULTIPLIER FOR RIPPLE CURRENT

Frequency Coefficient

(Hz) Frequency		60(50)	120	500	1k	10k \leq
Coefficient	200WV	0.8	1.0	1.10	1.14	1.18
	400WV	0.65	1.0	1.05	1.10	1.15
	10~100 μF	0.8	1.0	1.05	1.10	1.15

◆OPTION


	Code
PET Sleeve	EFC

◆PART NUMBER

□□□ SXW □□□□□ M □□□ □□ D×L
 Rated Voltage Series Rated Capacitance Capacitance Tolerance Option Lead Forming Case Size

◆DIMENSIONS

(mm)



ϕD	10	12.5	16	18
ϕd	0.6		0.8	
F	5.0		7.5	
a	1.5			

◆STANDARD SIZE

Rated Voltage (V.DC)	Rated Capacitance (μF)	Size $\phi D \times L$ (mm)	Rated Ripple Current (A r.m.s.105°C,120Hz)
200	68	16×20	0.32
	82	16×20	0.36
	82	16×25	0.38
	82	18×20	0.37
	100	16×25	0.43
	100	16×30	0.45
	100	18×20	0.43
	120	16×25	0.48
	120	16×30	0.50
	120	18×20	0.46
	120	18×25	0.48
	130	18×20	0.46
	150	16×30	0.57
	150	16×35	0.59
	150	18×20	0.50
	150	18×25	0.53
	150	18×30	0.58
	180	16×40	0.66
	180	18×25	0.60
	180	18×30	0.62
	220	18×30	0.71
	220	18×35	0.74
	270	18×35	0.77
	270	18×45	0.89
	330	18×40	0.91

Rated Voltage (V.DC)	Rated Capacitance (μF)	Size $\phi D \times L$ (mm)	Rated Ripple Current (A r.m.s.105°C,120Hz)
400	4.7	10×10	0.060
	10	10×16	0.087
	10	12.5×20	0.10
	22	16×20	0.17
	22	16×25	0.18
	27	16×25	0.22
	33	16×25	0.22
	33	16×30	0.24
	33	18×20	0.23
	33	18×25	0.25
	36	18×20	0.24
	39	16×30	0.27
	39	18×25	0.27
	47	16×30	0.30
	47	16×35	0.32
	47	18×20	0.28
	47	18×25	0.30
	47	18×30	0.32
	56	16×35	0.34
	56	16×40	0.36
	56	18×30	0.35
	56	18×35	0.37
	68	16×40	0.39
	68	18×35	0.40
	68	18×40	0.42
	82	18×40	0.46
	82	18×45	0.48
	100	18×45	0.52