



BDM40-UA 4½ Digit Display, True RMS, Benchtop DMM

Bench testing of voltage, ohms and amps made easy and precise

- AC and DC voltage, current, resistance and diode test
- High accuracy, basic V DC 0.03%
- 2A fused and 20A range
- Easy-to-read, 0.5 Inch LED Display
- Includes line cords and fuses for either 117V or 220V operation

No hassle warranty

No waiting.

No shipping charges.



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)

This 4½ digit (20,000 counts) digital multimeter features True RMS (AC or AC + DC coupling) measurement capabilities to assure accuracy regardless of the types of waveforms. The BDM40-UA features high resolution at a low cost, which makes it ideal for production test, QA test, depot service and university and school labs.

Measurement capabilities include voltage from 10 mV to 1200 V DC and to 1000 V AC, current from 10 mA to 20 A, and resistance from 10 mΩ to 20 MΩ. Diode test is provided on the 2 kΩ range.

The interlocking push buttons on the front panel provide easy selection of functions and ranges. Bold labels on the input jacks increase visibility and offer an added safety, as does the fully fused 2A jack.

The BDM40-UA's full 360° adjustable tilt bail and LED display maximize readability for most any bench application. Each meter comes with standard test leads, power cord, and users manual. A full line of optional probes, current clamps and test leads is available to meet your application needs.

Included Accessories

Spare fuses, standard test leads, 117V and 220V line cords and users manual.





BDM40-UA

4 1/2 Digit Display, True RMS, Benchtop DMM

Data Sheet

General Specifications

Display	4 1/2 digit, 0.5 in H (12.7 mm), red LED, 20,000 count
Update Speed	2rdg/sec.
Power	117 V AC $\pm 10\%$ or 234 V AC $\pm 10\%$, 50/60 Hz
Operating temperature	0 °C to 50 °C (32 °F to 122 °F);
Size	7.9 cm x 23 cm x 33 cm (3.1 in x 9 in x 13 in)
Weight	2.2 kg (4.7 lb)
Warranty	One year

Specifications (23 °C \pm 5 °C; <70 % R.H.)

Function	Range	Accuracy	
DC and AC voltage			
DC voltage	200 mV, 2 V, 20 V, 200 V, 1200 V	$\pm 0.03\%$ rdg ± 4 dgt	
AC voltage	200 mV, 2 V, 20 V, 200 V, 1000 V	45 Hz to 2 kHz	$\pm 0.5\%$ rdg ± 15 dgt
		2 kHz to 10 kHz	$\pm 1.0\%$ rdg ± 15 dgt
		10 kHz to 20 kHz	$\pm 2.0\%$ rdg ± 15 dgt
		20 kHz to 50 kHz	$\pm 5.0\%$ rdg ± 30 dgt
	1000 V	45 Hz to 1 kHz	$\pm 0.5\%$ rdg ± 15 dgt
AC conversion type	True RMS		
Crest factor	1:1 to 1:3 full scale		
Max. resolution	10 μ V		
Input impedance	DC 10 M Ω		
	AC 10 M Ω shunted by 10 pF		
DC and AC current			
DC current	200 mA, 2 mA, 20 mA, 200 mA	$\pm 0.2\%$ rdg ± 2 dgt	
	2 A, 20 A	$\pm 0.3\%$ rdg ± 2 dgt	
AC current	200 mA, 2 mA, 20 mA, 200 mA	45 Hz to 2 kHz	$\pm 0.5\%$ rdg ± 15 dgt
		2 kHz to 10 kHz	$\pm 1.0\%$ rdg ± 15 dgt
		10 kHz to 20 kHz	$\pm 2.0\%$ rdg ± 15 dgt
		2 A, 20 A 45 Hz to 2 kHz	$\pm 0.5\%$ rdg ± 15 dgt
Resistance			
200 Ω , 2 k Ω , 20k Ω ,	200 Ω	$\pm 0.1\%$ rdg ± 4 dgt	
200 k Ω , 2 M Ω , 20 M Ω	2 k Ω , 20 k Ω , 200 k Ω , 2 M Ω	$\pm 0.1\%$ rdg ± 2 dgt	
	20 M Ω	$\pm 0.25\%$ rdg ± 2 dgt	
Diode Test	On 2k Ω range		
Overload protection			
Voltage (AC/DC)	1200 V DC or peak AC Continuous (<10 seconds in 200 mV and 2 V ranges).		
Current (AC/DC)	2 A @ 250 V		
Resistance	250 V DC/AC RMS on all ranges		

Amprobe® Test Tools
website: www.Amprobe.com
email: info@amprobe.com
Everett, WA 98203
Tel: 877-AMPROBE

Amprobe® Test Tools Europe
In den Engematten 14
79286 Glottertal, Germany
Tel.: +49 (0) 7684 8009 - 0

©2007 Amprobe Test Tools. All rights reserved.
7/2007 PN: 2428662 D-US-N Rev B