



## Series 805 Mighty Mouse Triple-Start Protective Cover Ordering Information

667-261 and 667-262



**Protect Connectors From Damage**

Machined aluminum or stainless steel protective covers have fluorosilicone gasket for a watertight fit.

**Stainless Steel Fittings and Rings**

Choose small diameter eye fittings for panel attachment. Larger rings fit under the jam nut or over cable jackets. Split rings can be installed on fully assembled cables.

**Polyurethane-Coated SST Wire Rope** offers high strength, excellent abrasion resistance and good flexibility. Or, choose Teflon® jacket

for high temperature exposure.

**Braided Nylon Rope** provides excellent flexibility and good abrasion resistance, and can be ordered with slip knot fittings for easy installation on any size cable.

D

How to Order						
Sample Part Number						
667-262	-M	-G	9	04	-6	
Series	Shell Material / Finish	Attachment Type	Shell Size	Attachment Code	Attachment Length in Inches	
<p><b>667-261</b> Protective Cover for use with Series 805 Plugs</p> <p><b>667-262</b> Protective Cover for use with Series 805 Receptacles</p>	-C Aluminum / Black Anodize (Non-Conductive) RoHS Compliant	-G Nylon Rope	8 9	Omit for attachment Types <b>N</b> (No Attachment) and <b>SK</b> (Slip Knot)	Omit for attachment Type <b>N</b> (No Attachment)  <b>Example</b> "-6" equals six inch length	
	-M Aluminum / Electroless Nickel RoHS Compliant	-H SST Wire Rope, Teflon® Jacket	10 11 12			<p style="text-align: center;">Small Ring</p>
	-NF Aluminum / Cadmium with Olive Drab Chromate	-N No Attachment	15 18			
	-S Aluminum / Zinc-Nickel with Black Chromate	-SK Nylon Rope With Slip Knot	19 23	<p style="text-align: center;">Split Ring</p>		
	-Z1 Stainless Steel / Passivated RoHS Compliant	-T SST Wire Rope, No Jacket				
	-ZNU Aluminum / Zinc-Nickel with Black Chromate	-U SST Wire Rope, Polyurethane Jacket "SST" = Stainless Steel				
		-MT Aluminum / Nickel-PTFE RoHS Compliant				