

770-001S3 and 770-003S3
Type 3 Flexible Polyolefin
Straight Lipped Adapter Shrink Boots, Standard



Type 3 Flexible Polyolefin For General Duty Applications



Economical flexible polyolefin boots fit most standard shrink boot adapters, including M85049 adapters as well as Glenair Series 31 and Series 44 adapters. These self-extinguishing boots meet the requirements of SAE AS81765/1 Type 1. Good resistance to oils and fuels. Available with optional hot melt adhesive lining, these boots provide strain relief and environmental protection to connector/cable transitions, and are ideally suited for heat-sensitive cables due to the material's low heat shrink temperature of +100° C. Temperature rating -55° to +135° C. Black color.

- *General purpose harnessing*
- *Economical, flexible*
- *-55° C to +135° C*

| Boot Size | Part Number with Eyelet | | Part Number without Eyelet | |
|-----------|-----------------------------|---|-----------------------------|--------------------------------------|
| | No Adhesive Lining | Pre-Coated with W2 Standard Hot-Melt Adhesive | No Adhesive Lining | Pre-Coated with W2 Hot-Melt Adhesive |
| 00 | — | — | 770-003S300 | 770-003S300W2 |
| 01 | — | — | 770-003S301 | 770-003S301W2 |
| 02 | — | — | 770-003S302 | 770-003S302W2 |
| 03 | 770-001S303 | 770-001S303W2 | 770-003S303 | 770-003S303W2 |
| 04 | 770-001S304 | 770-001S304W2 | 770-003S304 | 770-003S304W2 |
| 05 | 770-001S305 | 770-001S305W2 | 770-003S305 | 770-003S305W2 |
| 06 | 770-001S306 | 770-001S306W2 | 770-003S306 | 770-003S306W2 |
| 07 | 770-001S307 | 770-001S307W2 | 770-003S307 | 770-003S307W2 |
| 08 | 770-001S308 | 770-001S308W2 | 770-003S308 | 770-003S308W2 |
| 09 | 770-001S309 | 770-001S309W2 | 770-003S309 | 770-003S309W2 |

Add "-DH" to the end of any part number for drain holes.
Add "-PP" to the end of any part number for potting ports.