



SEMITOP® 3

3-phase bridge rectifier +
brake chopper +3-phase
bridge inverter

SK 10 DGDL 065 ET


Preliminary Data

Features

- Compact design
- One screw mounting
- Heat transfer and isolation through direct copper bonded aluminum oxide ceramic (DCB)
- Ultrafast NPT technology IGBT
- CAL Technology FWD
- Integrated NTC temperature sensor

Typical Applications*

- Inverter



DGDL - ET

| Absolute Maximum Ratings | | $T_s = 25^\circ\text{C}$, unless otherwise specified | | |
|----------------------------------|---|---|--|------------------|
| Symbol | Conditions | Values | | Units |
| IGBT - Inverter, Chopper | | | | |
| V_{CES} | | 600 | | V |
| I_C | $T_s = 25(80)^\circ\text{C}$ | 17 (11) | | A |
| I_{CRM} | $I_{CRM} = 2 \times I_{Cnom}$, $t_p = 1\text{ ms}$ | 20 | | A |
| V_{GES} | | ± 20 | | V |
| T_j | | -40 ... +150 | | $^\circ\text{C}$ |
| Diode - Inverter, Chopper | | | | |
| I_F | $T_s = 25(80)^\circ\text{C}$ | 22 (15) | | A |
| I_{FRM} | $I_{FRM} = 2 \times I_{Fnom}$, $t_p = 1\text{ ms}$ | 28 | | A |
| T_j | | -40 ... +150 | | $^\circ\text{C}$ |
| Rectifier | | | | |
| V_{RRM} | | 800 | | V |
| I_F | $T_s = 80^\circ\text{C}$ | 21 | | A |
| I_{FSM} / I_{TSM} | $t_p = 10\text{ ms}$, sin 180°, $T_j = 25^\circ\text{C}$ | 220 | | A |
| I^2_t | $t_p = 10\text{ ms}$, sin 180°, $T_j = 25^\circ\text{C}$ | 240 | | A ² s |
| T_j | | -40 ... +150 | | $^\circ\text{C}$ |
| T_{sol} | Terminals, 10s | 260 | | $^\circ\text{C}$ |
| T_{stg} | | -40 ... +125 | | $^\circ\text{C}$ |
| V_{isol} | AC, 1 min. / 1s | 2500 / 3000 | | V |

| Characteristics | | $T_s = 25^\circ\text{C}$, unless otherwise specified | | |
|----------------------------------|---|---|-----------|------------------|
| Symbol | Conditions | min. | typ. | max. |
| IGBT - Inverter, Chopper | | | | |
| V_{CEsat} | $I_C = 6\text{ A}$, $T_j = 25(125)^\circ\text{C}$ | | 2 (2,3) | 2,5 |
| $V_{GE(th)}$ | $V_{GE} = V_{CE}$, $I_C = 0,5\text{ mA}$ | 3 | 4 | 5 |
| $V_{CE(TO)}$ | $T_j = 25^\circ\text{C}$ (125) °C | | 1,2 (1,1) | 1,3 |
| r_T | $T_j = 25^\circ\text{C}$ (125) °C | | 133 (183) | 200 |
| C_{ies} | $V_{CE} = 25\text{ V}$, $V_{GE} = 0\text{ V}$, $f = 1\text{ MHz}$ | | 0,5 | nF |
| C_{oes} | $V_{CE} = 25\text{ V}$, $V_{GE} = 0\text{ V}$, $f = 1\text{ MHz}$ | | 0,1 | nF |
| C_{res} | $V_{CE} = 25\text{ V}$, $V_{GE} = 0\text{ V}$, $f = 1\text{ MHz}$ | | 0,1 | nF |
| $R_{th(j-s)}$ | per IGBT | | 2 | K/W |
| $t_{d(on)}$ | under following conditions | | 45 | ns |
| t_r | $V_{CC} = 300\text{ V}$, $V_{GE} = \pm 15\text{ V}$ | | 30 | ns |
| $t_{d(off)}$ | $I_C = 6\text{ A}$, $T_j = 125^\circ\text{C}$ | | 340 | ns |
| t_f | $R_{Gon} = R_{Goff} = 210\Omega$ | | 25 | ns |
| E_{on} | inductive load | | 0,18 | mJ |
| E_{off} | | | 0,13 | mJ |
| Diode - Inverter, Chopper | | | | |
| $V_F = V_{EC}$ | $I_F = 6\text{ A}$, $T_j = 25(125)^\circ\text{C}$ | | 1,3 (1,2) | 1,5 |
| $V_{(TO)}$ | $T_j = 25^\circ\text{C}$ (125) °C | | 1 (0,9) | 1,1 |
| r_T | $T_j = 25^\circ\text{C}$ (125) °C | | 45 (50) | 60 |
| $R_{th(j-s)}$ | per diode | | 2,3 | K/W |
| I_{RRM} | under following conditions | | 8,4 | A |
| Q_{rr} | $I_F = 6\text{ A}$, $V_R = 300\text{ V}$ | | 0,8 | μC |
| E_{rr} | $V_{GE} = 0\text{ V}$, $T_j = 125^\circ\text{C}$ | | 0,18 | mJ |
| di_F/dt | $= 170\text{ A}/\mu\text{s}$ | | | |
| Diode rectifier | | | | |
| V_F | $I_F = 15\text{ A}$, $T_j = 25()^\circ\text{C}$ | | 1,1 | V |
| $V_{(TO)}$ | $T_j = 150^\circ\text{C}$ | | 0,8 | V |
| r_T | $T_j = 150^\circ\text{C}$ | | 20 | $\text{m}\Omega$ |
| $R_{th(j-s)}$ | per diode | | 2,7 | K/W |
| Temperatur sensor | | | | |
| R_{ts} | 5 %, $T_r = 25(100)^\circ\text{C}$ | | 5000(493) | Ω |
| Mechanical data | | | | |
| w | | 30 | | g |
| M_s | Mounting torque | | 2,5 | Nm |

SK 10 DGDL 065 ET

CONVERTER, INVERTER, BRAKE




Fig. 15 Input Bridge Diode forward characteristic




Fig. 16 Typical Output Characteristic




Fig. 17 Turn-on/-off energy = $f(I_c)$




Fig. 18 Turn-on/-off energy = $f(R_g)$




Fig. 19 Typical gate charge characteristic




Fig. 21 Typical switching time vs. I_C




Fig. 22 Typical switching time vs. R_G




Fig. 23 Typical NTC characteristic





Fig. 24 Typical FWD forward characteristic


SK 10 DGDL 065 ET CONVENTER, INVERTER, BRAKE

UL Recognized File
no. E 63532

Dimensions in mm



Case T 49 (Suggested hole diameter, in the PCB, for solder pins and plastic mounting pins: 2mm)



This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, Chapter IX.

* The specifications of our components may not be considered as an assurance of component characteristics. Components have to be tested for the respective application. Adjustments may be necessary. The use of SEMIKRON products in life support appliances and systems is subject to prior specification and written approval by SEMIKRON. We therefore strongly recommend prior consultation of our personal.