



## 10W Car Charging Adapter for Portable Electronics CLM10D is Compliant with US and EU Vehicle Standards



### Features

- High Efficiency
- Compliant with EU Vehicle Standards
- Robust Design
- Battery Charging

### Applications

- Portable Electronics
- Mobile Phones

### Safety Approvals

- CE
- C-Tick
- FCC
- E-Mark

### Mechanical Characteristics

- Length: 85.28mm (3.36in)
- Diameter (at cord): 30.48mm (1.2in)
- Diameter (at tip): 19.3mm (0.76in)
- Weight: 81.7g (2.88oz)

### Output Specifications

Model	DC Output Voltage	Load		Ripple P-P (max.)
		Min.	Max.	
CLM10D-050(A)-R	5.15V	0A	2.0A	100mVp-p

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at [www.phihong.com](http://www.phihong.com) for the most up-to-date specifications and contact information.

**Input:**

**AC Input Voltage Range**

10 to 30V DC (12 Volts Nominal)

**Input Current**

≤30mA at no load (12V Input)

≤1.40A at no load (10V Input)

≤1.44A at no load (30V Input)

**Output:**

**Output Power**

10W

**Efficiency**

80% minimum at maximum load and 12V

**Rise time:**

<50mSec.

**Input Over-Voltage**

Fuse will blow with no damage to unit

**Output Over-Voltage**

By Zener clamping

**Reverse Polarity Protection**

Fuse will blow with no damage to unit

**Short-Circuit Protection**

Current limiting without damage to unit

**Environmental:**

**Temperature**

Operation -20 to 60°C

Non-operation -40 to 85°C

Operating Humidity 0 to 95%

**MTBF**

100K Hours Minimum at full load and ambient 25°C

**DC Output Connector**

2.1mm x 5.5mm x 9mm Center Positive Barrel

**DC Cord**

1.61 Meters (extended)

**Dimension Diagram Unit: mm**

