



Single Port 16W Power over Ethernet Wall Plug Adapter POE16R-560 Passive Power Injector with Interchangeable Clips



Features

- No Detection
- Non-Vented Case
- Field Interchangeable AC Clips
- 1 Year Warranty
- IEEE802.3af compliant
- Full Protection OCP, OVP
- Level V Efficient
- Lowest Cost

Applications

- IP Telephones
- Wireless Network Access Points
- Blue Tooth Access Points
- Security Cameras
- IP Print Servers

Safety Approvals

- cUL/UL
- C-Tick
- CE
- SAA

Mechanical Characteristics

- Length: 80mm (3.15in)
- Width: 45mm (1.77in)
- Height: 33mm (1.29in)
- Weight: 95g (3.35oz.)

Output Specifications

Model ⁽²⁾	DC Output Voltage	Load		Regulation		Output Power
		Min.	Max.	Line	Load	
POE16R-560	56V	0A	0.286A	±5%		16W
POE16R-560G	56V	0A	0.286A	±5%		16W

- (1) Interchangeable AC clips sold separately
 (2) G model is gigabit compatible

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at www.phihong.com for the most up-to-date specifications and contact information.

INPUT:

AC Input Voltage Range
90 to 264VAC

AC Input Voltage Rating
100 to 240VAC

AC Input Current
0.8A (RMS) maximum for 120VAC
0.5A (RMS) maximum for 240VAC

Leakage Current
0.25mA maximum @ 254VAC 60Hz

AC Input Frequency
47-63Hz

AC Inrush Current
60A (RMS) maximum for 240VAC

No Load Power Consumption
>0.3W

OUTPUT:
Total Output Power
16W

Ripple and Regulation
100mV maximum

Efficiency
>80% at maximum load, and 120VAC 60Hz
Meets Level V requirements


Hold-up time:
10mS minimum at maximum load and 120VAC, 60Hz

ENVIRONMENTAL:

Temperature

Operation	0 to +40°C
Non-operation	-25 to +65°C
Humidity	5 to 90%

Dimension Diagram Unit: mm (inch)



EMC

FCC Part 15 Class B
EN55022 Class B

Immunity EN50082-1

ESD:	EN61000-4-2.	Level 3
RS:	EN61000-4-3.	Level 2
EFT:	EN61000-4-4.	Level 2
Surge:	EN61000-4-5.	Level 3
CS:	EN61000-4-6.	Level 2
Voltage Dips	EN61000-4-11	
Harmonic:	EN61000-3-2	Class A

Isolation Test

Primary to Secondary: 3000VAC for 1 second 10mA

Insulation Resistance

Primary to Secondary: >10M OHM 500VDC

FEATURE:

Over Voltage/Current, Short Circuit Protection

The output is equipped with short circuit protection and overload protection as per IEEE802.3af specifications and conforms to UL60950-2. The output can be shorted permanently without damage. This unit is not equipped with detection and may not be used in situation where it may be connected to non-PoE ready devices.

Indicator

Solid Green: Power "ON"

Data in/Output Connector

RJ45

Output Connection

+pin 4,5 / -pins 7,8

Warranty

1 Year

Interchangeable AC Clips (Sold Separately)

RPA: US	RPI: India
RPB: Brazil	RPK: UK
RPC: China	RPN: Argentina
RPE: Europe	RPS: Australia
RPH: Korea	RPX: C8