



## 30W Passive Power over Ethernet Adapter Lowest Cost IEEE802.3at Power



### Features

- Compliant with the IEEE802.3at Standard
- Level V Efficiency
- Very Low leakage
- Non-Vented Case
- Very Low Cost
- 2 Wire or 3 Wire Options
- Full Protection OCP, OVP
- 1 Year Warranty

### Applications

- IP Telephones (W Model Recommended)
- Wireless Network Access Points
- Blue Tooth Access Point
- Security Camera
- IP Print Servers
- Wimax APs

### Safety Approvals

- cUL/UL
- CE

### Mechanical Characteristics

- Length: 140mm (5.51in)
- Width: 65mm (2.55in)
- Height: 36mm (1.42in)
- Weight: 225g (0.44lb.)

### Output Specifications

Model Number	Output Voltage	Output Current	Input Connector
POE31U-240	24V	1.25A	3 Wire C13
POE31U-560	56V	0.54A	3 Wire C13
POE31W-240	24V	1.25A	2 Wire C8
POE31W-560	56V	0.54A	2 Wire C8

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at [www.phihong.com](http://www.phihong.com) for the most up-to-date specifications and contact information.

**INPUT:**

**AC Input Voltage Range**  
90 to 264VAC

**AC Input Voltage Rating**  
100 to 240VAC, 47-63Hz

**AC Input Current**  
0.8A (RMS) maximum for 120VAC  
0.5A (RMS) maximum for 240VAC

**Leakage Current**  
W models 250uA maximum @ 264VAC 60Hz  
U models 350uA maximum @ 264VAC 60Hz

**AC Inrush Current**  
30A (RMS) maximum for 115VAC  
60A (RMS) maximum for 240VAC

**OUTPUT:**

**Total Output Power**  
30W

**Output Ripple**  
24V            240mVp-p  
56V            560mVp-p

**Efficiency**  
Meets Level V Efficiency Requirements

**Hold-up Time**  
10mS min. 120VAC and maximum load

**ENVIRONMENTAL:**

**Temperature**  
Operation            0 to +40°C  
Non-operation       -25 to +65°C

**Humidity**  
Operation            20 to 90%

**EMC**

FCC Part 15 Class B  
EN55022 Class B

**Isolation Test**

Primary to Secondary: 1500VAC for 1 minute 10mA (U)  
Primary to Secondary: 3000 VAC for 1 minute (W models)  
Primary to F.G.: 1500VAC for 1 minute (U models)  
Output to F.G.: 1500VAC (U models)

**Immunity**

ESD:                EN61000-4-2. Level 3  
RS:                 EN61000-4-3. Level 2  
EFT:                EN61000-4-4. Level 2  
Surge:              EN61000-4-5. Level 3  
CS:                 EN61000-4-6. Level 2  
Voltage Dips       EN61000-4-11  
Harmonic:         EN61000-3-2 Class A

**Insulation Resistance**

Primary to Secondary: >10M OHM 500VDC  
Primary to Field Ground: >10M OHM 500VDC

**FEATURE:**

**Over Voltage/Current, Short Circuit Protection**

Outputs equipped with short circuit protection and overload protection.

The output can be shorted permanently without damage

**Input Connector**

IEC320 C12 for U Models  
IEC320 C8 for W Models

**Output Connection**

+pins 4, 5  
-pins 7, 8

**Warranty**

1 Year

**Dimension Diagram Unit: mm (inch)**

