

**Micro Commercial Components** 

Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939

# HER201G **THRU** HER208G

## **Features**

- Lead Free Finish/Rohs Compliant (Note1) ("P"Suffix designates Compliant. See ordering information)
  High Surge Current Capability
  High Reliability
  Low Forward Voltage Drop

- Halogen free available upon request by adding suffix "-HF" Epoxy meets UL 94 V-0 flammability rating Moisture Sensitivity Level 1

## **Maximum Ratings**

- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C
- For capacitive load, derate current by 20%


MCC	Device	Maximum	Maximum	Maximum
Catalog	Marking	Recurrent	RMS	DC
Number		Peak Reverse	Voltage	Blocking
		Voltage	_	Voltage
HER201G	HER201G	50V	35V	50V
HER202G	HER202G	100V	70V	100V
HER203G	HER203G	200V	140V	200V
HER204G	HER204G	300V	210V	300V
HER205G	HER205G	400V	280V	400V
HER206G	HER206G	600V	420V	600V
HER207G	HER207G	800V	560V	V008
HER208G	HER208G	1000V	700V	1000V

### Electrical Characteristics @ 25°C Unless Otherwise Specified-

			<b>-</b>
Average Forward	$I_{F(AV)}$	2 A	T <sub>A</sub> = 55°C
Current			
Peak Forward Surge	$I_{FSM}$	60A	8.3ms, half sine
Current			
Maximum			
Instantaneous			
Forward Voltage			
HER201G-204G	$V_{F}$	1.0V	$I_{FM} = 2.0A;$
HER205G		1.3V	T <sub>A</sub> = 25°C
HER206G - 208G		1.7V	- A
Reverse Current At	I <sub>R</sub>	5μΑ	T <sub>A</sub> = 25°C
Rated DC Blocking		150μΑ	T <sub>A</sub> = 125°C
Voltage (Maximum DC)		Ισορικ	14 120 0
Maximum Reverse			
Recovery Time			
HER201G-205G	$T_{rr}$	50ns	$I_F=0.5A, I_R=1.0A,$
HER206G-208G		75ns	I <sub>rr</sub> =0.25A
Typical Junction			
Capacitance			
HER201G-205G	$\mathbf{C}_{J}$	50pF	Measured at
HER206G-208G		30pF	1.0MHz, V <sub>R</sub> =4.0V

2.0 Amp Glass **Passivated High Efficient Rectifiers** 50 to 1000 Volts





DIMENSIONS							
	INCHES		MM				
DIM	MIN	MAX	MIN	MAX	NOTE		
Α	.230	.300	5.8	7.6			
В	.104	.140	2.6	3.6			
С	.028	.034	0.71	0.86			
D	1.000		25.40				

\*Pulse Test: Pulse Width 300µsec, Duty Cycle 1% Note: 1. High Temperature Solder Exemptions Applied, see EU Directive Annex 7.




# HER201G THRU HER208G

## **Micro Commercial Components**

### RATINGS AND CHARACTERISTIC CURVES

#### FIG.1- REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM



NOTES: 1. Rise Time=7ns max. Input Impedance= 1 megohm 22pf 2. Rise Time=10ns max. Sourse Impedan 50 ohms







FIG.2- MAXIMUM AVERAGE FORWARD CURRENT DERATING




#### FIG.3- TYPICAL REVERSE CHARACTERISTICS










Revision: B







## **Ordering Information:**

Device	Packing
Part Number-TP	Tape&Reel: 4Kpcs/Reel
Part Number-AP	Ammo Packing: 3Kpcs/Ammo Box
Part Number-BP	Bulk: 25Kpcs/Carton

Note: Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

#### \*\*\*IMPORTANT NOTICE\*\*\*

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. Micro Commercial Components Corp. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp* . and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.