


Capacitive sensor BC20-Q20-AZ3X2


TURCK

Industrial
Automation



- Rectangular, height 20 mm
- Active face on top
- Plastic, PBT-GF30-V0
- Fine adjustment via potentiometer
- AC 2-wire, 20...250 VAC
- NO contact
- Cable connection

Wiring diagram



Functional principle

Capacitive proximity switches are designed for non-contact and wear-free detection of electrically conductive as well as non-conductive metal objects.

Type code	BC20-Q20-AZ3X2
Ident no.	4352000
Rated operating distance S_n	20 mm
Rated operating distance S_n	20 mm, non-flush mounting
Assured sensing range	$\leq (0.72 \times S_n)$ mm
Hysteresis	2...20 %
Temperaturdrift	type $\leq \pm 20$ %
Repeatability	≤ 2 % of full scale
Ambient temperature	-25...+70 °C
Operating voltage	20...250 VAC
AC rated operational current	≤ 500 mA
Frequency	≥ 50 ... ≤ 60 Hz
Smallest operating current I_m	≤ 5 mA
Residual current	≤ 1.7 mA
Switching frequency	0.02 kHz
Rated insulation voltage	≤ 1.5 kV
Output function	2-wire, NO contact, 2-wire
Voltage drop at I_m	≤ 7 V
Design	rectangular, Q20
Dimensions	68x 40x 20 mm
Housing material	Plastic, PBT
Material active face	Plastic, PBT
Connection	cable
Cable quality	$\varnothing 5.2$, LifYY, PVC, 2 m
Cable cross section	3 x 0.34 mm ²
Vibration resistance	55 Hz (1 mm)
Shock resistance	30 g (11 ms)
Protection class	IP67
MTTF	1080 years acc. to SN 29500 (Ed. 99) 40 °C
Operating voltage	LED green
Switching state	• red
Included in scope of supply	MH-Q20

**Capacitive sensor
BC20-Q20-AZ3X2**

TURCK

Industrial
Automation

Accessories

Type code	Ident no.	Description	Dimension drawing
MW-Q14/Q20	6945006	Mounting bracket for rectangular Q14 or Q20; material VA 1.4301	
MH-Q20MONTAGEHÜLSEN	6950010	Mounted with active face downwards, for Q20	