



**Signal processor
MK96 for flow sensors
MK96-LI01**



- For connection of a standard flow sensor
- Adjustment via potentiometer
- 6 LEDs for display of the flow state
- 2-wire DC, 19.2...28.8 VDC
- 4...20 mA analog output

Wiring diagram



Functional principle

Signal processors not only supply insertion and inline sensors with voltage, they also process and display the measured signals. Devices with MK96..., MS96... and MC96... housing styles are available. The individual housing styles are designed for different operating voltages and feature various output and supplementary functions. For intrinsically safe flow sensors it is required to use signal processors with intrinsically safe control circuits of the series MS96...Ex... and MC96...Ex... .

Type code	MK96-LI01
Ident no.	7525004
Ambient temperature	-20 ... 60 °C
Operating voltage	19.2...28.8VDC
No-load current I ₀	≤ 100 mA
Output function	Analog output, 4 ... 20 mA
Current output	4...20mA
Load	≤ 500 Ω
Protection class	IP20
Protection class (terminals/housing)	IP20 / IP40
Design	terminal chamber
Dimensions	70x 18x 89 mm
Housing material	Polycarbonate/ABS
Connection	Terminal chamber
Flow state display	LED chain, red (1x), yellow (1x), green (4x)
LED display	red = 4 mA yellow > 4 mA 1x green > 8 mA 2x green > 12 mA 3x green > 16 mA 4x green = 20 mA