

The 1-channel Ex-temperature measuring amplifier IM34-11EX-CI is designed to evaluate the temperature-dependent variations of resistance thermo detectors (RTD) Ni100/Pt100, thermoelement types B, E, J, K, L, N, R, S and T or low voltages in a range of -160...+160 mV and to output them as linear temperature current signals 0/4...20 mA.

Resistance thermo detectors Ni100/Pt100 in 2, 3 or 4-wire-technology can be operated alternatively at the input circuit of the measuring amplifier. The Ni100/Pt100 input can either be used as external cold junction compensation for the thermoelement or as independent measuring input.

The device can be configured and parametrized via PC with the software tool Device Type Manager (DTM). For this, the device is connected to the PC via the 3.5 mm jack plug at the front (the matching transmission cable IM-PROG III can be ordered separately from TURCK).

The following settings are available:

- Connection mode (2, 3 and 4-wire technology)
- Lower limit
- Upper limit
- Input circuit monitoring for wire-break
- Current output adjustable in the event of input circuit errors: 0 resp. > 22 mA
- Internal or external cold junction compensation
- Output current (0/4...20 mA)
- Temperature indicated in °C or °K
- Mode (resistance, thermocouples, low voltage, line compensation)

The signals are transformed according to ITS 90/IEC 584 for thermoelements and IEC 751 for Pt100 RTDs and provided as temperature linear signals at the current output.

- Intrinsically safe input circuits Ex ia
- Application area acc. to ATEX: II (1) G; II (1) D
- Installation in zone 2
- Input for Pt100/ Ni100 resistors, thermocouples and millivolt signals in 2, 3 or 4-wire technology
- Output circuit: 0/4...20 mA
- Parametrized via FDT/DTM
- HART®
- Removable terminal blocks
- Complete galvanic separation

Ex-Temperature measuring amplifier

1-channel

IM34-11EX-CI

Type code	IM34-11EX-CI
Ident no.	7506633

Operating voltage	20...250 VAC
Frequency	40...70 Hz
Operating voltage range	20...125 VDC
Power consumption	≤ 3 W

Input circuits	intrinsically safe acc. to EN 50020
	thermocouple
Pt100	Pt100
Ni100	Ni100
Probe current	(IEC 751), 2, 3 and 4-wire technology
Thermoelements	(DIN 43760), 2, 3 and 4-wire technology
Voltage input	≤ 0.2 mA
	B, E, J, K, N, R, S, T (ITS 90/IEC 584), L (DIN 43710)
	-0.160...+0.160 VDC

Output circuits	
Output current	0/4...20 mA
Load resistance current output	≤ 0.6 kΩ
Fault current	0 / 22 mA adjustable


Reference temperature	23 °C
Accuracy current output	± 5 µA
Temperature drift analogue output	0.0025 %/K
Temperature drift RTD input	± 3 mΩ/K
Temperature drift TC input	3.2 µV / K (of 320mV)
Accuracy RTD input	± 50 mΩ
Accuracy TC input	± 15 µV
Cold junction compensation error	2-wire < 100mΩ after line compensation 3-wire < 100mΩ with asymmetrical wiring 4-wire < 50mΩ with cold junction compensation with IM-3-CJT < 1K

Galvanic separation	
Test voltage	2.5 kV

Ex approval acc. to conformity certificate	TÜV 02 ATEX 1898									
Application area	II (1) G, II (1) D									
Protection type	[Ex ia Ga] IIC ; [Ex ia Da] IIIC ;									
Max. output voltage U _o	≤ 5 V									
Max. output current I _o	≤ 2.5 mA									
Max. output power P _o	≤ 3 mW									
Rated voltage	250 V									
Characteristic	linear									
Internal inductance/capacitance L/C _i	negligibly small									
External inductance/capacitance L _e /C _e	<table border="1"> <tr> <td></td><td>EEx ia IIC</td><td>EEx ia IIB</td></tr> <tr> <td>Lo [mH]</td><td>1000</td><td>1000</td></tr> <tr> <td>Co [µF]</td><td>100</td><td>1000</td></tr> </table>		EEx ia IIC	EEx ia IIB	Lo [mH]	1000	1000	Co [µF]	100	1000
	EEx ia IIC	EEx ia IIB								
Lo [mH]	1000	1000								
Co [µF]	100	1000								

Ex approval acc. to conformity certificate	TÜV 06 ATEX 552978 X									
Application area	II 3 G									
Protection class for belonging equipment	Ex nA [ic Gc] IIC T4									
Max. output voltage U _o	≤ 5 V									
Max. output current I _o	≤ 2.5 mA									
Max. output power P _o	≤ 3 mW									
Internal inductance/capacitance L/C _i	negligibly small									
External inductance/capacitance L _e /C _e	<table border="1"> <tr> <td>Ex ic</td><td>IIC</td><td>IIB</td></tr> <tr> <td>Lo [mH]</td><td>100</td><td>100</td></tr> <tr> <td>Co [µF]</td><td>3.6</td><td>18</td></tr> </table>	Ex ic	IIC	IIB	Lo [mH]	100	100	Co [µF]	3.6	18
Ex ic	IIC	IIB								
Lo [mH]	100	100								
Co [µF]	3.6	18								

Ex approval acc. to conformity certificate	IS-1.106
--	----------

Dimensions

Ex-Temperature measuring amplifier
1-channel
IM34-11EX-CI


Indication

Operational readiness	green
Error indication	red

Protection class

Ambient temperature	IP20
Storage temperature	-25...+70 °C
Dimensions	-40...+80°C
Weight	104x 18x 110 mm
Mounting instruction	147 g
Housing material	For mounting on DIN rail or mounting panel
Electrical connection	Polycarbonate/ABS
Terminal cross-section	4 x 3-pole removable terminal blocks, reverse polarity protected, screw connection
Tightening torque	1 x 2.5 mm ² / 2 x 1.5 mm ²
	0.5 Nm

Accessories

Type code	Ident no.	Description	Dimension drawing
IM-PROG III	7525111	The programming adapter IM-PROG III is used for parametrization of TURCK IM and IMB devices via FDT/DTM and for galvanic separation.	
IM-CC-3X2BU/2BK	6900475	Cage clamp terminals for IM modules (Ex devices; width 18 mm): 2 blue/2 black, 3-pin, included in delivery.	