


PRODUCT SPECIFICATION


DATE : 09/05/2007

COSMO ELECTRONICS CORPORATION	SOLID STATE RELAY - MOSFET OUTPUT KAQY216	NO.60M00020	REV. 2
		SHEET 1 OF 7	

● OUTSIDE DIMENSION :



● Turn On / Turn Off time



● Absolute Maximum Ratings

(Ta=25°C)

Emitter (Input)	Detector (Output)
Reverse Voltage 5.0V	Output Breakdown Voltage ± 600V
Continuous Forward Current 50mA	Continuous Load Current ± 120mA
Peak Forward Current 1A	Power Dissipation 500mW
Power Dissipation 100mW	
Derate Linearly from 25°C 1.3mW/°C	

General Characteristics

Isolation Test Voltage 5000VACrms	Storage Temperature Range -40°C to +125°C
Isolation Resistance Vio=500V, Ta=25°C $\geq 10^{10}\Omega$	Operating Temperature Range ... -40°C to +85°C
Total Power Dissipation 550mW	Junction Temperature 100°C
Derate Linearly from 25°C 2.5mW/°C	Soldering Temperature , 2mm from case , 10 sec 260°C

PRODUCT SPECIFICATION

DATE : 09/05/2007



COSMO ELECTRONICS CORPORATION	SOLID STATE RELAY - MOSFET OUTPUT KAQY216	NO.60M00020	REV. 2
		SHEET 2 OF 7	

● Electro-optical Characteristics

(Ta=25°C)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit.
Emitter (Input)						
Forward Voltage	V_F	$I_F=10\text{mA}$		1.2	1.5	V
Operation Input Current	I_{FON}	$V_L=\pm 20\text{V}$, $I_L=100\text{mA}$, $t=10\text{mS}$			5.0	mA
Recovery Input Current	I_{FOFF}	$V_L=\pm 20\text{V}$, $I_L \leq 5\mu\text{A}$	0.2			mA
Detector (Output)						
Output Breakdown Voltage	V_B	$I_B=50\mu\text{A}$	600			V
Output Off-State Leakage	I_{TOFF}	$V_T=100\text{V}$, $I_F=0\text{mA}$		0.2	1	μA
I/O Capacitance	C_{ISO}	$I_F=0$, $f=1\text{MHz}$		6		pF
ON Resistance	R_{ON}	$I_L=100\text{mA}$, $I_F=10\text{mA}$		35	50	Ω
Turn-On Time	T_{ON}	$I_F=10\text{mA}$, $V_L=\pm 20\text{V}$ $t=10\text{ms}$, $I_L=\pm 100\text{mA}$		0.3	1.0	ms
Turn-Off Time	T_{OFF}			0.5	1.5	ms

● MOS Relay Schematic and Wiring Diagrams

Schematic	Output configuration	Load	Connection	Wiring Diagrams
	1a	AC/DC	-	 

PRODUCT SPECIFICATION

DATE : 09/05/2007


COSMO ELECTRONICS CORPORATION	SOLID STATE RELAY - MOSFET OUTPUT KAQY216	NO.60M00020	REV. 2
		SHEET 3 OF 7	

● Data Curve

Load current vs. ambient temperature

Allowable ambient Temperature :

-40°C to +85°C




Ambient temperature Ta (°C)

On resistance vs. ambient temperature across terminals 3 and 4 pin

LED current : 5mA

Continuous load current : 120mA (DC)




Ambient temperature Ta (°C)

Turn On Time vs. ambient temperature

Load voltage 600V (DC)

LED current : 5mA

Continuous load current : 120mA (DC)




Ambient temperature Ta (°C)

Turn Off Time vs. ambient temperature

Load voltage 600V (DC)

LED current : 5mA

Continuous load current : 120mA (DC)



Ambient temperature Ta (°C)

PRODUCT SPECIFICATION

DATE : 09/05/2007


COSMO ELECTRONICS CORPORATION	SOLID STATE RELAY - MOSFET OUTPUT KAQY216	NO.60M00020	REV. 2
SHEET 4 OF 7			

LED operate current vs.

ambient temperature

Load Voltage : 600V (DC)

Continuous load current : 120mA (DC)




Ambient temperature Ta (°C)

LED Turn Off current vs.

ambient temperature

Load Voltage : 600V (DC)

Continuous load current : 120mA (DC)




Ambient temperature Ta (°C)

LED dropout voltage vs.

ambient temperature

LED current : 5 to 50mA




Ambient temperature Ta (°C)

Voltage vs. current characteristics of output at MOSFET portion

Measured portion : across terminals 3 and 4 pin

Ambient temperature : 25°C



Ambient temperature : 25°C

PRODUCT SPECIFICATION

DATE : 09/05/2007

COSMO ELECTRONICS CORPORATION	SOLID STATE RELAY - MOSFET OUTPUT KAQY216	NO.60M00020	REV. 2
SHEET 5 OF 7			


LED forward current vs. Turn On Time

Across terminals 3 and 4pin


Load voltage : 600V (DC)

Continuous load current : 120mA (DC)

Ambient temperature : 25°C



Off state leakage current
Across terminals 3 and 4 pin
Ambient temperature : 25°C




LED forward current vs. Turn Off Time

Across terminals 3 and 4 pin


Load voltage : 600V (DC)

Continuous load current : 120mA (DC)

Ambient temperature : 25°C



Applied voltage vs. output capacitance
Across terminals 3 and 4 pin
Frequency : 1MHz
Ambient temperature : 25°C



PRODUCT SPECIFICATION

DATE : 09/05/2007


COSMO ELECTRONICS CORPORATION	SOLID STATE RELAY - MOSFET OUTPUT KAQY216	NO.60M00020	REV. 2
		SHEET 6 OF 7	

● USING METHODS

Examples of resistance value to control LED forward current (IF)


SSR-MOSFET OUTPUT

(IF=5mA)



E	R
3.3V	Approx. 330 Ω
5V	Approx. 640 Ω
12V	Approx. 1.9K Ω
15V	Approx. 2.5K Ω
24V	Approx. 4.1K Ω

- (1) LED forward current must be more than 5mA , at E min.
- (2) LED forward current must be less than 50mA , at E max.





PRODUCT SPECIFICATION

DATE : 09/05/2007

COSMO ELECTRONICS CORPORATION	SOLID STATE RELAY - MOSFET OUTPUT KAQY216	NO.60M00020	REV. 2
		SHEET 7 OF 7	

● USING METHODS

Regulate the spike voltage generated on the inductive load as follows :



R-C Snubber