

Ultra Miniature SMD Crystal Clock Oscillator



ASCO

1.6 x 1.2 x 0.7mm

ASCO

Moisture Sensitivity Level (MSL) – This product is Hermetically Sealed and not Moisture Sensitive - MSL = N/A: Not Applicable



RoHS Compliant

FEATURES:

- Ultra miniature package: 1.6 x 1.2 x 0.7mm
- Tri-state function
- Suitable for high density SMT
- Suitable for RoHS compliant reflow process
- Electrical beam sealed package assures extreme accuracy and high reliability

APPLICATIONS:

- CCD clock for VTR camera
- Computers and peripherals
- Portable electronics
- Mobile communication, PDA

STANDARD SPECIFICATIONS:

Common Key Electrical Specifications

Parameters		Minimum	Typical	Maximum	Units	Notes		
Frequency Range		1.0		80	MHz			
Operating Temperature		-10		+60	°C	See options		
Storage Temperature		-40		+85	°C			
Overall Frequency Stability*		-50		+50	ppm	See options		
Supply Voltage (Vdd)		2.97	3.3	3.63	V	Standard		
		2.25	2.5	2.75		Option "1"		
		1.62	1.8	1.98		Option "2"		
Supply Current (I _{dd}) into 15pF Load	Vdd = 3.3 V		3.0	4.5	mA	1MHz ≤ F ≤ 20 MHz		
			4.2	6.0		20 MHz < F ≤ 50 MHz		
			6.0	8.5		50 MHz < F ≤ 80 MHz		
	Vdd = 2.5 V		2.5	3.5		1MHz ≤ F ≤ 20 MHz		
			3.0	4.5		20 MHz < F ≤ 50 MHz		
			4.0	6.0		50 MHz < F ≤ 80 MHz		
	Vdd = 1.8 V		2.0	3.0		1MHz ≤ F ≤ 20 MHz		
			2.5	3.5		20 MHz < F ≤ 50 MHz		
			3.5	5.0		50 MHz < F ≤ 80 MHz		
	Output Load					15	pF	CMOS
	Output Voltage	V _{OH}	0.9*Vdd				V	
		V _{OL}				0.1*Vdd		
Tri-state function		"1" (VIH ≥ 0.7*Vdd) : Oscillation "0" (VIH < 0.3*Vdd) : Hi Z				Pin 1 must be pulled "high" for oscillation		
Aging		-3.0		3.0	ppm	@+25°C First year		
Symmetry @1/2Vdd		40	50	60	%	Standard		
		45	50	55		Option S		
Start-up Time				2.0	ms			
Rise/Fall Time (Tr/Tf)				5.0	ns			

*Overall frequency stability includes initial frequency tolerance @+25°C and stability over the operating temperature.

Ultra Miniature SMD Crystal Clock Oscillator



1.6 x 1.2 x 0.7mm

ASCO



RoHS
Compliant

PART IDENTIFICATION:

ASCO - [] - [] MHz - [] - [] - [] - []

Supply Voltage
Blank: 3.3V±10%
1: 2.5 V±10%
2: 1.8 V±10%

Frequency in MHz
Please specify the frequency in MHz. e.g. 14.31818MHz

Operating Temp.
Blank: -10°C ~ +60°C
E: -20°C ~ +70°C
L: -40°C ~ +85°C


Overall Freq. Stability
Blank: ±50ppm
*Y: ±10ppm
**J: ±20ppm
K: ±30 ppm

Symmetry
Blank: 40/60% @1/2Vdd
S: 45/55% @1/2Vdd

Packaging
Blank: Bulk
T3: 3000pcs/reel (Standard)
T: 1000pcs/reel (Special order. Available upon request)

*Available for -10 to +60°C only
 **Available for -10 to +60°C, option E only
 Contact Abracon for tighter frequency stability options

OUTLINE DRAWING:



Dimensions: mm

ABRACON IS
ISO 9001:2008
CERTIFIED



ABRACON
CORPORATION

Visit www.abracon.com for Terms & Conditions of Sale
 30332 Esperanza, Rancho Santa Margarita, California 92688
 tel 949-546-8000 | fax 949-546-8001 | www.abracon.com

Revised: 01.25.13

Ultra Miniature SMD Crystal Clock Oscillator




1.6 x 1.2 x 0.7mm

ASCO


Pb RoHS Compliant

REFLOW PROFILE:



TAPE & REEL:

T3= 3,000pcs/reel (Standard)
 T = 1,000pcs/reel (Special order. Available upon request)



Dimensions: mm

ATTENTION: Abracon Corporation's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.

ABRACON IS ISO 9001:2008 CERTIFIED



Visit www.abracon.com for Terms & Conditions of Sale
 30332 Esperanza, Rancho Santa Margarita, California 92688
 tel 949-546-8000 | fax 949-546-8001 | www.abracon.com
 Revised: 01.25.13