



VRLA Rechargeable Battery

EP100-12 (EP100-12FR)



FEATURES

- Absorbent Glass Mat technology for efficient gas recombination
- Maintenance free(no water topping-up required)
- No free acid(Non-spillable battery)
- Can be used in any orientation(excluding used inverted)
- The battery is designed for heavy duty cyclic application
- Flame-arrestor is installed to ensure safety
- Carry handles for easy installation
- Low self-discharge rate, lower than 3% capacity loss per month

APPLICATION

- UPS
- Telecom
- Golf-Carts



SPECIFICATIONS

Nominal Voltage	12 V
Nominal Capacity	100Ah @ 20 hour rate F.V.(1.75V/cell)
Approx. Weight	40.0Kg(88.2lbs.)
Terminals	B4 (Fitting M6 bolt & nut) I2 is optional
Internal Resistance	≤4.0mΩ (Fully Charged)
Max. Discharge Current	800 A (5 sec.)
Max. Charge Current	30 A
Operating Temperature Range	Charge : 0°C~40°C(32°F~104°F) Discharge : -20°C~50°C(-4°F~122°F) Storage. : -20°C~40°C(-4°F~104°F)
Container Material	ABS(UL94-HB, UL94-V0 is optional)

ISO 9001	
ISO14001	
UL	
CE	
<ul style="list-style-type: none"> ● IEC 60896-21/22 ● JIS C 8704-2 ● GB/T 19638.2 	

DIMENSION(mm/inch)	OUTER DIMENSIONS	TERMINAL TYPE
<ul style="list-style-type: none"> ■ Length 407±2.0 (16.02±0.08) ■ Width 173±2.0 (6.81±0.08) ■ Container Height 210±2.0 (8.27±0.08) ■ Total Height 239±2.0 (9.41±0.08) 		<p>● Terminal B4 25.0(0.98) 7.3(0.29) 10.0(0.39) 26.5(1.04) 7.0(0.28) [M6 BOLT & NUT]</p> <p>● Terminal I2 M6x1.0 2.0(0.08) [M6 BOLT]</p> <p>Terminal Hardware Initial Torque: B4,I2(5.5Nm±5%)</p>

Constant power discharge characteristics at 25 °C/77 °F Unit: W

F.V. (V/cell) \ Discharge Time	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V	1983	1193	691	291	201	112.3	58.7
1.75V	2076	1239	711	297	204	114.0	60.0
1.70V	2139	1266	724	300	206	114.6	60.3
1.65V	2189	1284	734	303	207	114.9	60.4
1.60V	2231	1297	741	304	207	114.9	60.4

Constant current discharge characteristics at 25 °C/77 °F Unit: A

F.V. (V/cell) \ Discharge Time	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V	178.7	105.6	58.07	24.25	16.75	9.36	4.89
1.75V	188.7	109.6	59.75	24.75	17.00	9.50	5.00
1.70V	194.5	112.0	60.84	25.00	17.17	9.55	5.03
1.65V	199.0	113.6	61.68	25.25	17.25	9.58	5.03
1.60V	202.8	114.8	62.27	25.33	17.25	9.58	5.03

All data shall be changed without prior notice, BB reserves the right to explain and update the information contained hereinto.