



PC Board Layout Thickness=1.6mm
Component Side Shown Tolerance±0.05mm

NOTES:

ELECTRICAL:

- VOLTAGE RATING : 125 VAC RMS.
- CURRENT RATING : 1.5 AMP.
- CONTACT RESISTANCE : 50 MILLIOHMS MAX.
- INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 500 VDC.
- DIELECTRIC STRENGTH : 1000 VAC RMS 60Hz, 1MIN.

MECHANICAL:

- HOUSING MATERIAL : PBT, UL94V-0, COLOR BLACK.
- CONTACT MATERIAL : PHOSPHOR BRONZE Ø0.46mm.
- PLATING : GOLD PLATING OVER NICKEL.
- OPERATING LIFE : 750 CYCLES MIN.
- PCB RETENTION PRE-SOLDER : 1 LB MIN.
- PCB RETENTION POST-SOLDER: 10 LBS MIN.
- LED COLOR : OPTION

ENVIRONMENTAL:

- STORAGE : -40°C TO +85°C.
- OPERATION: -40°C TO +85°C.
- WAVE SOLDERING TEMPERATURE: 230~250°C(3~5 SECONDS)
- RoHS COMPLIANT.

MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.

PART NUMBER	LED COLOR		TAB TYPE	GOLD PLATING
	LED 1	LED 2		
E5J88-A1L2F2-L	GREEN	GREEN	NO TAB	6u"
E5J88-A4L2F2-L	GREEN	GREEN	TOP & SIDE	6u"
E5J88-A4L2F4-L	GREEN	GREEN	TOP & SIDE	30u"
E5J88-C4L2F2-L	GREEN	YELLOW	TOP & SIDE	6u"
E5J88-D4L2F2-L	GREEN/RED	GREEN/RED	TOP & SIDE	6u"

DETACHED LISTS	MM (INCH)				FULL RISE ELECTRONIC CO., LTD	
	TOLERANCES EXCEPT AS NOTED					
	MM	±	RoHS Compliant		TITLE RJ45 LED JACK, 2x1PORTS	
	.0 ± 0.2	±				
.00 ± 0.15	±					
.000 ± 0.075	±	DFTO Jeri Chi DATE 07/13/2006		DRAWING NO. CE5J3021-LC-01 SIZE A3 REV 0		
ANGLES ± 0.5		SCALE : 5:3		/PART NO. SEE TABLE		
 THIRD ANGLE PROJECTION		DO NOT SCALE DRAWING		SHEET 1 OF 1		