

SMT POWER INDUCTORS

Shielded Toroid - PA0040NL Series



- **Height:** 1.8mm Max
- **Footprint:** 7.8mm x 5.2mm Max
- **Current Rating:** up to 1.84A
- **Inductance Range:** .80µH to 32.5µH

Electrical Specifications @ 25°C — Operating Temperature -40°C to +130°C

Part Number ⁴	Inductance @ Rated (µH MIN)	I _{rated} ¹ (ADC)	DCR (mΩ)		Inductance @ 0ADC (µH ±20%)	Saturation Current ² (ADC)		Heating Current ³ (ADC TYP)
			TYP	MAX		25°C	100°C	
PA0040.102NL	0.80	1.84	80	103	1.0	2.10	1.70	1.84
PA0040.222NL	1.60	1.40	115	130	2.2	1.40	1.12	1.52
PA0040.472NL	3.22	0.98	150	180	4.7	0.98	0.80	1.22
PA0040.103NL	6.96	0.67	214	240	10.0	0.67	0.56	1.04
PA0040.153NL	10.71	0.54	260	300	15.0	0.54	0.48	1.00
PA0040.223NL	15.26	0.45	310	360	22.0	0.45	0.40	0.88
PA0040.333NL	23.59	0.36	470	556	33.0	0.36	0.32	0.80
PA0040.473NL	32.48	0.31	700	833	47.0	0.31	0.26	0.72




NOTES:

1. The rated current as listed is either the saturation current or the heating current depending on which value is lower.
2. The saturation current is the current which causes the inductance to drop by 30% at the stated ambient temperatures (25°C, 100°C). This current is determined by placing the component in the specified ambient environment and applying a short duration pulse current (to eliminate self-heating effects) to the component.

3. The heating current is the dc current which causes the temperature of the part to increase by approximately 40°C. This current is determined by mounting the component on a PCB and applying the current to the device for 30 minutes without any forced air.

4. The Leaded version of these parts is available by removing the "NL" suffix when ordering.


Mechanical



Weight 0.10 grams
Tape & Reel 3,900/reel

Dimensions: Inches/mm
Unless otherwise specified, all tolerances are $\pm \frac{.01}{.25}$

Typical Inductance vs. DC Bias



For More Information:

Pulse Worldwide Headquarters	Pulse Northern Europe	Pulse Southern Europe	Pulse China Headquarters	Pulse North China	Pulse South Asia	Pulse North Asia
12220 World Trade Drive San Diego, CA 92128 U.S.A. www.pulseeng.com TEL: 858 674 8100 FAX: 858 674 8262	3 Huxley Road Surrey Research Park Guildford, Surrey GU2 5RE United Kingdom	Zone Industrielle F-39270 Orgelet France	No. 1 Industrial District Changan, Dongguan China	Room 1002 No. 819 Nanjing West Rd Shanghai China	150 Kampong Ampat #07-01/02 KA Centre Singapore 368324	3F-4, No. 81, Sec. 1 Hsin Tai Wu Road Hsi-Chih Taipei Hsien Taiwan
TEL: 858 674 8100 FAX: 858 674 8262	TEL: 44 1483 401700 FAX: 44 1483 401701	TEL: 33 3 84 35 04 04 FAX: 33 3 84 25 46 41	TEL: 86 769 5538070 FAX: 86 769 5538870	TEL: 86 21 32181071 FAX: 86 21 32181396	TEL: 65 6287 8998 FAX: 65 6280 0080	TEL: 886 2 26980228 FAX: 886 2 26980948

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners.

© Copyright, 2006. Pulse Engineering, Inc. All rights reserved.