

# HIGH FREQUENCY PLANAR TRANSFORMERS

## PA003X Series (up to 30W)



- Power Rating:** up to 30W
- Height:** 7.4mm Max
- Footprint:** 19.6mm x 18.0mm Max
- Frequency Range:** 200kHz to 750kHz

### Electrical Specifications @ 25°C — Operating Temperature -40°C to 125°C

Part Number	Power Rating	Turns Ratio <sup>1</sup> (Pri:Sec)	Primary Secondary Isolation	Primary Inductance (μH MIN)	Leakage Inductance (μH MAX)	DCR (mΩ MAX)			Maximum Height (mm)
						Primary	Primary Aux.	Secondary	
PA0030	30W 24v to 3.3v/8A	6:2	1500 V <sub>DC</sub> Operational	52	0.85	43	N/A	2.7	7.4
PA0031	30W 48v to 3.3v/8A	12:2	1500 V <sub>DC</sub> Operational	200	1.7	210	N/A	3.5	7.4
PA0032 <sup>2</sup>	30W 24v to 5.0v/6A	6:3	1500 V <sub>DC</sub> Operational	52	0.27	43	N/A	10*	7.4
PA0033 <sup>2</sup>	30W 48v to 5.0v/6A	12:3	1500 V <sub>DC</sub> Operational	200	0.925	210	N/A	10*	7.4
PA0034	30W 24v to 12v/2.5A	6:6	1500 V <sub>DC</sub> Operational	52	0.27	43	N/A	43	7.4
PA0035	30W 48v to 12.0v/2.5A	12:8	1500 V <sub>DC</sub> Operational	200	0.98	210	N/A	75	7.4
PA0036	30W 24v to 15v/2.0A	6:8	1500 V <sub>DC</sub> Operational	52	0.195	43	N/A	75	7.4
PA0037	30W 48v to 15v/2.0A	12:8	1500 V <sub>DC</sub> Operational	200	0.98	210	N/A	75	7.4




\*DCR rating for indicated parts is for both windings tied in parallel.

NOTES: 1. Other turns ratios may be available. Contact Pulse Applications Engineering for more information.

2. The secondary windings on PA0032 and PA0033 can be connected in series for a 6T secondary if required.


3. Optional Tape & Reel packaging can be ordered by adding a "T" suffix to the part number, (i.e. PA0037T).

### Mechanical




SUGGESTED PAD LAYOUT - (PA0032/33)

### Schematics



PA0030/31/34/35/36/37




PA0032/33

Weight ..... 4.5 grams  
Tape & Reel ..... .250/reel  
Tray ..... .90/tray

Dimensions:  $\frac{\text{Inches}}{\text{mm}}$

Unless otherwise specified, all tolerances are  $\pm \frac{.010}{0.25}$

### TAPE & REEL LAYOUT



### For More Information:

#### Pulse Worldwide Headquarters

12220 World Trade Dr.  
San Diego, CA 92128  
U.S.A.

[www.pulseeng.com](http://www.pulseeng.com)

Tel: 858 674 8100

Fax: 858 674 8262

#### Pulse Europe

Einsteinstrasse 1  
D-71083 Herrenberg  
Germany

Tel: 49 7032 7806 0

Fax: 49 7032 7806 12

#### Pulse China Headquarters

B402, Shenzhen  
Tech-Innovation International  
Tenth Kejinan Rd.  
High-Tech Industrial Park  
Nanshan District, Shenzhen  
China

Tel: 86 755 33966678

Fax: 86 755 33966700

#### Pulse North China

Room 1503  
XinYin Building  
No. 888 YiShan Rd.  
Shanghai 200233  
China

Tel: 86 21 54643211/2

Fax: 86 21 54643210

#### Pulse South Asia

150 Kampong Ampat  
#07-01/02  
KA Centre  
Singapore 368324

Tel: 65 6287 8998

Fax: 65 6280 0080

#### Pulse North Asia

No. 26  
Kao Ching Rd.  
Yang Mei Chen  
Tao Yuan Hsien  
Taiwan, R. O. C.

Tel: 886 3 4641811

Fax: 886 3 4641911

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2007. Pulse Engineering, Inc. All rights reserved.