

Common Mode Chokes For ADSL and VDSL



- RoHS peak reflow solder temperature rating 245°C
- RoHS peak wave solder temperature rating 260°C
- For use in XDSL interfaces
- Effective reduction of C.M. noise caused by AM broadcast or ham radio
- Isolation 1500V line to line

Electrical Specifications @ 25°C - Operating Temperature -40°C to +85°C



RoHS Compliant Part No.	C.M. Attenuation (dB TYP)			Isolation Voltage (Vrms)	Mounting
	@ 500kHz	@ 1kHz	@ 10kHz		
B4001NL	45	49	35	1500	THT
B4003NL	45	49	35	1500	SMT
BX4053NL	45	49	35	150	SM

Notes: Surge Voltage Capability - Metallic: 800Vpeak 10/560sec. Long.: 2400Vpeak 10/700sec. BX4053NL is a dual choke. Please add the suffix "T" for Tape & Reel orders (i.e. B4003NL becomes B4003NLT).

Mechanical

Schematic

B4001NL



Weight2.2grams

Tube60/tube

Dimensions: $\frac{\text{Inches}}{\text{mm}}$

Unless otherwise specified,
all tolerances are $\pm \frac{.010}{0,25}$

USA 858 674 8100

Germany 49 7032 7806 0

Singapore 65 6287 8998

Shanghai 86 21 62787060

China 86 755 33966678



Taiwan 886 3 4356768

Common Mode Chokes For ADSL and VDSL

Mechanicals (continued)

Schematics

B4003NL





Weight1.0grams
Tape & Reel425/reel
Tube50/tube

Dimensions: $\frac{\text{Inches}}{\text{mm}}$

Unless otherwise specified,
all tolerances are $\pm \begin{matrix} .010 \\ 0,25 \end{matrix}$

BX4053NL



Weight2.1grams
Tape & Reel400/reel
Tube50/tube

Dimensions: $\frac{\text{Inches}}{\text{mm}}$

Unless otherwise specified,
all tolerances are $\pm \begin{matrix} .010 \\ 0,25 \end{matrix}$

For More Information

Pulse Worldwide Headquarters
12220 World Trade Drive
San Diego, CA
92128
U.S.A.

Pulse Europe
Einsteinstrasse 1
D-71083 Herrenberg
Germany
Tel: 49 7032 78060
Fax: 49 7032 7806 135

Pulse China Headquarters
B402, Shenzhen Academy of
Aerospace Technol-
ogy Bldg.
10th Kejian Road
High-Tech Zone
Nanshan District
Shenzhen, PR China
518057
Tel: 86 755 33966678
Fax: 86 755 33966700

Pulse North China
Room 2704/2705
Super Ocean Finance
Ctr.
2067 Yan An Road
West
Shanghai 200336
China
Tel: 86 21 62787060
Fax: 86 2162786973

Pulse South Asia
135 Joo Seng Road
#03-02
PM Industrial Bldg.
Singapore 368363
Tel: 65 6287 8998
Fax: 65 6287 8998

Pulse North Asia
3F, No. 198
Zhongyuan Road
Zhongli City
Taoyuan County 320
Taiwan R. O. C.
Tel: 886 3 4356768
Fax: 886 3 4356823 (Pulse)
Fax: 886 3 4356820 (FRE)

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2012. Pulse Electronics, Inc. All rights reserved.