2.4 GHz External Vehicle or Enclosure Direct Mount Antenna

Pulse Part Number SLPT2400DMN





Pulse is proud to introduce the SLPT (Shadow Low Profile Transit) product line for Public Safety, WLAN, LTE and 3G/4G applications. These rugged, aesthetically pleasing antennas provide a smaller, slimmer option to our current LPT product line without sacrificing mechanical or electrical performance. The product line includes both NMO and tamper-proof direct mount products, which will support multiple cable and connector options.

SLPT antennas were designed to perform over the highpercentage bandwidth applications prevalent in the market today. As a new product line, these antennas were created specifically to serve emerging applications such as 700 MHz Public Safety, LTE, Smart Grid and WLAN. These valueoriented antennas provide a cost-effective, high-performance solution for LTE and 802.11n MIMO applications as well.

Features

- Direct mount models
- Multiple and dual frequency products available
- Shorter, slimmer profile without sacrificing mechanical performance
- IP-67 rating when installed to compliant surface
- RoHS Compliant Product

Applications

- Public Safety & LTE
- 802.11n Applications
- M2M and Smart Metering

San Diego, CA 858 674 8100

1

Vancouver, WA 360 944 7551

Europe 49 7032 7806 0

Asia 86 755 33966678

North Asia 886 3 4356768

China 86 512 6807 9998

2.4 GHz External Vehicle or Enclosure Direct Mount Antenna

Pulse Part Number SLPT2400DMN

Electrical Specifications

| Frequency [MHz] | 2400 - 2500 |
|--------------------------------|-------------|
| Nominal Impedance [Ω] | 50 |
| Gain [dBi avg] | 4.3 |
| VSWR | 2.0:1 |
| Polarization | Vertical |
| Horizontal Plane | Omni |
| Power Rating [W] | 10 |

Environmental Specifications

| Operating Temperature [°C] | -40 to +85 |
|----------------------------|------------|
| Storage Temperature [°C] | -40 to +85 |
| Relative Humidity [%] | 100 |

Mechanical Specifications

| Radome Material | PC + ABS Plastic |
|--------------------|--|
| Color | Black |
| Ingress Protection | IP-67 |
| Weight [oz/g] | 4.6 / 130.4 |
| Dimensions [In/mm] | 2.5 H x 1.5 Ø base / 63.5 x 38.1 Ø base |
| Mounting | Direct 3/4" (19.05 mm) hole |
| Connector | N Female |

NOTE: Performance measurements are taken on an 18" (450 mm) diameter ground plane. A similar ground plane size is recommended for optimal performance.

Radiation Pattern

Elevation Plane



