

200mA High Speed "Green Operation" LDO Voltage Regulators

★ GreenOperation Compatible

■ GENERAL DESCRIPTION

The XC6217 series are precise, low noise, high speed, low dropout regulators with green operation (GO) function. They are fabricated using Torex's CMOS process. Performance features of the series include high ripple rejection and low dropout voltage, and the series include a reference voltage source, an error amplifier, a current limiter, and a phase compensation circuit.

GO provides high speed operation, low power consumption and high efficiencies by automatically switching between a high speed mode (HS) and a power save mode (PS) depending upon the load current level. The switching point of the GO to the output current is being fixed inside the IC. When only high-speed operation is required, it can be fixed by inputting a high level signal to the GO pin, thus providing operating conditions with the most suitable level of supply current for the application.

The CE function enables the output to be turned off resulting in greatly reduced power consumption. In this state, with the XC6217 series B/D Type, the IC turns on the internal switch located between the V_{OUT} and V_{SS} pins. This short enables the electric charge at the output capacitor (C_L) to be discharged via the internal auto-discharge resistance, and as a result the V_{OUT} pin quickly returns to the V_{SS} level. The series' output stabilization capacitor (C_L) is also compatible with low ESR ceramic capacitors.

Output voltage is selectable in 0.05V increments within a range of 0.80V~4.00V, using laser trimming technologies.

The current limiter's foldback circuit also operates as a short circuit protection for the output current limiter and the output pin.


■ APPLICATIONS

- Cellular phones
- Cordless phones
- Wireless communication equipment
- Portable games
- Cameras, VCRs
- Portable AV equipment
- PDAs


■ FEATURES

Output Current	: 200mA <Limit: 250mA TYP.>
Dropout Voltage	: 80mV@ $I_{OUT}=100mA$, $V_{OUT}=3.0V$
Operating Voltage Range	: 1.6V ~ 6.0V (0.8V $\leq V_{OUT} \leq$ 1.55V 1.8V ~ 6.0V (1.6V $\leq V_{OUT} \leq$ 4.0V)
Output Voltage Range	: 0.80V~4.00V (0.05V increments)
Accuracy	: $\pm 2\%$ (HS: $V_{OUT} \geq 2.00V$) (Standard) $\pm 30mV$ (HS: $V_{OUT} \leq 1.95V$) (Standard) $\pm 2.5\%$, -3.5% (PS: $V_{OUT} \geq 2.60V$) (Standard) $\pm 3.5\%$, -4.5% (PS: $1.60 \leq V_{OUT} \leq 2.55V$) (Standard) $\pm 70mV$, -90mV (PS: $0.80 \leq V_{OUT} \leq 1.55V$) (Standard) $\pm 1\%$ (HS: $V_{OUT} \geq 2.00V$) (High Accuracy) $\pm 20mV$ (HS: $V_{OUT} \leq 1.95V$) (High Accuracy) $\pm 1.5\%$, -2.5% (PS: $V_{OUT} \geq 2.60V$) (High Accuracy) $\pm 2.5\%$, -3.5% (PS: $1.60 \leq V_{OUT} \leq 2.55V$) (High Accuracy) $\pm 50mV$, -70mV (PS: $0.80 \leq V_{OUT} \leq 1.55V$) (High Accuracy)
Low Power Consumption	: TYP.4.5 μA when PS mode TYP.25 μA when HS mode
Standby Current	: Less than 0.1 μA
High Ripple Rejection	: 70dB @ 1kHz (When HS mode)
Low ESR Capacitor	: 1.0 μF Ceramic capacitor
Regulators with Green Operation (GO) Function	
C_L High-Speed-Discharge (XC6217B/D)	
Operating Ambient Temperature	: -40°C~+85°C
Packages	: USP-4D, SOT-25(XC6217 Series A/B Type) SSOT-24,USPN-4(XC6217 Series C/D Type)
Environmentally Friendly	: EU RoHS Compliant, Pb Free


■ TYPICAL APPLICATION CIRCUIT






■ TYPICAL PERFORMANCE CHARACTERISTICS



■PIN CONFIGURATION



The USP-4D heat dissipation pad is recommended to solder in use of the reference mount pattern and metal mask pattern for the mounting strength and heat dissipation.



The USPN-4 is recommended to solder in use of the reference mount pattern and metal mask pattern for the mounting strength.

■PIN ASSIGNMENT

PIN NUMBER				PIN NAME	FUNCTION
USP-4D	SOT-25	SSOT-24	USPN-4		
4	1	4	4	V _{IN}	Power Input
1	5	3	1	V _{OUT}	Output
2	4	-	-	GO	Green Operation Mode Switch
5	2	2	2	V _{SS}	Ground
3	3	1	3	CE	ON/OFF Control

* XC6217 Series A/B type: USP-4D package

XC6217 Series A/B type: SOT-25 package

XC6217 Series C/D type: SSOT-24 package

XC6217 Series C/D type: USPN-4 package

■ PRODUCT CLASSIFICATION

● Ordering Information

XC6217①②③④⑤⑥-⑦^(*)

DESIGNATOR	DESCRIPTION	SYMBOL	DESCRIPTION		
①	Type of Regulator	A	CE High Active, no C_L discharge resistor		
		B	CE High Active, with C_L discharge resistor		
		C	CE High Active, no C_L discharge resistor, no GO pin		
		D	CE High Active, with C_L discharge resistor, no GO pin		
②③	Output Voltage	08 ~ 40	ex.) $V_{OUT(T)} = 3.00V \rightarrow ② = 3, ③ = 0$		
④	Output Accuracy	2	0.1V increments (Standard)		
			$V_{OUT}^{(*)}$	HS mode	PS mode
			0.80V ~ 1.50V	$V_{OUT(T)} \pm 30mV$	$V_{OUT(T)} +70mV, V_{OUT(T)} -90mV$
			1.60V ~ 1.90V	$V_{OUT(T)} \pm 30mV$	$V_{OUT(T)} +3.5\%, V_{OUT(T)} -4.5\%$
			2.00V ~ 2.50V	$V_{OUT(T)} \pm 2\%$	$V_{OUT(T)} +3.5\%, V_{OUT(T)} -4.5\%$
		A	2.60V ~ 4.00V	$V_{OUT(T)} \pm 2\%$	$V_{OUT(T)} +2.5\%, V_{OUT(T)} -3.5\%$
			ex.) 2.00V Standard → ②=2, ③=0, ④=2		
			0.05V increments (Standard)		
			$V_{OUT}^{(*)}$	HS mode	PS mode
			0.85V ~ 1.55V	$V_{OUT(T)} \pm 30mV$	$V_{OUT(T)} +70mV, V_{OUT(T)} -90mV$
		1	1.65V ~ 1.95V	$V_{OUT(T)} \pm 30mV$	$V_{OUT(T)} +3.5\%, V_{OUT(T)} -4.5\%$
			2.05V ~ 2.55V	$V_{OUT(T)} \pm 2\%$	$V_{OUT(T)} +3.5\%, V_{OUT(T)} -4.5\%$
			2.65V ~ 3.95V	$V_{OUT(T)} \pm 2\%$	$V_{OUT(T)} +2.5\%, V_{OUT(T)} -3.5\%$
			ex.) 2.05V Standard → ②=2, ③=0, ④=A		
			0.1V increments (High Accuracy)		
⑤⑥-⑦	Packages (Order Unit)	B	$V_{OUT}^{(*)}$	HS mode	PS mode
			0.80V ~ 1.50V	$V_{OUT(T)} \pm 20mV$	$V_{OUT(T)} +50mV, V_{OUT(T)} -70mV$
			1.60V ~ 1.90V	$V_{OUT(T)} \pm 20mV$	$V_{OUT(T)} +2.5\%, V_{OUT(T)} -3.5\%$
			2.00V ~ 2.50V	$V_{OUT(T)} \pm 1\%$	$V_{OUT(T)} +2.5\%, V_{OUT(T)} -3.5\%$
			2.60V ~ 4.00V	$V_{OUT(T)} \pm 1\%$	$V_{OUT(T)} +1.5\%, V_{OUT(T)} -2.5\%$
			ex.) 2.00V High Accuracy → ②=2, ③=0, ④=B		
		GR	GR	$USP-4D$ (XC6217 Series A/B type) (3,000/Reel)	
			GR-G	$USP-4D$ (XC6217 Series A/B type) (3,000/Reel)	
			MR	$SOT-25$ (XC6217 Series A/B type) (3,000/Reel)	
			MR-G	$SOT-25$ (XC6217 Series A/B type) (3,000/Reel)	
			NR	$SSOT-24$ (XC6217 Series C/D type) (3,000/Reel)	
			NR-G	$SSOT-24$ (XC6217 Series C/D type) (3,000/Reel)	
			7R-G	$USPN-4$ (XC6217 Series C/D type) ^(*) (5,000/Reel)	

^(*) The “-G” suffix denotes Halogen and Antimony free as well as being fully RoHS compliant.^{(**) Output Range of USPN-4 1.6V ≤ V_{OUT} ≤ 4.00V}


■ PRODUCT CLASSIFICATION

● Selection Guide


Type	GO Pin	C _L Discharge
A	YES	NO
B	YES	YES
C	NO	NO
D	NO	YES

■ BLOCK DIAGRAMS


● XC6217 Series A Type




● XC6217 Series B Type



● XC6217 Series C Type



● XC6217 Series D Type



*Diodes inside the circuit are an ESD protection diode and a parasitic diode.

■FUNCTION CHART

PIN NAME	LOGIC	IC CONDITION
CE	L	OFF
	H	ON
	OPEN	Undefined operation
GO ^(*)1)	L	GO Mode ^(*)2)
	H	HS Mode
	OPEN	Undefined operation

(*1) Since there is no GO pin about SSOT-24 and USPN-4, they always operate by GO Mode.

(*2) GO mode = PS/HS auto switching

PowerSave(PS) mode : Low supply current

HighSpeed(HS) mode : High Speed

(*3) CE pin and GO pin should not be left open. Each should have a certain voltage.

■ABSOLUTE MAXIMUM RATINGS

T_a=25°C

PARAMETER	SYMBOL	RATINGS	UNITS
Input Voltage	V _{IN}	V _{SS} -0.3 ~ +6.5	V
Output Current	I _{OUT}	400 *1	mA
Output Voltage	V _{OUT}	V _{SS} -0.3 ~ V _{IN} +0.3	V
CE/GO Input Voltage	V _{CE/V_{GO}}	V _{SS} -0.3 ~ +6.5	V
Power Dissipation	Pd	120	mW
		650 (PCB mounted)*2	
		250	
		150	
		100	
		600 (PCB mounted)*2	
Operating Ambient Temperature	Topr	-40 ~ +85	°C
Storage Temperature	Tstg	-55 ~ +125	°C

*1: I_{OUT} ≤ Pd / (V_{IN}-V_{OUT})

*2: This power dissipation figure shown is PCB mounted and is for reference only. Please refer to page 26-27 for details.

■ ELECTRICAL CHARACTERISTICS

● XC6217 series A/B Type

Ta=25°C

PARAMETER	SYMBOL	CONDITIONS	MIN.	TYP.	MAX.	UNITS	CIRCUIT
Output Voltage (Standard)	V _{OUT(E)} (*2)	High Speed Mode (HS) V _{OUT(T)} ≥2.00V V _{GO} =V _{IN} , V _{CE} =V _{IN} , I _{OUT} =10mA	V _{OUT(T)} ×0.98	V _{OUT(T)} (*3)	V _{OUT(T)} ×1.02	V	①
		High Speed Mode (HS) V _{OUT(T)} ≤1.95V V _{GO} =V _{IN} , V _{CE} =V _{IN} , I _{OUT} =10mA	V _{OUT(T)} -0.03		V _{OUT(T)} +0.03		
		Power Save Mode (PS) V _{OUT(T)} ≥2.60V V _{GO} =V _{SS} , V _{CE} =V _{IN} , I _{OUT} =0.1mA	V _{OUT(T)} ×0.965		V _{OUT(T)} ×1.025		
		Power Save Mode (PS) 1.60V≤V _{OUT(T)} ≤2.55V V _{GO} =V _{SS} , V _{CE} =V _{IN} , I _{OUT} =0.1mA	V _{OUT(T)} ×0.955		V _{OUT(T)} ×1.035		
		Power Save Mode (PS) 0.80V≤V _{OUT(T)} ≤1.55V V _{GO} =V _{SS} , V _{CE} =V _{IN} , I _{OUT} =0.1mA	V _{OUT(T)} -0.09		V _{OUT(T)} +0.07		
Output Voltage (High Accuracy)	V _{OUT(E)} (*2)	High Speed Mode (HS) V _{OUT(T)} ≥2.00V V _{GO} =V _{IN} , V _{CE} =V _{IN} , I _{OUT} =10mA	V _{OUT(T)} ×0.99	V _{OUT(T)} (*3)	V _{OUT(T)} ×1.01	V	①
		High Speed Mode (HS) V _{OUT(T)} ≤1.95V V _{GO} =V _{IN} , V _{CE} =V _{IN} , I _{OUT} =10mA	V _{OUT(T)} -0.02		V _{OUT(T)} +0.02		
		Power Save Mode (PS) V _{OUT(T)} ≥2.60V V _{GO} =V _{SS} , V _{CE} =V _{IN} , I _{OUT} =0.1mA	V _{OUT(T)} ×0.975		V _{OUT(T)} ×1.015		
		Power Save Mode (PS), 1.60V≤V _{OUT(T)} ≤2.55V V _{GO} =V _{SS} , V _{CE} =V _{IN} , I _{OUT} =0.1mA	V _{OUT(T)} ×0.965		V _{OUT(T)} ×1.025		
		Power save mode (PS), 0.80V≤V _{OUT(T)} ≤1.55V V _{GO} =V _{SS} , V _{CE} =V _{IN} , I _{OUT} =0.1mA	V _{OUT(T)} -0.07		V _{OUT(T)} +0.05		
Output Current	I _{OUTMAX}	V _{GO} =V _{IN} (HS), V _{CE} =V _{IN} V _{IN} =V _{OUT(T)} +1.0V 0.80V≤V _{OUT(T)} ≤4.00V	200	250	-	mA	①
Load Regulation	ΔV _{OUT}	V _{GO} =V _{IN} (HS), V _{CE} =V _{IN} 0.1mA≤I _{OUT} ≤100mA		10	40	mV	①
Dropout Voltage (*4)	V _{dif}	V _{GO} =V _{IN} (HS), V _{CE} =V _{IN} , I _{OUT} =100mA		[E-2]		mV	①
Supply Current 1	I _{SS1}	V _{CE} =V _{IN} , V _{GO} =V _{IN} (HS), I _{OUT} =0mA	-	25	50	μA	②
Supply Current 2	I _{SS2}	V _{CE} =V _{IN} , V _{GO} =V _{SS} (PS), I _{OUT} =0mA	-	4.5	8.0	μA	②
Standby Current	I _{STB}	V _{IN} =6.0V, V _{CE} =V _{SS}	-	0.01	0.10	μA	②
Line Regulation	ΔV _{OUT} ΔV _{IN} ·V _{OUT}	V _{OUT(T)} +0.5V≤V _{IN} ≤6.0V V _{OUT(T)} ≥1.10V V _{GO} =V _{IN} (HS), V _{CE} =V _{IN} , I _{OUT} =10mA	-	0.01	0.20	%/V	①
		1.6V≤V _{IN} ≤6.0V V _{OUT(T)} ≤1.05V V _{GO} =V _{IN} (HS), V _{CE} =V _{IN} , I _{OUT} =10mA	-				
Input Voltage	V _{IN}	0.80V≤V _{OUT(T)} ≤1.55V	1.6	-	6.0	V	①
Output Voltage Temperature Characteristics	ΔV _{OUT} / (ΔTopr · V _{OUT})	V _{GO} =V _{IN} , V _{CE} =V _{IN} I _{OUT} =30mA -40°C≤Topr≤85°C	-	±100	-	ppm/°C	①

■ ELECTRICAL CHARACTERISTICS (Continued)

● XC6217 series A/B Type (Continued)

PARAMETER	SYMBOL	CONDITIONS	MIN.	TYP.	MAX.	UNITS	CIRCUIT
Ripple Rejection Rate	PSRR	$V_{IN} = \{V_{OUT(T)} + 1.0\}V_{DC} + 0.5V_{p-pAC}$ $0.85V \leq V_{OUT(T)} \leq 4.00V$ $V_{GO} = V_{IN} (\text{HS}), V_{CE} = V_{IN}$ $I_{OUT} = 30mA, f = 1kHz$	-	70	-	dB	③
		$V_{IN} = 1.85V_{DC} + 0.5V_{p-pAC}$ $V_{OUT(T)} = 0.80V$ $V_{GO} = V_{IN} (\text{HS}), V_{CE} = V_{IN}$ $I_{OUT} = 30mA, f = 1kHz$					
Limit Current	I_{LIM}	$V_{GO} = V_{IN} (\text{HS}), V_{CE} = V_{IN}$	200	250	-	mA	①
Short Current	I_{SHORT}	$V_{GO} = V_{IN} (\text{HS}), V_{CE} = V_{IN}$ V_{OUT} is short-circuited to the V_{SS} level.	-	30	-	mA	①
PS Switching Current	I_{GOR}	$V_{CE} = V_{IN}$ $V_{GO} = V_{SS}$ (GO mode), I_{OUT} : heavy to light load	0.5	-	-	mA	④
HS Switching Current	I_{GO}	$V_{CE} = V_{IN}, V_{GO} = V_{SS}$ (GO mode), I_{OUT} : light to heavy load	-	-	8.0	mA	④
Switch Current Hysteresis Range	I_{GOHYS}	$I_{GOHYS} = I_{GO} - I_{GOR}$	-	3.5	-	mA	④
PS Switching Delay Time	t_{DPS}	$V_{CE} = V_{IN}, V_{GO} = V_{SS}$ (GO mode)	-	-	[E-3]	μs	④
CE High Level Voltage	V_{CEH}		1.2	-	6.0	V	④
GO High Level Voltage	V_{GOH}	$V_{CE} = V_{IN}, I_{SS}$ Search, $I_{OUT} = 0mA$	1.2	-	6.0	V	④
CE Low Level Voltage	V_{CEL}		-	-	0.3	V	④
GO Low Level Voltage	V_{GOL}	$V_{CE} = V_{IN}, I_{SS}$ Search, $I_{OUT} = 0mA$	-	-	0.3	V	④
CE High Level Current	I_{CEH}	$V_{GO} = V_{IN}, V_{CE} = V_{IN}$	-0.1	-	0.1	μA	④
GO High Level Current	I_{GOH}	$V_{GO} = V_{IN}, V_{CE} = V_{IN}$	-0.1	-	0.1	μA	④
CE Low Level Current	I_{CEL}	$V_{CE} = V_{SS}, V_{GO} = V_{SS}$	-0.1	-	0.1	μA	④
GO Low Level Current	I_{GOL}	$V_{CE} = V_{SS}, V_{GO} = V_{SS}$	-0.1	-	0.1	μA	④
CL Auto-Discharge Resistance (*7)	R_{DCHG}	$V_{IN} = 6.0V, V_{OUT} = 4.00V, V_{CE} = V_{GO} = V_{SS}$	-	780	-	Ω	①

NOTE:

- * 1: Unless otherwise stated regarding input voltage conditions, $V_{IN} = V_{OUT(T)} + 1.0V$.
- * 2: $V_{OUT(E)}$ = Effective output voltage (Refer to the voltage chart E-1)
(I.e. the output voltage when an amply stabilized " $V_{OUT(T)} + 1.0V$ " is provided at the V_{IN} pin while maintaining a certain I_{OUT} value.)
- * 3: $V_{OUT(T)}$ = Nominal output voltage
- * 4: $V_{dif} = \{V_{IN1}^{(*)6} - V_{OUT1}^{(*)5}\}$
- * 5: V_{OUT1} = A voltage equal to 98% of the output voltage whenever an amply stabilized $I_{OUT} \{V_{OUT(T)} + 1.0V\}$ is input in the HS mode.
- * 6: V_{IN1} = The input voltage when V_{OUT1} appears as input voltage is gradually decreased.
- * 7: For the XC6217 series B type only. The XC6217 series A type discharges by resistors R1 and R2 only as shown in the block diagrams.

■ELECTRICAL CHARACTERISTICS (Continued)

●XC6217 series C/D Type

Ta=25°C

PARAMETER	SYMBOL	CONDITIONS	MIN.	TYP.	MAX.	UNITS	CIRCUIT
Output Voltage (Standard)	$V_{OUT(E)}$ (* 2)	High Speed Mode (HS) $V_{OUT(T)} \geq 2.00V$ $V_{CE} = V_{IN}$, $I_{OUT} = 10mA$	$V_{OUT(T)}$ $\times 0.98$ (* 3)	$V_{OUT(T)}$ (* 3)	$V_{OUT(T)}$ $\times 1.02$	V	①
		High Speed Mode(HS) $V_{OUT(T)} \leq 1.95V$ $V_{CE} = V_{IN}$, $I_{OUT} = 10mA$	$V_{OUT(T)}$ -0.03 (* 3)		$V_{OUT(T)}$ $+0.03$		
		Power Save Mode (PS) $V_{OUT(T)} \geq 2.60V$ $V_{CE} = V_{IN}$, $I_{OUT} = 0.1mA$	$V_{OUT(T)}$ $\times 0.965$ (* 3)		$V_{OUT(T)}$ $\times 1.025$		
		Power Save Mode (PS) $1.60V \leq V_{OUT(T)} \leq 2.55V$ $V_{CE} = V_{IN}$, $I_{OUT} = 0.1mA$	$V_{OUT(T)}$ $\times 0.955$ (* 3)		$V_{OUT(T)}$ $\times 1.035$		
		Power Save Mode(PS) $0.80V \leq V_{OUT(T)} \leq 1.55V$ $V_{CE} = V_{IN}$, $I_{OUT} = 0.1mA$	$V_{OUT(T)}$ -0.09 (* 3)		$V_{OUT(T)}$ $+0.07$		
Output Voltage (High Accuracy)	$V_{OUT(E)}$ (* 2)	High Speed Mode (HS) $V_{OUT(T)} \geq 2.00V$ $V_{CE} = V_{IN}$, $I_{OUT} = 10mA$	$V_{OUT(T)}$ $\times 0.99$	$V_{OUT(T)}$ (* 3)	$V_{OUT(T)}$ $\times 1.01$	V	①
		High Speed Mode(HS) $V_{OUT(T)} \leq 1.95V$ $V_{CE} = V_{IN}$, $I_{OUT} = 10mA$	$V_{OUT(T)}$ -0.02		$V_{OUT(T)}$ $+0.02$		
		Power Save Mode (PS) $V_{OUT(T)} \geq 2.60V$ $V_{CE} = V_{IN}$, $I_{OUT} = 0.1mA$	$V_{OUT(T)}$ $\times 0.975$		$V_{OUT(T)}$ $\times 1.015$		
		Power Save Mode (PS) $1.60V \leq V_{OUT(T)} \leq 2.55V$ $V_{CE} = V_{IN}$, $I_{OUT} = 0.1mA$	$V_{OUT(T)}$ $\times 0.965$		$V_{OUT(T)}$ $\times 1.025$		
		Power Save Mode(PS) $0.80V \leq V_{OUT(T)} \leq 1.55V$ $V_{CE} = V_{IN}$, $I_{OUT} = 0.1mA$	$V_{OUT(T)}$ -0.07		$V_{OUT(T)}$ $+0.05$		
Output Current	I_{OUTMAX}	$V_{CE} = V_{IN}$, $V_{IN} = V_{OUT(T)} + 1.0V$, $0.80V \leq V_{OUT(T)} \leq 4.00V$	200	250	-	mA	①
Load Regulation	ΔV_{OUT}	$V_{CE} = V_{IN}$, $8mA \leq I_{OUT} \leq 100mA$	-	10	40	mV	①
Dropout Voltage (*4)	V_{dif}	$V_{CE} = V_{IN}$, $I_{OUT} = 100mA$		[E-2]		mV	①
Supply Current 1	I_{SS1}	$V_{CE} = V_{IN}$, $I_{OUT} = 8mA$	-	25	50	μA	④
Supply Current 2	I_{SS2}	$V_{CE} = V_{IN}$, $I_{OUT} = 0mA$	-	4.5	8.0	μA	②
Standby Current	I_{STBY}	$V_{IN} = 6.0V$, $V_{CE} = V_{SS}$	-	0.01	0.10	μA	②
Line Regulation	$\frac{\Delta V_{OUT}}{\Delta V_{IN} \cdot V_{OUT}}$	$V_{OUT(T)} + 0.5V \leq V_{IN} \leq 6.0V$ $V_{OUT(T)} \geq 1.10V$ $V_{CE} = V_{IN}$, $I_{OUT} = 10mA$	-	0.01	0.20	%/ V	①
		$1.6V \leq V_{IN} \leq 6.0V$ $V_{OUT(T)} \leq 1.05V$ $V_{CE} = V_{IN}$, $I_{OUT} = 10mA$					
Input Voltage	V_{IN}		1.6	-	6.0	V	①
Output Voltage Temperature Characteristics	$\Delta V_{OUT}/(\Delta T_{op} \cdot V_{OUT})$	$V_{CE} = V_{IN}$, $I_{OUT} = 30mA$ $-40^{\circ}C \leq T_{op} \leq 85^{\circ}C$	-	± 100	-	ppm/ $^{\circ}C$	①

■ ELECTRICAL CHARACTERISTICS (Continued)

● XC6217 series C/D Type (Continued)

Ta=25°C

PARAMETER	SYMBOL	CONDITIONS	MIN.	TYP.	MAX.	UNITS	CIRCUIT
Ripple Rejection Rate	PSRR	$V_{IN} = \{V_{OUT(T)} + 1.0\}V_{DC} + 0.5V_{P-PAC}$ $0.85V \leq V_{OUT(T)} \leq 4.00V$ $V_{CE} = V_{IN}, I_{OUT} = 30mA, f = 1kHz$	-	70	-	dB	③
		$V_{IN} = 1.85V_{DC} + 0.5V_{P-PAC}$ $V_{OUT(T)} = 0.80V$ $V_{CE} = V_{IN}, I_{OUT} = 30mA, f = 1kHz$					
Limit Current	I _{LIM}	$V_{CE} = V_{IN}$	200	250	-	mA	①
Short Current	I _{SHORT}	$V_{CE} = V_{IN}$ V _{OUT} is short-circuited at the V _{SS} level.		30	-	mA	①
PS Switching Current	I _{GOR}	$V_{CE} = V_{IN}, I_{OUT}$: heavy to light load	0.5	-	-	mA	④
HS Switching Current	I _{GO}	$V_{CE} = V_{IN}, I_{OUT}$: light to heavy load	-	-	8.0	mA	④
Switch Current Hysteresis Range	I _{GOHYS}	$I_{GOHYS} = I_{GO} - I_{GOR}$	-	3.5	-	mA	④
PS Switching Delay Time	t _{DPS}	$V_{CE} = V_{IN}$	-	-	[E-3]	μ s	④
CE High Level Voltage	V _{CEH}		1.2		6.0	V	④
CE Low Level Voltage	V _{CEL}		-	-	0.3	V	④
CE High Level Current	I _{CEH}	$V_{CE} = V_{IN}$	-0.1	-	0.1	μ A	④
CE Low Level Current	I _{CEL}	$V_{CE} = V_{SS}$	-0.1	-	0.1	μ A	④
CL Auto-Discharge Resistance ^{(*)7}	R _{DCDCHG}	$V_{IN} = 6.0V, V_{OUT} = 4.00V, V_{CE} = V_{SS}$	-	780	-	Ω	①

NOTE:

- * 1: Unless otherwise stated regarding input voltage conditions, $V_{IN} = V_{OUT(T)} + 1.0V$.
- * 2: $V_{OUT(E)}$ = Effective output voltage (Refer to the voltage chart E-1)
(I.e. the output voltage when an amply stabilized " $V_{OUT(T)} + 1.0V$ " is provided at the V_{IN} pin while maintaining a certain I_{OUT} value.)
- * 3: $V_{OUT(T)}$ = Nominal output voltage
- * 4: $V_{dif} = \{V_{IN1}^{(*)6} - V_{OUT1}^{(*)5}\}$
- * 5: V_{OUT1} = A voltage equal to 98% of the output voltage whenever an amply stabilized I_{OUT} { $V_{OUT(T)} + 1.0V$ } is input in the HS mode.
- * 6: V_{IN1} = The input voltage when V_{OUT1} appears as input voltage is gradually decreased.
- * 7: For the XC6217 series D Type only. The XC6217 series C Type discharges by resistors R1 and R2 only as shown in the block diagrams.

■ OUTPUT VOLTAGE CHART (Continued)

OUTPUT VOLTAGE (V)	OUTPUT VOLTAGE (HS MODE) Standard (V)		OUTPUT VOLTAGE (PS MODE) Standard (V)		OUTPUT VOLTAGE (HS MODE) High Accuracy (V)		OUTPUT VOLTAGE (PS MODE) High Accuracy (V)		DROPOUT VOLTAGE $I_{out}=100mA$ (mV)		PS SWITCH DELAY TIME (GOMode) (μs)
$V_{out(T)}$	$V_{out(E)}$		$V_{out(E)}$		$V_{out(E)}$		$V_{out(E)}$		Vdif		t_{DPS}
	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	TYP.	MAX.	
0.80	0.77000	0.83000	0.71000	0.87000	0.78000	0.82000	0.73000	0.85000	500	850	650
0.85	0.82000	0.88000	0.76000	0.92000	0.83000	0.87000	0.78000	0.90000			
0.90	0.87000	0.93000	0.81000	0.97000	0.88000	0.92000	0.83000	0.95000			
0.95	0.92000	0.98000	0.86000	1.02000	0.93000	0.97000	0.88000	1.00000			
1.00	0.97000	1.03000	0.91000	1.07000	0.98000	1.02000	0.93000	1.05000			
1.05	1.02000	1.08000	0.96000	1.12000	1.03000	1.07000	0.98000	1.10000			
1.10	1.07000	1.13000	1.01000	1.17000	1.08000	1.12000	1.03000	1.15000			
1.15	1.12000	1.18000	1.06000	1.22000	1.13000	1.17000	1.08000	1.20000			
1.20	1.17000	1.23000	1.11000	1.27000	1.18000	1.22000	1.13000	1.25000			
1.25	1.22000	1.28000	1.16000	1.32000	1.23000	1.27000	1.18000	1.30000			
1.30	1.27000	1.33000	1.21000	1.37000	1.28000	1.32000	1.23000	1.35000			
1.35	1.32000	1.38000	1.26000	1.42000	1.33000	1.37000	1.28000	1.40000			
1.40	1.37000	1.43000	1.31000	1.47000	1.38000	1.42000	1.33000	1.45000			
1.45	1.42000	1.48000	1.36000	1.52000	1.43000	1.47000	1.38000	1.50000			
1.50	1.47000	1.53000	1.41000	1.57000	1.48000	1.52000	1.43000	1.55000			
1.55	1.52000	1.58000	1.46000	1.62000	1.53000	1.57000	1.48000	1.60000			
1.60	1.57000	1.63000	1.52800	1.65600	1.58000	1.62000	1.54400	1.64000	160	250	850
1.65	1.62000	1.68000	1.57575	1.70775	1.63000	1.67000	1.59225	1.69125			
1.70	1.67000	1.73000	1.62350	1.75950	1.68000	1.72000	1.64050	1.74250			
1.75	1.72000	1.78000	1.67125	1.81125	1.73000	1.77000	1.68875	1.79375			
1.80	1.77000	1.83000	1.71900	1.86300	1.78000	1.82000	1.73700	1.84500			
1.85	1.82000	1.88000	1.76675	1.91475	1.83000	1.87000	1.78525	1.89625	125	210	850
1.90	1.87000	1.93000	1.81450	1.96650	1.88000	1.92000	1.83350	1.94750			
1.95	1.92000	1.98000	1.86225	2.01825	1.93000	1.97000	1.88175	1.99875			
2.00	1.96000	2.04000	1.91000	2.07000	1.98000	2.02000	1.93000	2.05000			
2.05	2.00900	2.09100	1.95775	2.12175	2.02950	2.07050	1.97825	2.10125			
2.10	2.05800	2.14200	2.00550	2.17350	2.07900	2.12100	2.02650	2.15250	115	195	850
2.15	2.10700	2.19300	2.05325	2.22525	2.12850	2.17150	2.07475	2.20375			
2.20	2.15600	2.24400	2.10100	2.27700	2.17800	2.22200	2.12300	2.25500			
2.25	2.20500	2.29500	2.14875	2.32875	2.22750	2.27250	2.17125	2.30625			
2.30	2.25400	2.34600	2.19650	2.38050	2.27700	2.32300	2.21950	2.35750			
2.35	2.30300	2.39700	2.24425	2.43225	2.32650	2.37350	2.26775	2.40875	115	195	850
2.40	2.35200	2.44800	2.29200	2.48400	2.37600	2.42400	2.31600	2.46000			
2.45	2.40100	2.49900	2.33975	2.53575	2.42550	2.47450	2.36425	2.51125			

*USPN-4 $1.6V \leq V_{out(T)} \leq 4.00V$.

■OUTPUT VOLTAGE CHART (Continued)


SYMBOL	E-1								E-2		E-3
	NOMINAL OUTPUT VOLTAGE (V)		OUTPUT VOLTAGE (HS MODE) Standard (V)		OUTPUT VOLTAGE (PS MODE) Standard (V)		OUTPUT VOLTAGE (HS MODE) High Accuracy (V)		OUTPUT VOLTAGE (PS MODE) High Accuracy (V)		DROPOUT VOLTAGE $I_{out}=100mA(mV)$
$V_{OUT(T)}$	$V_{OUT(E)}$		$V_{OUT(E)}$		$V_{OUT(E)}$		$V_{OUT(E)}$		V_{dif}		t_{DPS}
	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	TYP.	MAX.	MAX.
2.50	2.45000	2.55000	2.38750	2.58750	2.47500	2.52500	2.41250	2.56250	95	170	850
2.55	2.49900	2.60100	2.43525	2.63925	2.52450	2.57550	2.46075	2.61375			
2.60	2.54800	2.65200	2.50900	2.66500	2.57400	2.62600	2.53500	2.63900			
2.65	2.59700	2.70300	2.55725	2.71625	2.62350	2.67650	2.58375	2.68975			
2.70	2.64600	2.75400	2.60550	2.76750	2.67300	2.72700	2.63250	2.74050			
2.75	2.69500	2.80500	2.65375	2.81875	2.72250	2.77750	2.68125	2.79125			
2.80	2.74400	2.85600	2.70200	2.87000	2.77200	2.82800	2.73000	2.84200			
2.85	2.79300	2.90700	2.75025	2.92125	2.82150	2.87850	2.77875	2.89275			
2.90	2.84200	2.95800	2.79850	2.97250	2.87100	2.92900	2.82750	2.94350			
2.95	2.89100	3.00900	2.84675	3.02375	2.92050	2.97950	2.87625	2.99425			
3.00	2.94000	3.06000	2.89500	3.07500	2.97000	3.03000	2.92500	3.04500	80	140	1200
3.05	2.98900	3.11100	2.94325	3.12625	3.01950	3.08050	2.97375	3.09575			
3.10	3.03800	3.16200	2.99150	3.17750	3.06900	3.13100	3.02250	3.14650			
3.15	3.08700	3.21300	3.03975	3.22875	3.11850	3.18150	3.07125	3.19725			
3.20	3.13600	3.26400	3.08800	3.28000	3.16800	3.23200	3.12000	3.24800			
3.25	3.18500	3.31500	3.13625	3.33125	3.21750	3.28250	3.16875	3.29875			
3.30	3.23400	3.36600	3.18450	3.38250	3.26700	3.33300	3.21750	3.34950			
3.35	3.28300	3.41700	3.23275	3.43375	3.31650	3.38350	3.26625	3.40025			
3.40	3.33200	3.46800	3.28100	3.48500	3.36600	3.43400	3.31500	3.45100			
3.45	3.38100	3.51900	3.32925	3.53625	3.41550	3.48450	3.36375	3.50175			
3.50	3.43000	3.57000	3.37750	3.58750	3.46500	3.53500	3.41250	3.55250			
3.55	3.47900	3.62100	3.42575	3.63875	3.51450	3.58550	3.46125	3.60325	80	140	1200
3.60	3.52800	3.67200	3.47400	3.69000	3.56400	3.63600	3.51000	3.65400			
3.65	3.57700	3.72300	3.52225	3.74125	3.61350	3.68650	3.55875	3.70475			
3.70	3.62600	3.77400	3.57050	3.79250	3.66300	3.73700	3.60750	3.75550			
3.75	3.67500	3.82500	3.61875	3.84375	3.71250	3.78750	3.65625	3.80625			
3.80	3.72400	3.87600	3.66700	3.89500	3.76200	3.83800	3.70500	3.85700			
3.85	3.77300	3.92700	3.71525	3.94625	3.81150	3.88850	3.75375	3.90775			
3.90	3.82200	3.97800	3.76350	3.99750	3.86100	3.93900	3.80250	3.95850			
3.95	3.87100	4.02900	3.81175	4.04875	3.91050	3.98950	3.85125	4.00925			
4.00	3.92000	4.08000	3.86000	4.10000	3.96000	4.04000	3.90000	4.06000			

*USPN-4 1.6V $\leq V_{OUT(T)} \leq$ 4.00V.

■OPERATIONAL EXPLANATION

<Output Voltage Control>

The voltage divided by resistors R1 & R2 is compared with the internal reference voltage by the error amplifier. The P-channel MOSFET, which is connected to the V_{OUT} pin, is then driven by the subsequent output signal. The output voltage at the V_{OUT} pin is controlled & stabilized by a system of negative feedback. The current limit circuit and short protect circuit operate in relation to the level of output current. The GO function monitors the output current and switches a supply current to two values according to the level of output current. Further, the IC's internal circuitry can be shutdown via the CE pin's signal.



<Green Operation>

XC6217 series A/B types can be set as a fixed high-speed mode or a green operation (GO) mode via a signal to the green operation (GO) pin. Under the condition that the GO pin becomes low level, the IC operates in the GO mode and the IC operates in the fixed high-speed mode when the GO pin is at high level. The XC6217 series C/D types always operates in GO mode (= PS/HS automatic change).

The GO mode enables the IC to switch automatically the supply current to the high speed (HS) mode or the power save (PS) mode according to the level of output current. While having both high-speed operation and low supply current state, the series can acquire high efficiency. At the HS/PS automatic switching mode (GO mode), the switching point of the HS mode and the PS mode is being fixed inside the IC. When the output current becomes I_{GOR} 0.5mA (MIN.) or below, the mode changes automatically to the PS mode after the delay time of hundreds [sec(s)], and it can reduce supply current in light load. Also when the output current becomes I_{GO} 8mA (MAX.) or more, the mode changes automatically to the HS mode and the IC becomes high speed operation.

When the XC6217 is used in the GO mode, stable operation range is over 8.0mA is HS mode and below 0.5mA in PS mode.

<Low ESR capacitor>

With the XC6217 series, a stable output voltage is achievable even if used with low ESR capacitors, as a phase compensation circuit is built-in. Values required for the phase compensation are as the chart below. In order to ensure the stable phase compensation while avoiding run-out of values, please use the capacitor which does not depend on bias or temperature too much. For a stable power input, please connect an input capacitor (C_{IN}) of 1.0 μ F between the V_{IN} pin and the V_{SS} pin.

- Excluding USPN-4

OUTPUT VOLTAGE (V)	OUTPUT CAPACITOR VALUE
0.8 ~ 1.15	More than C _L =4.7 μ F
1.2 ~ 1.35	More than C _L =2.2 μ F
1.4 ~ 4.0	More than C _L =1.0 μ F

- USPN-4

OUTPUT VOLTAGE (V)	OUTPUT CAPACITOR VALUE
1.6 ~ 4.0	More than C _L =2.2 μ F

■OPERATIONAL EXPLANATION (Continued)

<C_L Auto-Discharge Function>

XC6217 series B/D type can quickly discharge the electric charge at the output capacitor (C_L), when a low signal to the CE pin, which enables a whole IC circuit put into OFF state, is inputted via the N-channel transistor located between the V_{OUT} pin and the V_{SS} pin (cf. BLOCK DIAGRAM). The C_L auto-discharge resistance value is fixed to 780Ω (V_{IN}=6.0V, V_{OUT}=4.0V at typical). The discharge time of the output capacitor (C_L) is set by the C_L auto-discharge resistance (R) and the output capacitor (C_L). By setting time constant of a C_L auto-discharge resistance value [R_{DCHG}] and an output capacitor value (C_L) as τ ($\tau = C \times R_{DCHG}$), the output voltage after discharge via the N channel transistor is calculated by the following formulas.

$$V = V_{OUT(E)} \times e^{-t/\tau}, \quad \text{or} \quad t = \tau \ln(V_{OUT(E)} / V)$$

(V : Output voltage after discharge, V_{OUT(E)} : Output voltage, t: Discharge time,

τ : C_L auto-discharge resistance R_{DCHG} × Output capacitor (C_L) value C)

<Current Limiter, Short-Circuit Protection>

The XC6217 series' foldback circuit operates as an output current limiter and a short protection of the output pin. When the load current reaches the current limit level, the fixed current limiter circuit operates and output voltage drops. As a result of this drop in output voltage, the foldback circuit operates, output voltage drops further and output current decreases. When the output pin is shorted to the V_{SS} level, a current of about 30mA flows.

<CE Pin>

The IC's internal circuitry can be shutdown via the signal from the CE pin with the XC6217 series. In shutdown mode, output at the V_{OUT} pin will be pulled down to the V_{SS} level via R1 & R2. However, as for the XC6217 series B/D type, the C_L auto-discharge resistor is connected in parallel to R1 and R2 while the power supply is applied to the V_{IN} pin. Therefore, time until the V_{OUT} pin reaches the V_{SS} level becomes short. The output voltage becomes unstable, when the CE pin is open. Please input a certain voltage within an electrical characteristic into CE pin.


If this IC is used with the correct output voltage for the CE pin, the logic is fixed and the IC will operate normally. However, supply current may increase as a result of through current in the IC's internal circuitry when medium voltage is input.

■NOTES ON USE

1. Please use this IC within the stated absolute maximum ratings. The IC is liable to malfunction should the ratings be exceeded.
2. Where wiring impedance is high, operations may become unstable due to noise and/or phase lag depending on output current.
Please strengthen V_{IN} and V_{SS} wiring in particular.
3. Please wire the input capacitor (C_{IN}) and the output capacitor (C_L) as close to the IC as possible.
4. Capacitances of these capacitors (C_{IN}, C_L) are decreased by the influences of bias voltage and ambient temperature. Care shall be taken for capacitor selection to ensure stability of phase compensation from the point of ESR influence.
5. When the IC is used under the condition of very small dropout voltage, an output may carry out unstable operation.
Please use it after evaluating enough under the conditions to be used.
6. Torex places an importance on improving our products and their reliability.
We request that users incorporate fail-safe designs and post-aging protection treatment when using Torex products in their systems.


■ TEST CIRCUITS

Circuit 1: Output Voltage, Output Current, Dropout Voltage, Input/Operating Voltage, Line Regulation, Load Regulation, Current Limit, Short Current, C_L Discharge Resistance




*No GO pin with the XC6217C/D type.

Circuit 2: Supply Current, Standby Current




*No GO pin with the XC6217C/D type.

Circuit 3: Ripple Rejection Rate



*No GO pin with the XC6217C/D type.





Circuit 4: Supply Current, HS/PS Switching Current, PS Switching Delay Time, CE/GO "H" "L" Level Voltage, CE/GO "H" "L" Level Current





*No GO pin with the XC6217C/D type.

■ TYPICAL PERFORMANCE CHARACTERISTICS

(1) Output Voltage vs. Output Current





(2) Output Voltage vs. Input Voltage





■ TYPICAL PERFORMANCE CHARACTERISTICS (Continued)



(2) Output Voltage vs. Input Voltage (Continued)



(3) Dropout Voltage vs. Output Current




(4) Output Voltage vs. Ambient Temperature




■ TYPICAL PERFORMANCE CHARACTERISTICS (Continued)

(5) Supply Current vs. Input Voltage




(6) PS Switching Delay Time vs. Ambient Temperature




■ TYPICAL PERFORMANCE CHARACTERISTICS (Continued)





(7) CL Auto-Discharge Resistance vs. Ambient Temperature



(8) PS/HS Switching Current vs. Ambient Temperature




(9) Load Transient Response




■ TYPICAL PERFORMANCE CHARACTERISTICS (Continued)

(9) Load Transient Response






(10) Line Transient Response





■ TYPICAL PERFORMANCE CHARACTERISTICS (Continued)

(10) Line Transient Response







(11) Turn-On Response





■ TYPICAL PERFORMANCE CHARACTERISTICS (Continued)

(11) Turn-On Response (Continued)







(12) CE Turn-On Response







■ TYPICAL PERFORMANCE CHARACTERISTICS (Continued)

(12) CE Turn-On Response (Continued)



■ TYPICAL PERFORMANCE CHARACTERISTICS (Continued)


(13) Ripple Rejection Rate



■ PACKAGING INFORMATION

● USP-4D

●SOT-25



*Soldering fillet surface is not formed because the sides of the pins are plated.


The technical drawing illustrates a component's dimensions and features. Key dimensions include:

- Total width: 2.9 ± 0.2
- Height: 2.8 ± 0.2
- Width of the central rectangular area: 1.6 ± 0.2
- Width of the top section: 0.4 ± 0.05
- Width of the bottom section: 1.9 ± 0.2
- Width of the leftmost slot: (0.95)
- Width of the rightmost slot: 1.1 ± 0.1
- Depth of the rightmost slot: 1.3 MAX
- Width of the bottom-most slot: 1.3 MAX
- Width of the leftmost slot: 1.1 ± 0.1
- Width of the middle slot: 1.1 ± 0.1
- Width of the rightmost slot: 1.1 ± 0.1
- Width of the top-most slot: $0 \sim 0.1$
- Width of the leftmost slot: 0.2 MIN


Feature labels 1 through 5 are positioned around the component's perimeter.

● SSOT-24

(unit : mm)




USPN-4




■ PACKAGING INFORMATION (Continued)


● USP-4D Reference Pattern Layout Dimension




● USP-4D Reference metal mask design



● USPN-4 Reference Pattern Layout Dimension



● USPN-4 Reference metal mask design



- USP-4D Power Dissipation


Power dissipation data for the USP-4D is shown in this page.

The value of power dissipation varies with the mount board conditions.

Please use this data as one of reference data taken in the described condition.

1. Measurement Condition (Reference data)


Condition: Mount on a board
 Ambient: Natural convection
 Soldering: Lead (Pb) free
 Board: Dimensions 40 x 40 mm (1600 mm² in one side)
 Copper (Cu) traces occupy 50% of the board area
 In top and back faces
 Package heat-sink is tied to the copper traces
 Material: Glass Epoxy (FR-4)
 Thickness: 1.6 mm
 Through-hole: 4 x 0.8 Diameter



2. Power Dissipation vs. Ambient Temperature

Board Mount (T_j max = 125°C)

Ambient Temperature(°C)	Power Dissipation Pd (mW)	Thermal Resistance(°C/W)
25	650	153.8
85	260	



● USPN-4 Power Dissipation

Power dissipation data for the USPN-4 is shown in this page.

The value of power dissipation varies with the mount board conditions.

Please use this data as one of reference data taken in the described condition.

1. Measurement Condition (Reference data)

Condition: Mount on a board

Ambient: Natural convection

Soldering: Lead (Pb) free

Board: Dimensions 40 x 40 mm (1600 mm² in one side)

Copper (Cu) traces occupy 50% of the front and 50% of the back.

The copper area is divided into four block, one block is 12.5% of total.


The USPN-4 package has four terminals.

Each terminal connects one copper block in the front and one in the back.

Material: Glass Epoxy (FR-4)

Thickness: 1.6 mm

Through-hole: 4 x 0.8 Diameter




Evaluation Board (Unit: mm)

2. Power Dissipation vs. Ambient Temperature


Board Mount (T_j max = 125°C)

Ambient Temperature(°C)	Power Dissipation Pd (mW)	Thermal Resistance(°C/W)
25	600	166.67
85	240	



■ MARKING RULE

● SOT-25



SOT-25
(TOP VIEW)

① represents product series

MARK	PRODUCT SERIES
1	XC6217xxxxx

② represents type of regulators

MARK				PRODUCT SERIES	
OUTPUT VOLTAGE 0.1V INCREMENTS		OUTPUT VOLTAGE 0.05V INCREMENTS			
0.80V~3.00V	3.10V~4.00V	0.85V~3.05V	3.15V~3.95V		
V	A	E	L	XC6217Axxxxx	
X	B	F	M	XC6217Bxxxxx	

③ represents output voltage

MARK	OUTPUT VOLTAGE (V)				MARK	OUTPUT VOLTAGE (V)			
0	-	3.10	-	3.15	F	1.60	-	1.65	-
1	-	3.20	-	3.25	H	1.70	-	1.75	-
2	-	3.30	-	3.35	K	1.80	-	1.85	-
3	-	3.40	-	3.45	L	1.90	-	1.95	-
4	-	3.50	-	3.55	M	2.00	-	2.05	-
5	-	3.60	-	3.65	N	2.10	-	2.15	-
6	-	3.70	-	3.75	P	2.20	-	2.25	-
7	0.80	3.80	0.85	3.85	R	2.30	-	2.35	-
8	0.90	3.90	0.95	3.95	S	2.40	-	2.45	-
9	1.00	4.00	1.05	-	T	2.50	-	2.55	-
A	1.10	-	1.15	-	U	2.60	-	2.65	-
B	1.20	-	1.25	-	V	2.70	-	2.75	-
C	1.30	-	1.35	-	X	2.80	-	2.85	-
D	1.40	-	1.45	-	Y	2.90	-	2.95	-
E	1.50	-	1.55	-	Z	3.00	-	3.05	-

④⑤ represents production lot number

01 to 09, 10 to 99, 0A~0Z, 1A in order. (G, I, J, O, Q, W excluded)

Note: No character inversion used.

■ MARKING RULE (Continued)

●SSOT-24



SSOT-4
(TOP VIEW)

① represents type of regulators and output voltage range

MARK				PRODUCT SERIES	
OUTPUT VOLTAGE 0.10V INCREMENTS		OUTPUT VOLTAGE 0.05V INCREMENTS			
0.80V~3.0V	3.10V~4.00V	0.85V~3.05V	3.15V~3.95V		
1	5	2	6	XC6217Cxxxxx	
3	7	4	8	XC6217Dxxxxx	

② represents output voltage numbers after the decimal point.

MARK	OUTPUT VOLTAGE (V)			MARK	OUTPUT VOLTAGE (V)		
0	-	3.10	-	3.15	F	1.60	-
1	-	3.20	-	3.25	H	1.70	-
2	-	3.30	-	3.35	K	1.80	-
3	-	3.40	-	3.45	L	1.90	-
4	-	3.50	-	3.55	M	2.00	-
5	-	3.60	-	3.65	N	2.10	-
6	-	3.70	-	3.75	P	2.20	-
7	0.80	3.80	0.85	3.85	R	2.30	-
8	0.90	3.90	0.95	3.95	S	2.40	-
9	1.00	4.00	1.05	-	T	2.50	-
A	1.10	-	1.15	-	U	2.60	-
B	1.20	-	1.25	-	V	2.70	-
C	1.30	-	1.35	-	X	2.80	-
D	1.40	-	1.45	-	Y	2.90	-
E	1.50	-	1.55	-	Z	3.00	-
							3.05
							-

③④ represents production lot number

01 to 09, 10 to 99, 0A~0Z, 1A in order. (G, I, J, O, Q, W excluded)

Note: No character inversion used.

■ MARKING RULE (Continued)

● USP-4D



USP-4D
(TOP VIEW)

① represents product series

MARK	PRODUCT SERIES
1	XC6217xxxxx

② represents type of regulators

MARK	TYPE OF REGULATORS	PRODUCT SERIES
A	CE High Active, without CL-Discharge	XC6217Axxxxx
B	CE High Active, with CL-Discharge	XC6217Bxxxxx

③ represents integer number of output voltage

ex.)

MARK	VOLTAGE (V)	PRODUCT SERIES
3	3.xx	XC6217x3xxGx
5	5.xx	XC6217x5xxGx

④ represents output voltage numbers after the decimal point.

MARK	VOLTAGE(V)	PRODUCT SEIRES	MARK	VOLTAGE (V)	PRODUCT SEIRES
0	x.00	XC6217xx02/1Gx	A	x.05	XC6217xx0A/1Gx
1	x.10	XC6217xx12/1Gx	B	x.15	XC6217xx1A/1Gx
2	x.20	XC6217xx22/1Gx	C	x.25	XC6217xx2A/1Gx
3	x.30	XC6217xx32/1Gx	D	x.35	XC6217xx3A/1Gx
4	x.40	XC6217xx42/1Gx	E	x.45	XC6217xx4A/1Gx
5	x.50	XC6217xx52/1Gx	F	x.55	XC6217xx5A/1Gx
6	x.60	XC6217xx62/1Gx	H	x.65	XC6217xx6A/1Gx
7	x.70	XC6217xx72/1Gx	K	x.75	XC6217xx7A/1Gx
8	x.80	XC6217xx82/1Gx	L	x.85	XC6217xx8A/1Gx
9	x.90	XC6217xx92/1Gx	M	x.95	XC6217xx9A/1Gx


⑤⑥ represents production lot number

01 to 09, 10 to 99, 0A~0Z, 1A in order. (G, I, J, O, Q, W excluded)

Note: No character inversion used.

■ MARKING RULE (Continued)

● USPN-4



① represents type of regulators and output voltage range

MARK				PRODUCT SERIES	
OUTPUT VOLTAGE 0.10V INCREMENTS		OUTPUT VOLTAGE 0.05V INCREMENTS			
0.80V~3.00V	3.10V~4.00V	0.85V~3.05V	3.15V~3.95V		
1	5	2	6	XC6217Cxxxxx	
3	7	4	8	XC6217Dxxxxx	

② represents output voltage numbers after the decimal point.

MARK	OUTPUT VOLTAGE (V)			MARK	OUTPUT VOLTAGE (V)				
0	-	3.10	-	3.15	F	1.60	-	1.65	-
1	-	3.20	-	3.25	H	1.70	-	1.75	-
2	-	3.30	-	3.35	K	1.80	-	1.85	-
3	-	3.40	-	3.45	L	1.90	-	1.95	-
4	-	3.50	-	3.55	M	2.00	-	2.05	-
5	-	3.60	-	3.65	N	2.10	-	2.15	-
6	-	3.70	-	3.75	P	2.20	-	2.25	-
7	0.80	3.80	0.85	3.85	R	2.30	-	2.35	-
8	0.90	3.90	0.95	3.95	S	2.40	-	2.45	-
9	1.00	4.00	1.05	-	T	2.50	-	2.55	-
A	1.10	-	1.15	-	U	2.60	-	2.65	-
B	1.20	-	1.25	-	V	2.70	-	2.75	-
C	1.30	-	1.35	-	X	2.80	-	2.85	-
D	1.40	-	1.45	-	Y	2.90	-	2.95	-
E	1.50	-	1.55	-	Z	3.00	-	3.05	-

*USPN-4 0.80V ≤ V_{OUT(T)} ≤ 1.55V underdevelopment.

③ represents production lot number

1 to 9, A to Z, repeated. (G, I, J, O, Q, W excluded)

Note: No character inversion used.

1. The products and product specifications contained herein are subject to change without notice to improve performance characteristics. Consult us, or our representatives before use, to confirm that the information in this datasheet is up to date.
2. We assume no responsibility for any infringement of patents, patent rights, or other rights arising from the use of any information and circuitry in this datasheet.
3. Please ensure suitable shipping controls (including fail-safe designs and aging protection) are in force for equipment employing products listed in this datasheet.
4. The products in this datasheet are not developed, designed, or approved for use with such equipment whose failure of malfunction can be reasonably expected to directly endanger the life of, or cause significant injury to, the user.
(e.g. Atomic energy; aerospace; transport; combustion and associated safety equipment thereof.)
5. Please use the products listed in this datasheet within the specified ranges.
Should you wish to use the products under conditions exceeding the specifications, please consult us or our representatives.
6. We assume no responsibility for damage or loss due to abnormal use.
7. All rights reserved. No part of this datasheet may be copied or reproduced without the prior permission of TOREX SEMICONDUCTOR LTD.

TOREX SEMICONDUCTOR LTD.