

PART NUMBER SSI-LXMP059GD

	REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
	Α	ADDED DIMS, NOTES AND UPDATED SPECS.	12.19.94
	В	E.C.N. #10122.	3.1 <i>.</i> 96
1	C	FCN #10BRDR & REDRAWN IN 3D	1 7 02

11- 20ma A

2x theta

ELECTRU—UPTICAL	CHARACTERIS	IICS IA=Z		f = ZUMA		
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND	
PEAK WAVELENGTH		565		nm		
FORWARD VOLTAGE		2.2	2.6	Vf		
REVERSE VOLTAGE	5.0			٧r	1 _r =100,uA	
AXIAL INTENSITY		10		mcd	If = 20mA	

110

EMITTED COLOR: GREEN EPOXY LENS FINISH: GREEN DIFFUSED

VIEWING ANGLE

FLECTOR ADTICAL CHARACTERISTICS TA-45'A

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	25	mA
POWER DISSIPATION	105	mW
DERATE FROM 25°C	-1.2	mW/ ' C
OPERATING, STORAGE TEMP.	-40 TO +85	°C
SOLDERING TEMP.	+ 260	•C
2.0mm FROM BODY		3 SEC. MAX

* t<10µS

NOTES:

- 1. SSL-LX2573GD, GREEN LED.
- 2. SSH-LXMP059-HSG, BLACK HOUSING.
- 3. SSH-LXMP059-BSG, BLACK BUSHING.

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.039). MIN=+DECIMAL PRECISION

REV. PART NUMBER SSI-LXMP059GD

565nm GREEN RECTANGULAR PANEL INDICATOR. GREEN DIFFUSED LENS.

CONFIDENTIAL INFORMATION THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

1,25~3,00 [0,049~0,118]

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 US WEB: www.lumex.com

TW WEB: www.lumex.com.tw

APPROVED BY: DATE: DRAWN BY: CHECKED BY: 8.18.93 PAGE: 1 OF 1 SCALE: N/A