

PART NUMBER SSI-LXMP059YD

C

REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
Α	ADDED DIMS, NOTES AND UPDATED SPECS.	12.19.94
В	E.C.N. #10122.	6.27.96
С	E.C.N. #10BRDR. & REDRAWN IN 3D.	1.7.02

ELECTRO-OPTICAL C	HARACTERIS	STICS TA=25	5 ' C	$I_f = 20mA$	
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		585		nm	
FORWARD VOLTAGE		2.1	2.5	٧f	
REVERSE VOLTAGE	5.0			v_r	1 _r =100µA
AXIAL INTENSITY		10		mcd	$I_f = 20 \text{mA}$
VIEWING ANGLE		110		2x theta	
EMITTED COLOR:	YELLOW				
EPOXY LENS FINISH:	YELLOW	DIFFUSED			

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	30	mA
POWER DISSIPATION	105	mW
DERATE FROM 25°C	-1.2	mW/'C
OPERATING, STORAGE TEMP.	-40 TO +85	° C
SOLDERING TEMP.	+ 260	° C
2.0mm FROM BODY		3 SEC. MAX

* t<10µS

NOTES:

- 1. SSL-LX2573YD, YELLOW LED.
- 2. SSH-LXMP059-HSG, BLACK HOUSING.
- 3. SSH-LXMP059-BSG, BLACK BUSHING.

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECIMAL PRECISION MIN= +DECIMAL PRECISION

PART NUMBER

C SSI-LXMP059YD

585nm YELLOW RECTANGULAR PANEL INDICATOR.

YELLOW DIFFUSED LENS.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

1,25~3,00 [0,049~0,118]

RELIABILITY NOTE
OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT
SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE.
PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com

US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY: CHECKED BY: APPROVED BY: DATE: 2.26.93
BC PAGE: 1 OF 1
SCALE: N/A