
UNCONTROLLED DOCUMENT



| PART NUMBER |
|-----------------|
| SSF-LXH100GD-01 |

E.C.N. NUMBER AND REVISION COMMENTS DATE CHG'D LEAD LENGTH. 10.2.93 UPDATED SPECS. 7.28.95 E.C.N. #10301. 1.30.97 E.C.N. #10BRDR. & REDRAWN IN 3D. 5.14.02

| ELECTRO-OPTICAL CH | ARACTER | ISTICS TA=25'C | ; | If = 20mA | |
|--------------------|---------|----------------|-----|-----------|-----------------------|
| PARAMETER | MIN | TYP | MAX | UNITS | TEST COND |
| PEAK WAVELENGTH | | 565 | | nm | |
| FORWARD VOLTAGE | | 2.2 | 2.6 | ٧f | |
| REVERSE VOLTAGE | 5.0 | | | V_r | 1 _r =100µA |
| AXIAL INTENSITY | | 30 | | mcd | $I_f = 20mA$ |
| VIEWING ANGLE | | 60 | | 2x theta | |
| EMITTED COLOR: | GREEN | | | | |
| EPOXY LENS FINISH: | GREEN | DIFFUSED | | | |

■ LIMITS OF SAFE OPERATION AT 25°C

| PARAMETER | MAX | UNITS |
|--------------------------|-------------|------------|
| PEAK FORWARD CURRENT* | 150 | mA |
| STEADY CURRENT | 25 | mA |
| POWER DISSIPATION | 105 | mW |
| DERATE FROM 25°C | -1.2 | mW/°C |
| OPERATING, STORAGE TEMP. | - 40 TO +85 | . C |
| SOLDERING TEMP. | + 260 | ° C |
| 2.0mm FROM BODY | | 3 SEC. MAX |
| * 141D.C | | |

^{*} t<10µS

NOTES:

- 1. SSL-LX509F3GD, GREEN LED.
- 2. SSH-LXH100, BLACK HOLDER.

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN=+DECIMAL PRECISION MAX.=+0.00 -0

REV.

PART NUMBER SSF-LXH100GD-01

ANDDE

T-5mm (T-1 3/4) LED, RIGHT ANGLE FAULT INDICATOR, 565nm GREEN LED, GREEN DIFFUSED LENS.

<u>CONFIDENTIAL INFORMATION</u>
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



BC

290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790

US WEB: www.lumex.com TW WEB: www.lumex.com.tw

DRAWN BY:

CHECKED BY: APPROVED BY: DATE: 7.16.93 PAGE: 1 OF 1 SCALE: N/A