

# SMD Oscillators- HCSL Output 5.0 x 3.2 x 1.2 mm CX Series



## Features


- 3.3V and 2.5V operation available.
- HCSL output, output frequencies 25 MHz to 200 MHz.
- Excellent low phase noise and jitter.
- Tri-State function available.
- PCI-Express, SAS, SATA and other high-Speed interface applications.
- RoHS Compliant / Pb Free.

## Electrical Specifications

Item / Type	CX
Output Type	HCSL
Output Load	50 Ω
Oscillation Mode	3rd Overtone
Supply Voltage	2.5 V , 3.3 V
Frequency Range	25 MHz to 200 MHz
Overall Frequency Stability *	± 50 ppm
Operating Temperature Range	- 40 ~ + 85 °C
Storage Temperature Range	- 55 ~ + 125 °C
Voltage Vol ( Typ. ) / Voh ( Typ. )	0 mV / 740 mV
Rise ( Tr ) / Fall ( Tf ) Time ( 20 % ~ 80 % )	0.5 nS Max.
Supply Current	30 mA Max.
Symmetry	45 ~ 55 %
Start-up Time	10 mS Max.
Phase Jitter ( 12 KHz ~ 20 MHz )	0.2 pS Typ. , 1.0 pS Max.


\* Inclusive of frequency tolerance at 25 °C, variation over temperature, supply voltage variation, aging and vibration.

## Dimensions



- PAD FUNCTION:
- 1: ENABLE CONTROL or NC
  - 2: ENABLE CONTROL or NC
  - 3: GND
  - 4: OUT
  - 5: OUTN
  - 6: VDD

\*: External high frequency power supply decoupling required.



Units: mm

Remark : Specification subject to change without prior notice. Please confirm with our sales.